CEILING MOUNTS

FEATURES

2

INDEPENDENT ROLL, PITCH AND YAW

For quick and precise projector registration.

MULTIPLE INSTALLATION OPTIONS Mounting options include: flush mount to ceiling, use 0.5" (12.7 mm) threaded rods or use a 1-1/2" NPT threaded extension column.

QUICK CONNECT/DISCONNECT

Convenient lamp and filter access on most projectors. Disconnecting maintains registration and doesn't affect pre-set adjustments.

CABLE MANAGEMENT

Route cables through top of mount without additional accessories.



Touchboar

205 Westwood Ave, Long Branch, NJ 07740 Phone: 866-94 BOARDS (26273) / (732)-222-1511

SPECIFICATIONS	
Roll	±5°
Pitch	±20°
Yaw	360°
Dimensions* (HxWxD)	3.8 x 17 x 9.3" (97 x 432 x 235 mm)
Color	Black
Weight Capacity	250 lbs (113.4 kg)

* Dimensions don't include interface bracket

TECHNICAL DRAWINGS

17.36"

(441 mm)

Λ

о

о

(206 mm) >

16.25" (413 mm) 4.5″

(114 mm)

9'

(229 mm)

11⁄2″ NPT

Threads

3.97

(101 mm)

8.13"

0

0

ο

9.86"

(250 mm)

.

6.04"

(153 mm)

0

WHAT YOU NEED TO KNOW

ABOUT VCM

- · Industry-first microadjustable independent roll
- Three mounting methods
- Ships fully assembled with everything you need for installation in one box
- · Compatible with a wide array of accessories
- Available in universal and custom options



RECOMMENDED ACCESSORIES



For a complete list of projector mount accessories see page 21.





ố 💿 🁌



