

VELP Scientifica Solutions for JAR/Leaching Test



JLT 4



JLT 6



FC4S



FC6S



FP4

Number of positions	4	6	4	6	4 (portable)	
Independent positions			•	•		
Speed settings rpm	from 10 to 300	from 10 to 300	10-15-30-45-60-90-120-150-200-300	10-15-30-45-60-90-120-150-200-300	20-40-50-100-200	
Time settings	0÷999 minutes	0÷999 minutes	-	-	0÷30 minutes	
	0÷99 hours	0÷99 hours	-	-	-	
	continuous	continuous	continuous	continuous	continuous	
Disconnectable light	backlight	backlight	backlight	backlight	central light	
Dimensions (WxHxD) mm	645x347x260	935x347x260	645x347x260	935x347x260	250x320x250	
	(in)	(25.4x13.7x10.2)	(36.8x13.7x10.2)	(25.4x13.7x10.2)	(9.8x12.6x9.8)	
Weight	Kg	13.0	17.0	12.5	18.0	4.8
	(lb)	(28.6)	(37.4)	(27.5)	(39.6)	(10.6)
Power Supply	100÷240 V	100÷240 V	100÷240 V	100÷240 V	100÷240 V	
Power	11 W	19 W	18 W	23 W	6 W	



www.velp.com