



PW

Overhead Stirrers

Powerful overhead stirrer with 120 Ncm torque
ideal for stirring high viscosity applications



Resistant and Easy-to-Use

The PW is an intuitive overhead stirrer ensuring safety with overload, over-current and overheating protection.

- Maximum torque of 120 Ncm
- Supports applications with a maximum viscosity of 100 000 mPa*s
- Electronic speed regulation from 20 to 1200 rpm, up to 70 L
- Long life, robust motor
- Easy-chuck to change the shafts without tools
- Automatically stops if blocked – no burn-out or damage
- Overload, overcurrent and overtemperature protection
- Sealed to IP 40 standard



INSTRUMENT - CODE

PW

110-230 V / 50-60 Hz

F201A0150

TECHNICAL DATA

CONSTRUCTION MATERIAL	Technopolymer and epoxy painted aluminum alloy
CHUCK RANGE	1 - 10 mm
ELECTRONIC PROTECTION RATING CEI EN 60529	IP 40
ELECTRONIC SPEED REGULATION	From 20 to 1200 rpm
STIRRING VOLUME MAX (H2O)	Up to 70 L
MAX VISCOSITY	100 000 (mPa*s)*
TORQUE MAX	120 Ncm
ALLOWED ROOM TEMPERATURE	From 0 to 40 °C
DIMENSION (WXHXD)	80x230x196 mm (3.1x9x7.7 in)
POWER	190 W
WEIGHT	2.9 Kg (6.4 lb)



We reserve the right to make technical alterations
We do not assume liability for errors in printing, typing or transmission

VELP Official Partner

DESIGNED AND MANUFACTURED IN ITALY



ITALY - HQ
Via Stazione 16
20865 Usmate (MB) Italy
Tel. +39 039 628811
velpitalia@velp.com

INDIA
velpindia@velp.com

USA
155 Keyland Court, Bohemia
NY 11716 - U.S.
Tel. +1 631 573 6002
velpusa@velp.com

CHINA
Xinlong Rd Building 28, Lane 1333
Shanghai city - China
Tel. +86 180 1755 7329
velpchina@velp.com