

## Key Features

Enhanced Touchscreen Performance | Immersive Stereo

Sound | myViewBoard™ Annotation Software | ViewBoard



Cast Content Sharing Software | SmartPort USB™



## Product Description

Featuring 4K Ultra HD resolution and an advanced, next-generation touchscreen, the ViewSonic® ViewBoard® IFP6550 delivers incredible collaborative capabilities for 21st century boardrooms and classrooms. With integrated myViewBoard® annotation software and ViewBoard Cast streaming software, content creation and sharing has never been easier. What's more, this ENERGY STAR certified display delivers optional slot-in PC capability for more computing-intensive interactive applications. A VESA-compatible design allows for installation on a wall mount, or on an optional trolley cart for more flexible installation in classrooms and meeting rooms.

For more detailed information on how ViewSonic ViewBoards can best be utilized in a school environment, see our [ViewBoard FAQs](#).



65"  
DISPLAY

RESOLUTION

20-Point  
TOUCH  
INTERACTIVE

### Contact Sales

- call: 888.881.8781
- email: [salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)
- visit: [viewsonic.com](http://viewsonic.com)

#### Display:

Display Size (in.):	65
Viewable Area (in.):	65
Light Source:	LED
Resolution:	3840 x 2160
Aspect Ratio:	16:9
Static Contrast Ratio:	1,200:1
Backlight Life (Hours):	50,000
Brightness:	350 cd/m2
Response Time (Typical GTG):	8ms
Viewing Angles:	178° horizontal, 178° vertical
Panel Surface:	Anti-glare 7H tempered glass

#### Networking:

Ethernet LAN:	10/100/1000 Mbps
---------------	------------------

#### Embedded Player:

OS:	Embedded ViewBoard OS
GPU:	ARM Mali450 Quad Core
CPU:	ARM Dual Core Cortex A73
CPU Processor Speed:	1.2GHz
Memory:	2GB
Storage:	16GB
Interface:	OSD / Remote Control / Annotation overlay

#### Audio:

Internal Speakers:	10W (x2)
Subwoofer:	15W (x1)

#### Connector:

HDMI 2.0(3), HDMI Out(1), VGA(1), Composite RCA(1), 3.5mm Audio In(1), 3.5mm Audio Out(1), SPDIF Audio Out(1), USB 3.0(2), USB 2.0(4), Slot-in PC Slot(1), USB B Touch Port(2), RS232(1), Ethernet LAN (RJ45)(1), WIFI Module Slot(1)

#### Power:

Voltage:	100-240 VAC
Consumption (typical):	350W
Stand-by:	<.5W

#### Controls:

On Screen Display:	Input, Volume, Backlight, Audio, Screen, Display, Adjust
Remote Control:	Volume, Channel, Source, Mute, Back, Input, Menu

#### Operating Conditions:

Temperature:	32-104° F (0 - 40° C)
Humidity (non-condensing):	10-90%

#### Touch:

Touch Technology:	Infrared
Touch Points:	20-Point Touch
Tip Detection:	Dual tips, 3mm and 8mm

#### Weight (imperial):

Net (lbs):	88.9
Gross (lbs):	102.6

#### Weight (metric):

Net (kg):	40
Gross (kg):	47

#### Dimensions (imperial) (WxHxD):

Packaging (in.):	65.7 x 39.8 x 8.8
Physical (in.):	58.6 x 35.3 x 3.5

#### Dimensions (metric) (WxHxD):

Packaging (mm):	1669.0 x 1010.0 x 223.0
Physical (mm):	1488.0 x 897.0 x 90.0

#### Mount:

VESA Compatible:	600 x 400 mm
------------------	--------------

#### Additional Hardware:

Camera Mounting Bracket:	1
--------------------------	---

#### General:

Warranty: 3-year limited warranty on parts, labor and backlight, onsite warranty

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

PACKAGE CONTENTS: IFP6550 display, stylus pen x 2, power cable, HDMI cable, USB cable, AV cable, remote control with batteries, Camera plate, M8 screw x 8, Quick Start Guide

Regulations: cTUVus, FCC, ENERGY STAR, Mexico Energy, CE, CB, RoHS, ErP, WEEE

UPC: 766907912814

#### Accessories:

Intel Unite, LB-PEN-002, LB-WIFI-001, NMP660, PD-IFP-001, PD-IFP-002, PD-IFP-003, PD-IFP-004, STND-047, SW-071, SW-072, SW-072-2, SW-073, SW-073-2, SW-074, SW-074-2, SW-075, SW-075-2, SW-101, SW-110, SW-111, SW-UP-117, VB-BLF-002, VB-BLF-005, VB-BLM-002, VB-BLM-005, VB-BLW-002, VB-BLW-005, VB-BWS-001, VB-BWS-004, VB-CAM-001, VB-EBL-001, VB-EBS-001, VB-EBT-001, VB-EBV-001, VB-EBW-001, VB-STND-001, VB-STND-002, VB-STND-003, VB-STND-004, VB-STND-005, VB-VIS-001, VB-WKB-001, VBD100, VBH100, VBS100, VPC15-WP-4, VPC15-WP-6, VPC16-WP-4, VPC17-WP-6, WMK-047-2, WMK-071