Key Features

Bright Images in any Environment | Large Images in Small Spaces | Long-lasting Laser Phosphor Light Source | Horizontal and Vertical Keystone Correction | Compatible with Interactive Whiteboard Module



Product **Description**

Featuring 1024x768 XGA resolution and 3,200 lumens of brightness, the ViewSonic LS625X short throw laser projector is an ideal projection solution for education environments. Designed with a laser phosphor light source lasting up to 20,000 hours, and a sealed optical engine with a waveform air filter that protects against dust and moisture, this projector delivers long-term, virtually maintenance-free usage for any classroom. With its 0.49 short throw ratio and horizontal/vertical keystoning, the LS625X makes installation a hassle-free experience. What's more, the short throw ratio allows you to place the projector just a few feet from a wall or screen to give you a huge image for less cost than a comparably sized display. Crestron and AMX certification delivers network management capabilities, while exclusive SuperColor™ technology offers a wide color range for true-to-life images in any classroom.




Projection Lens IR Řemote Sensor Focus/Zoom Rings RS-232 LAN

USB 5V/2A Out 12V Trigger AC In HDMI Monitor Out

 12 0 14 15 16 17. Composite Control Panel

S-Video Mini USB Kensington® Lock Slot Audio In/Out


Computer In



1024 x 768 RESOLUTION



3,200 ANSI **LUMENS**



0.49 **THROW RATIO**

Display:

Type:	DLP Laser			
Resolution Type:	XGA (1024x768)			
Resolution:	1024 x 768			
Brightness (Lumens):	3,200 ANSI			
Display Size (in.):	60 - 300 in. / 1.5 - 7.6 m			
Throw Distance:	2.1 - 10.4 ft / 0.6 - 3.2 m			
Throw Ratio:	0.49			
Keystone:	Vertical (+/- 40°)			
Lens:	Fixed Zoom			
Light Source Life, Normal (hours):	20000			
Light Source Life, Dynamic Eco- Mode (hours):	20000			
Color Depth:	1.07B Color (R/G/B 10bit)			
Aspect Ratio:	4:3			
Video Signal:				
Frequency Horizontal:	15K~102KHz			

Frequency Vertical: 23~120Hz

Compatibility:

PC Resolution (max): 1920 x 1080 Mac® Resolution (max): 1920 x 1080

Connector:

Ethernet LAN (RJ45)(1), 3.5mm 12V Trigger(1), 3.5mm Audio Out(1), 3.5mm Audio In(1), Control (RS232)(1), HDMI 1.4(1), HDMI 1.4 (with HDCP 1.4)(1), VGA In(2), VGA Out(1), Composite RCA Video In(1), S-Video In(1), Mini USB(1)

Audio:

)W (x1)			
Power:			
)5W			
0.5W			
)			

Controls:

Power, keystone/arrow keys, left/blank, menu/exit, Physical Controls: right/panel key lock, mode/enter, auto, source Display, Image, Power

Management, Basic, Advanced, System, On Screen Display: Information (See user quide for full OSD functionality)

Operating Conditions:

Temperature:	32-104° F (0 - 40° C)
Humidity (non-condensing):	0-90%
Additional Hardware:	
Kensington Lock Slot:	1
Weight (imperial):	

weight (impenal):

Weight (metric):		
	Gross (lbs):	15.4
	Net (lbs):	13.6

weight (metric):

Net (kg): 6.2 Gross (kg):

Dimensions (imperial) (WxHxD):

Packaging (in.): 19.1 x 9.4 x 15.4 Physical (in.): 15.1 x 5.8 x 11.5

Dimensions (metric) (WxHxD):

Packaging (mm): 485.0 x 238.0 x 390.0 Physical (mm): 383.0 x 147.0 x 291.0

General:

AV Control: AMX Certified, Crestron Certified, PJ Link Certified

Regulations: FCC, cTUVus, ROHS

PACKAGE CONTENTS: LS625X projector, power cable, VGA cable, remote control, Quick Start Guide

Warranty: Three-year limited warranty on parts and labor, 1-year limited warranty on the light source, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration).

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

UPC: 766907979916

Accessories:

HB10B, IFP2710, PGD-350, PJ-IWBADP-008, PJ-SCW-1001W, PJ-VTOUCH-10S, PJ-WMK-305, VC10, VCB10