

Key Features


Bright Images in any Environment | Long-lasting Laser Phosphor Light Source | One-Wire HDBT® Input | 360-Degree Orientation | Portrait Mode Projection



Product Description

Bright and versatile for any professional installation, the ViewSonic® LS900WU WUXGA laser projector delivers everything you need for big screens in big venues. Delivering 6,000 lumens of advanced high brightness, 100,000:1 contrast ratio, and up to 30,000 hours* of light source life, this projector is ideal for auditoriums, lecture halls, large boardrooms, houses of worship, and more. Thanks to SuperColor™ technology, content is brought to life with captivating color, crisp graphics, and stunning videos no matter the environment. This top-notch performer is also easy to deploy and manage with its wide 1.65x optical zoom adjustment, vertical/horizontal keystone, 4 corner adjustment, and a vertical/horizontal lens shift feature that provide extreme flexibility in even the most challenging installations. Thanks to the built-in HDBT receiver, the projector is capable of receiving uncompressed HD video and audio from over 200 feet away via network cable. Moreover, 360-degree tilt angle projection, portrait mode, and 24/7 operation allow for extreme mounting flexibility. The ViewSonic® LS900WU is the ideal WUXGA laser projector for professional installations, large venues, and business and education environments.

*Light source life may vary based on actual usage and other factors.




01 Lens
02 Lens Sensor
03 Feet
04 Controls

05 Lens Shift
06 VGA In
07 HDMI (x3)
08 LAN
09 AC In

10 HDBT
11 RS232
12 Audio Out
13 Monitor Out
14 Video

15 3D Sync
16 USB 2.0 Type A
17 USB Mini B
18 Kensington Lock Slot
19 Audio In (R/L)


20 Audio In / Mic In
21



1920 x 1200
RESOLUTION



6,000 ANSI
LUMENS



1.2 - 1.9
THROW RATIO

Display:

Type:	DLP Laser
Resolution Type:	WUXGA (1920x1200)
Resolution:	1920 x 1200
Brightness (Lumens):	6,000 ANSI
Display Size (in.):	50 - 300 in. / 1.27 - 7.62 m
Throw Distance:	4.0 - 24.4 ft / 1.24 - 7.43 m
Throw Ratio:	1.2 - 1.9
Keystone:	Vertical (± 25°) / Horizontal (± 30°)
Lens:	1.65x optical zoom
Light Source (watt):	Laser bank x 4
Light Source Life, Normal (hours):	20000
Light Source Life, Dynamic Eco-Mode (hours):	30000
Color Depth:	1.07B Color (R/G/B 10bit)
Dynamic Contrast Ratio:	100,000:1
Aspect Ratio:	16:10
Lens Shift:	Horizontal (-2.5% +2.5%) / Vertical (-2.4% +9.2%)

Video Signal:

Frequency Horizontal:	15K~102KHz
Frequency Vertical:	23~120Hz

Compatibility:

PC Resolution (max):	1920 x 1200
PC Resolution (min):	640 x 480
Mac® Resolution (max):	1920 x 1200
Mac® Resolution (min):	640 x 480

Connector:

USB 2.0 Type A(1), Ethernet LAN (RJ45)(1), 3.5mm Audio Out(1), 3.5mm Audio In(1), Control (RS232)(1), HDMI(3), VGA In(1), VGA Out(1), Composite RCA Video In(1), Mini USB(1), RCA Audio In (L/R)(1), RCA Audio Out(1), 3D VESA(1), HDBT(1)

Audio:

Internal Speakers:	5W (x2)
--------------------	---------

Power:

Voltage:	100-240V+/- 10%, 50/60Hz AC
Consumption (typical):	430W
Stand-by:	<0.5W

Controls:

Physical Controls:	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, mode/enter, auto, source
On Screen Display:	Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)

Operating Conditions:

Temperature:	32-104° F (0 - 40° C)
Humidity (non-condensing):	0-90%

Additional Hardware:

Kensington Lock Slot:	1
-----------------------	---

Weight (imperial):

Net (lbs):	24.2
Gross (lbs):	30.0

Weight (metric):

Net (kg):	11.0
Gross (kg):	13.6

Dimensions (imperial) (WxHxD):

Packaging (in.):	22.0 x 11.9 x 18.5
Physical (in.):	14.2 x 6.3 x 17.3

Dimensions (metric) (WxHxD):

Packaging (mm):	559.0 x 301.0 x 469.0
Physical (mm):	360.0 x 161.0 x 440.0

General:

Regulations: FCC, UL/CUL, ROHS

PACKAGE CONTENTS: LS900WU projector, power cable, VGA cable, remote control, Quick Start Guide

Warranty: Five-year limited warranty on parts and labor, 1-year limited warranty on the light source, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration).

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

UPC: 766907001242

Accessories:

IFP2710, PGD-350, PJ-SCW-1001W, PJ-WMK-006, PJ-WMK-007, PM-FCP, VC10, VCB10

Awards:

