multimedia content.


# Key Features

360-degree projection with Smart Stand Dual Harman Kardon Speakers | USB Type-C for Video and Power | Built-in Battery and 16GB Internal Storage | Advanced LED Light Source

Product Description

The ViewSonic® M1 is an ultra-portable LED projector that delivers convenient entertainment in nearly any room. With a built-in battery and over 30,000 hours of operational life, this projector will deliver years of multimedia entertainment wherever it goes. Weighing less than two pounds, the M1's compact and lightweight design makes it ideal for moving from room to room, or for indoor/outdoor usage. An integrated smart stand provides for simple 360-degree setup, while also doubling as a lens cover. Once the lens is uncovered, the projector automatically powers on with full brightness for instant entertainment. A built-in safety feature temporarily turns off the lens when objects are detected too close to the projector. Dual Harman Kardon speakers provide crisp and clear sound for multimedia content, while a short throw lens can display large images in small spaces. What's more, versatile connectivity options include a MicroSD card slot, USB Type-A, and USB Type-C – making the M1 a great option for sharing and displaying videos and other







HDMI

1.4

Out

Menu

Controls

DC

In

Stand

Focus

Ring

Remote

Sensor



Speakers

Display:

Display.	
Type:	DLP LED
Resolution Type:	WVGA (854x480)
Resolution:	854 x 480
Brightness (Lumens):	250
Display Size (in.):	24 - 100 in. / 0.6 - 2.54 m
Throw Distance:	40 in / 1.0 m
Throw Ratio:	1.2
Keystone:	Vertical (+/- 40°)
Lens:	Fixed Zoom
Light Source Life, Normal (hours):	30000
Color Depth:	1.07B Color (R/G/B 10bit)
Dynamic Contrast Ratio:	120,000:1
Aspect Ratio:	16:9
Video Signal:	
Frequency Horizontal:	15h~135kHz
Frequency Vertical:	23~120Hz
Compatibility:	
PC Resolution (max):	1920 x 1080
PC Resolution (min):	640 x 480
Mac® Resolution (max):	1920 x 1080

### USB 2.0 Type A(1), USB 3.1 Type C(1), Card Reader(Micro SD), 3.5mm Audio Out(1), HDMI 1.4(1)

**Connector:** 

Mac® Resolution (min):

Audio: Internal Speakers: 3W(x2)

640 x 480

key lock, mode/enter,

32-104° F (0 - 40° C)

0-90%

## Power:

i owei.	
Voltage:	100-240 VAC
Consumption (typical):	55W
Stand-by:	<0.5W
Controls:	
Physical Controls:	Power, keystone/arrow keys, left/blank, menu/exit, right/panel

	auto, source
On Screen Display:	Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)
<b>Operating Conditions:</b>	

### Temperature: Humidity (non-condensing):

Weight (imperial):		
Net (lbs):	1.7	
Gross (lbs):	3.7	
Weight (metric):		
Net (kg):	0.8	
Gross (kg):	1.7	
Dimensions (imperial) (WyHyD)		

umensions (imperial) (wxHxD): Packaging (in.): 16.0 x 9.2 x 15.0 5.7 x 1.6 x 5.0

### Physical (in.):

Dimensions (metric) (WxHxD):

Packaging (mm): 406.0 x 233.0 x 380.0 146.0 x 40.0 x 126.0

## Physical (mm):

**General:** Regulations: FCC, cTUVus, ROHS, TUV-S, NOM, UL2054

PACKAGE CONTENTS: M1 Projector, Power Cable, USB Type C Cable, Remote Control, Projector Case, Quick Start Guide

Warranty: Three-year limited warranty on parts and labor, 1-

year limited warranty on the light source, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration). Recycle/Disposal: Please dispose of in accordance with

local, state or federal laws. UPC: 766907000658

### **Accessories:**

PGD-350, PJ-CASE-010, PRJ-EE-05-03, PRJ-EEEW-07-01, PRJ-

EEEW-07-02, PRJ-EW-07-01, PRJ-EW-07-02, VC10

**Awards:** 







