

Ultra Short Throw Networkable XGA Projector

Advanced Connectivity for Classrooms and Boardrooms

PJD8333s



Shine big, bright and bold even in small spaces. Capable of projecting a 70" image from just 2.2 feet away, the ViewSonic® PJD8333s advanced networkable XGA ultra short throw projector delivers stunning images for classrooms and meeting spaces. Advanced features and extensive connectivity let users hit the ground running with plug-and-play PC-less USB presenting, or the ViewSonic mobile app on their Android™ or iOS device. IT easily keeps everything operating smoothly with integrated software for simplified remote management of multiple projectors throughout a campus or enterprise.

Key Features:

- XGA 1024x768 resolution
- Up to 3,000 lumens, and 15,000:1 contrast ratio
- Ultra short throw lens
- 1.6x optical zoom lens
- LAN control, wired & wireless LAN display, USB display, PC-less presentations
- Mobile app for smartphones & tablets

Designed for:

- Education
- Business

Touchboards

205 Westwood Ave, Long Branch, NJ 07740
Phone: 866-94 BOARDS (26273) / (732)-222-1511
Fax: (732)-222-7088 | E-mail: sales@touchboards.com

Ultra Short Throw Networkable XGA Projector

PJD8333s



Projection Distance	
Feet	Meters
1.9	0.6
2.5	0.8
3.1	1.0
3.7	1.1
4.7	1.4
6.2	1.9
7.8	2.4

Screen Size (4:3) Diagonal	
Inches	Meters
60	1.5
80	2.0
100	2.5
120	3.0
150	3.8
200	5.1
250	6.3

Specifications

DISPLAY	Type Resolution Lens Keystone Size Throw Distance Throw Ratio Lamp Light Life Brightness Contrast Ratio Aspect Ratio Color Depth Color Wheel	0.55" Digital Micromirror Device (DLP™) XGA 1024x768 (native) Fixed zoom / Manual optical focus Vertical digital keystone correction (+/- 40°) 60 – 250 in. / 1.52 – 6.35 m (diagonal) 1.6 – 6.6 ft. / 0.5 – 2.0 m 0.468:1 240 watt 3500 / 5000 / 7000 hours* (Normal / Eco-mode / DynamicEco™ Mode) 3000 lm 15,000:1 (DynamicEco Mode) 4:3 (native) 30 bits, 1.07B Color (10+10+10) 6-seg RGBCYW / 7200rpm	CONNECTOR (CONT)	Control LAN USB DC 12V Trigger	RS232 (DB-9) RJ45 Type A (card reader and wireless dongle) Type B (mouse control and service) Mini Type B (USB display) 3.5mm plug 12V/1A
INPUT SIGNAL	Computer and Video Frequency	NTSC M(3.58MHz), 4.43MHz, PAL (B, D, G, H, I, M, N, 60), SECAM (B, D, G, L, L1), SD 480i and 576i, ED 480p and 576p, HD 720p, 1080i, 1080p Fh: 31–100KHz, Fv: 24–120Hz	AUDIO	Speaker	16-watt (x1)
COMPATIBILITY	PC Mac	VGA to 1600x1200 UXGA Up to WUXGA (may require MAC adapter)	NOISE LEVEL	Normal / Eco-mode	34 dB / 32 dB
CONNECTOR	RGB Input RGB Output Digital Input Component Input Composite Input S-Video Input Audio Input Microphone Input Audio Output	15-pin mini D-sub (x2) 15-pin mini D-Sub HDMI 15-pin min D-sub (x2, shared with RGB) RCA jack 4-pin mini-DIN 3.5mm mini jack (x2) 3.5mm mini jack (shared with Audio 2) 3.5mm mini jack	POWER	Voltage Consumption	100–240VAC (Auto Switching), 50–60Hz (universal) 350W (max) / <0.5W (stand-by mode)
			CONTROLS	Basic OSD	Power, keystone/arrow keys, left, menu/exit, right, source, enter Display, Picture, Source, System Setup (Basic), System Setup (Advanced), Information (See user guide for full OSD functionality)
			OPERATING CONDITIONS	Temperature Humidity Altitude	32–104° F (0–40° C) 10–90% (non-condensing) 0–10,000 ft (3,048m)
			DIMENSIONS (W x H x D)	Physical Packaging	13.2 x 5.1 x 10.4 in. / 335 x 128.3 x 265 mm 15.0 x 13.5 x 9.5 in. / 383 x 342 x 242 mm
			WEIGHT	Net Gross	8.0 lbs. / 3.6 kg 12.5 lbs. / 5.7 kg
			REGULATIONS		CB, UL/cUL, FCC-B, NOM, KC, REACH, ErP, SVHC UL-Argentina, PSB, C-tick, SASO, CE, GOST-R, CCC, RoHS, WEEE, UkrSEPRO
			WARRANTY		3-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year free Express Exchange® service**

Optional Accessories

Replacement Lamp	RLC-090
3D Active Shutter Glasses	PGD-series
Wireless Presentation Gateway	WPG-series
Wireless USB Adapter	PJ-WPD-200
Carrying Case	PJ-CASE-009
Extended 5-Year Limited Warranty	PRJ-EW-07-02
Ultra Short Throw Mount	PJ-WMK-401
Short Throw Mount	WMK-027

What's in the box?

PJD8333s projector, power cable, VGA cable, remote control with batteries, carrying case, Quick Start Guide, ViewSonic Wizard DVD (with User Guide).



205 Westwood Ave, Long Branch, NJ 07740
Phone: 866-94 BOARDS (26273) / (732)-222-1511
Fax: (732)-222-7088 | E-mail: sales@touchboards.com



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by TUV NORD.

*Lamp life may vary based on actual usage and other factors. **One year free Express Exchange® service requires product registration. Programs, specifications and availability are subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. DLP® and DLP logo are registered trademarks of Texas Instruments and BrilliantColor™ is a trademark of Texas Instruments. HDMI, the HDMI Logo, and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. Copyright © 2015 ViewSonic Corporation. All rights reserved. [17620-02B-06/15]