



## Key Features

Stunning Resolution & Brightness | Bright Images in Any Environment | Long Lamp Life | Reduced Input Latency



## Product Description


For an incredible audiovisual experience at a great value, the ViewSonic® PX703HD projector delivers. Perfect for home entertainment, this projector features 3500 lumens, Full HD 1920x1080 native resolution, an intuitive, user-friendly design, and a sleek white chassis. Exclusive SuperColor™ technology offers a wide color gamut for beautiful image production in nearly any environment, while a 10W speaker delivers incredibly clear and audible sound. An ultra-low input latency provides faster frame-by-frame action, while a Sports Mode feature delivers stunning detail so you can enjoy fast-action sports on the big screen. Full HD 3D compatibility lets you enjoy 3D movies and games. What's more, an energy-saving SuperEco® feature reduces power consumption and extends the lamp life by up to 15,000 hours.\* With a shorter throw ratio, 1.3x optical zoom, smart design, and extensive connectivity, the PX703HD provides flexible and quick set-up in any home.



1920 x 1080  
**RESOLUTION**



3,500 ANSI  
**LUMENS**



1.13-1.47  
**THROW RATIO**

### Display:

Type:	DLP LED
Resolution Type:	HD (1920x1080)
Resolution:	1920 x 1080
Brightness (Lumens):	3,500 ANSI
Display Size (in.):	30 - 300 in. / 0.76 - 7.62 m
Throw Distance:	2.4 - 32.0 ft / 0.7 - 9.8 m
Throw Ratio:	1.13-1.47
Keystone:	Vertical (+/- 40°)
Light Source (watt):	203
Light Source Life, Normal (hours):	5000
Light Source Life, Dynamic Eco-Mode (hours):	20000
Color Depth:	1.07B Color (R/G/B 10bit)
Aspect Ratio:	16:9

### Video Signal:

Frequency Horizontal:	15K-102KHz
Frequency Vertical:	23-120Hz

### Compatibility:

PC Resolution (max):	1920 x 1080
PC Resolution (min):	640 x 480
Mac® Resolution (max):	1920 x 1080
Mac® Resolution (min):	640 x 480

### Connector:

USB 2.0 Type A(1), 3.5mm Audio Out(1), 3.5mm Audio In(1), Control (RS232)(1), HDMI 1.4(1), HDMI 1.4 (with HDCP 1.4)(1), VGA In(1), VGA Out(1)

### Audio:

Internal Speakers:	10W (x1)
--------------------	----------

### Power:

Voltage:	100-240 VAC
Consumption (typical):	300W
Stand-by:	<0.5W

### Controls:

On Screen Display:	Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)
--------------------	--

### Operating Conditions:

Temperature:	32-104° F (0 - 40° C)
Humidity (non-condensing):	0-90%

### Additional Hardware:

Kensington Lock Slot:	1
-----------------------	---

### Weight (imperial):

Net (lbs):	5.8
Gross (lbs):	8.3

### Weight (metric):

Net (kg):	2.6
Gross (kg):	3.8

### Dimensions (imperial) (WxHxD):

Packaging (in.):	16.3 x 6.6 x 11.7
Physical (in.):	12.3 x 8.7 x 4.3

### Dimensions (metric) (WxHxD):

Packaging (mm):	415.0 x 168.0 x 297.0
Physical (mm):	312.0 x 222.0 x 108.0

### General:

Regulations: FCC, cTUVus, ROHS

PACKAGE CONTENTS: PX703HD projector, power cable, VGA cable, remote control, Quick Start Guide

Warranty: Three-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration).

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

UPC: 766907001778

### Accessories:

HB10B, IFP2710, PGD-350, PJ-CASE-008, PJ-SCW-1001W, PJ-WMK-006, PJ-WMK-007, VC10, VCB10