
Key Features


Dual-Point Optical Touch | SuperClear® MVA panel technology | Full HD1080p Resolution




Product **Description**

Great for public kiosks, POS displays, and other retail and commercial applications, the ViewSonic® TD2421 dual-point optical touch monitor lets users execute two-finger pinches, taps, and swipes for fast and intuitive navigation. With Full HD 1920x1080 resolution, 3000:1 static contrast ratio, and SuperClear MVA technology, the TD2421 delivers stunning brightness and contrast with amazing screen performance at nearly any viewing angle. Flexible connectivity options include HDMI, VGA, DVI, and USB ports, and a VESA-mountable design offers additional convenience for use as a wall-mounted display. What's more, ViewSonic's exclusive ViewMode feature provides intuitive presets that deliver optimized screen performance in different applications. In addition, Flicker-Free technology and a Blue Light Filter help to eliminate eye strain from extended viewing periods for improved productivity. Whether in retail or deployed in a high-traffic commercial setting, its scratch-resistant surface stands up to heavy use and safeguards its high quality touch experience.









24" DISPLAY	MVA PANEL	1920 x 1080 RESOLUTION

Display:	
Display Size (in.):	24
Viewable Area (in.):	23.6
Resolution:	1920 x 1080
Static Contrast Ratio:	3,000:1
Dynamic Contrast Ratio:	50,000,000:1
Brightness:	250 cd/m2
Backlight Life (Hours):	40,000
Response Time (Typical GTG):	5ms
Panel Type:	MVA
Colors:	16.7M
Viewing Angles:	178° horizontal, 178° vertical
Light Source:	LED
Panel Surface:	6H Scratch Resistant Surface Hardness
Aspect Ratio:	16:9
Compatibility:	
PC Resolution (max):	1920 x 1080
Touch:	
Touch Technology:	Optical
Touch Points:	2-Point Touch
Connector:	
USB 2.0 Type A(2), USB 2.0 Type B(2)	1), VGA(1), HDMI 1.4(1), DVI-I(1)
Audio:	
Internal Speakers:	2W (x2)
Video Signal:	
Frequency Horizontal:	Analog and Digital: 24 ~ 82KHz
Frequency Vertical:	Analog: 50 ~ 75Hz, Digital: 50 ~ 75Hz
Video Input:	
Analog Sync:	Analog: Separate Sync / Composite Sync / Sync on Green, Digital: TMDS
Power:	
Consumption (typical):	16.5W
Consumption (max):	28W
Voltage:	AC 100-240V (universal), 50-60Hz
Stand-by:	0.5W

mount:		
VESA Compatible:	100 x 100 mm	
Weight (metric):		
Gross (kg):	7.3	
Net (kg):	5.2	
Net Without Stand (kg):	4.3	
Weight (imperial):		
Net (lbs):	11.4	
Net Without Stand (lbs):	9.5	
Gross (lbs):	16	
Dimensions (metric) (WxHxD):		
Packaging (mm):	640 x 460 x 200	
Physical (mm):	571 x 392 x 240	
Physical Without Stand (mm):	571 x 340 x 58	
Dimensions (imperial) (WxHxD):		
Packaging (in.):	25.2 x 18.1 x 7.9	
Physical (in.):	22.5 x 15.4 x 9.5	
Physical Without Stand (in.):	22.5 x 13.4 x 2.3	
General:		
Regulations: cULus, FCC, ICES003, Energy Star, EPEAT Silver, UL-MX-CoC, Mexico Energy, CE, CB, RoHS Green BOM & RoHS DoC, ErP, REACH SVHC List & DoC, EEL, WEEE, EAC, TCO		
PACKAGE CONTENTS: LCD Display, Power Cable, VGA Cable, DVI Cable, USB2.0 Upstream Cable, Audio Cable, Quick Start Guide, ViewSonic Wizard CD-ROM		
Warranty: Three-year limited warranty on parts, labor and backlight		
Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.		
UPC: 766907851915		
Accessories:		
CB-00008187, CB-00009950, LCD-CA EEEW-24-01, TD-EEEW-24-02, TD-EW VSPF2360	ABLE-001, LCD-WMK-001, TD-EE-24-03, TD- /-24-01, TD-EW-24-02, TD-EW-24-03,	
Awards:		





GameMode, 1, 2, 3, 4, Power

compléte OSD functionality)

Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)

Ergonomics: Tilt (Forward/Back): 6° / 22°

Additional Hardware: Kensington Lock Slot:

Controls:

Physical Controls:

On Screen Display:

Operating Conditions: