Key **Features**

• OLED TECH : True Black with 1.07 Billion colors (10Bit)

ViewSonic Media VP16-OLED

- Real and Surreal : 100 % DCI-P3 Pantone
 Validated color coverage with Delta E < 2 as color quality guarantee
- Create Anywhere You Want : Tripod ready and foldable stand for outdoor shooting and indoor review
- Instant View : Camera ready (Micro HDMI) and USB-C charging that brings your creative workstation wherever you are
- Integrated hood : Foldaway hood attaches instantly when you need to eliminate ambient light



Product **Description**

Introducing industry-leading VP16-OLED with 1.07 Billion colors (10Bit). Merging what's real with the surreal, it boasts 100 % DCI-P3 Pantone Validated color coverage with Delta E < 2 as the color quality guarantee. Tripod-ready, VP16-OLED comes equipped with a foldable stand allowing you to perform your best in both indoor and outdoor settings. "Go dark" at any moment with a foldaway attachable hood that instantly eliminates any ambient light. Take your creative workstation no matter where you go and review the immediate results of your work, connecting your camera to the VP16-OLED via Micro HDMI and charging it effortlessly through USB-C connectivity.

Visit Us www.viewsonic.com

DISPLAY	10	VIDEO INPUT	
Display Size (in.):	16	Digital Sync:	TMDS - micro HDMI (v1.4), Micro- Packet - Type C
Viewable Area (in.):	15.6	ERGONOMICS	
Panel Type:	OLED Technology	Tilt (Forward/Back):	-60° / 20°
Resolution:	1920 x 1080	WEIGHT (IMPERIAL)	
Resolution Type:	FHD (Full HD)	Net (lbs):	2.2
Static Contrast Ratio:	100,000:1 (typ)	Net Without Stand (lbs):	2.2
Dynamic Contrast Ratio:	20M:1	Gross (lbs):	4.8
Brightness:	400 cd/m ² (typ)	WEIGHT (METRIC)	
Colors:	1.07B	Net (kg):	0.98
Color Space Support:	10 bit (8 bit + FRC)	Net Without Stand (kg):	0.98
Aspect Ratio:	16:9	Gross (kg):	2.2
Response Time (Typical Tr+Tf):	1ms	DIMENSIONS (IMPERIAL) (WXHXD)	
Viewing Angles:	170º horizontal, 170º vertical	Packaging (in.):	16.3 x 12.3 x 3.5
Backlight Life (Hours):	N/A Hrs (Min)	Physical (in.):	14.1 x 8.92~12.38 x 0.8
Curvature:	Flat	Physical Without Stand (in.):	14.1 x 8.9 x 0.2
Refresh Rate (Hz):	60	DIMENSIONS (METRIC) (WXI	HXD)
Blue Light Filter:	Yes	Packaging (mm):	415 x 312 x 90
	Adobe RGB: 112% size / 96% coverage (Typ) DCL-P3: 111% size / 100% coverage (Typ) EBU: 149% size / 100% coverage	Physical (mm):	359 x 226.682~314.48 x 19
		Physical Without Stand (mm):	359 x 227 x 6
		GENERAL	
Color Gamut:	(Typ) REC709: 150% size / 100% coverage (Typ) SMPTE-C: 163% size / 100% coverage (Typ) NTSC: 107% size (Typ)	Regulations:	cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, NRCan, NOM, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, UKCA, BSMI, BIS
	sRGB: 150% size / 100% coverage (Typ)		VP16-OLED x1, micro HDMI Cable (v1.4; Male-Male) x1, USB Type-C
Pixel Pitch:	0.179 mm (H) x 0.179 mm (V)	PACKAGE CONTENTS:	Cable (Male-Male) x1, USB Type-C Type-A 3.2 Gen1 Cable (Male-Male)
Surface Treatment:	Glare, Hard Coating (N/A)		x1, AC/DC Adapter x1, Quick Start Guide x1, Hood x1
COMPATIBILITY			Please dispose of in accordance wit
PC Resolution (max):	1920x1080	Recycle/Disposal:	local, state or federal laws.
Mac® Resolution (max):	1920x1080	Warranty:	*Warranty offered may differ from market to market
PC Operating System:	Windows 10/11 certified; macOS tested	Power Management:	Energy Star standards, EPEAT
Mac® Resolution (min):	1920x1080		
CONNECTOR			
USB 3.2 Type C Up Stream; DisplayPort Alt mode :	2 (40W power charger)		
3.5mm Audio Out:	1		
Micro HDMI 1.4 In:	1		
Power in:	USB Type C (with video & data)		
AUDIO			
Internal Speakers:	1Watts x2		
POWER			
Eco Mode (Conserve):	5W		
Eco Mode (optimized):	6W		
Consumption (typical):	7W		
Consumption (max):	15W		
,	AC 100-240V		
Voltage:			
Stand-by:	0.5W		
Power Supply:	External Power Adaptor		
CONTROLS			
Physical Controls:	Up, Down, Left/Return, Right/Confirmed, Power		
On Screen Display:	Input Select, Color Mode, ViewMode, Audio Adjust, Setup Menu		
OPERATING CONDITIONS			
Temperature:	32°F to 104°F (0°C to 40°C)		
Humidity (non-condensing):	20% to 90%		
INPUT SIGNAL			
Frequency Horizontal:	24 ~ 83KHz		
Frequency Vertical:	50 ~ 61Hz		