


Key **Features**


27" 10-point projected capacitive touch enabled LED monitor with Windows 8 Touch Certification to deliver best in class experience | VApanel technology with1920x1080 Full HD resolution to provide stunning image and picture quality for photography and entertainment | Advanced ergonomic stand designed for optimal touch experience | Versatile connectivity with DisplayPort, HDMI, and VGA | 7H scratch resistant surface hardness helps ensure high touch accuracy and



"ම් ්ර්duct **Description**

The ViewSonic TD2740 is an ideal solution for both commercial and consumer touch screen applications. With an intuitive 10-point multi-touch display and full 1080p HD resolution, the 27-inch TD2740 delivers a versatile solution for use in the office or at home, as well as for use as an information kiosk in public areas, or as a teaching tool in interactive learning environments. The bookstand support of the TD2740 provides advanced ergonomics and allows the display to be tilted or laid flat on a tabletop for more comfortable use. SuperClear VAtechnology with ultra-wide viewing angles and 20M:1 MEGA Dynamic Contrast Ratio bring greater definition and clarity to multimedia content. As a complete package, the display also includes a pair of integrated 2W speakers, anHD webcam, and a microphone for video chatting. VGA, HDMI, and DisplayPort inputs provide flexible and future-proof connectivity. Touch the Difference with the ViewSonic TD2740 interactive multi-touch display.













Display:

27 Display Size (in.): Panel Type: MVA Resolution: 1920 x 1080 Static Contrast Ratio: 3,000:1 Dynamic Contrast Ratio: 50,000,000:1 Light Source: LED Brightness: 260 cd/m2 Response Time (Typical GTG): 12ms

178º horizontal, 178º vertical Viewing Angles:

Backlight Life (Hours): 30,000

Panel Surface: 7H Scratch Resistant Surface Hardness

Compatibility:

PC Resolution (max): 1920 x 1080

Connector:

USB 2.0 Type A(2), 3.5mm Audio In(1), 3.5mm Audio Out(1), HDMI(2), VGA(1), HDMI 1.4(1), Display Port(1)

Touch:

Touch Technology: Capacitive Touch Points: 10-Point Touch

Audio:

Internal Speakers: 3W (x2)

Power:

Eco Mode (Conserve): 29W Eco Mode (optimized): 35W Consumption (typical): 41W Consumption (max): 52W

Voltage: AC 100-240V (universal), 50-60Hz

Additional Hardware:

Kensington Lock Slot: Webcam: 1MP

Controls:

Physical Controls: 1, 2, Down, Up, Power

Auto Image Adjust, Contrast/Brightness, Input Select, AudioAdjust, Color Adjust, Information, Manual Image Adjust,Setup Menu, Memory Recall (See user guide for completeOSD functionality) On Screen Display:

Operating Conditions:

Temperature: 32-104° F (0 - 40° C)

Humidity (non-condensing): 20-90%

Mount:

VESA Compatible: 100 x 100 mm

Video Signal:

Frequency Horizontal: 24~82kHz Frequency Vertical: 50~75Hz

Video Input:

Analog Sync: Separate Sync **Ergonomics:**

Tilt (Forward/Back): 15° / 70°

Weight (imperial):

Net (lbs): 19.4 Gross (lbs): 22.5

Weight (metric):

Net (kg): 8.2 Gross (kg): Dimensions (imperial) (WxHxD):

Packaging (in.):

29.1 x 20.1 x 5.0 Physical (in.): 26.5 x 16.5 x 2.0

Dimensions (metric) (WxHxD):

Packaging (mm): 739 x 510 x 127 Physical (mm): 672.6 x 418.9 x 49.9

General:

Regulations: cULus, FCC, ICES2003, UL-MX-CoC, Mexico Energy, CE, REACH, WEEE, UkrSEPRO

PACKAGE CONTENTS: TD2740 display, power cable, audio cable, VGA cable, HDMI cable, USB cable, Quick Start Guide, ViewSonic Wizard CD (available in some countries only)

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

Warranty: Three-year limited warranty on parts, labor and backlight

UPC: 766907719512

Accessories:

CB-00008187, LCD-CABLE-001, LCD-WMK-001, TD-EE-27-03, TD-EEEW-27-01, TD-EEEW-27-02, TD-EW-27-01, TD-EW-27-02, TD-EW-27-03, VSPF2700

Awards:



Copyright © ViewSonic Corporation 2000-2019. All rights reserved. (03/22/2019 09:23 AM PST)