Key **Features**

Frameless Design | VERSATILE CONNECTIVITY | Wide QUAD HD

RESOLUTION | Adaptive Sync

Product **Description**

The ViewSonic® VA2715-2K-MHD is a 27" WQHD monitor that delivers solid multimedia features at a great value with flexible connectivity, wide-angle viewing, and amazing screen performance. Featuring 2560 x 1440 resolution and a frameless design, this monitor provides a near-seamless viewing experience ideal for multi-monitor setups. Whether for working at the office, or enjoying entertainment at home, the VA2715-2K-MHD also features DisplayPort and HDMI ports for flexible connectivity to PCs, laptops, and other multimedia devices. In addition, a 3-year limited warranty, along with one of the industry's best pixel performance policies, makes the VA2715-2K-MHD a great overall value choice.

27"	MVA	2560 x 1440
DISPLAY	**PANEL**	**RESOLUTION**

Contact Sales

- call: 888.881.8781
- email: salesinfo@viewsonic.com
- visit: viewsonic.com

Display:

Display Size (in.):	27
Viewable Area (in.):	27
Panel Type:	MVA
Resolution:	2560 x 1440
Resolution Type:	WQHD (2560x1440)
Static Contrast Ratio:	4,000:1
Dynamic Contrast Ratio:	50,000,000:1
Light Source:	LED
Brightness:	250 cd/m2
Colors:	16.7M
Aspect Ratio:	16:9
Response Time (GTG w/OD):	5ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	30,000
Panel Surface:	Anti-glare, Hard coating (3H)
Refresh Rate (Hz):	75

Compatibility:

PC Resolution (max):	2560x1440
Mac® Resolution (max):	2560x1440

Connector:

3.5mm Audio Out(1), HDMI 1.4 In(2), DisplayPort(1)

Audio:

Internal Speakers:	2W (x2)

Power:

Eco Mode (Conserve):	19W
Eco Mode (optimized):	24W
Consumption (typical):	29W
Consumption (max):	31W
Voltage:	100-240 VAC, 50-60Hz
Stand-by:	0.5W
Power Supply:	External

Additional Hardware:

Kensington Lock Slot:	1

Controls:

Physical Controls:	U, R, D, L, EN (power)
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu

Operating Conditions:

Temperature:	32-104° F (0 - 40° C)
Humidity (non-condensing):	20-90%

Mount:

VESA Compatible:	100 x 100 mm

Video Signal:

Frequency Horizontal:	15 ~ 120KHz
Frequency Vertical:	24 ~ 75Hz

Ergonomics:

Tilt (Forward/Back):	5° / 20°

Weight (imperial):

Net (lbs):	7.9
Net Without Stand (lbs):	6.8
Gross (lbs):	11.0

Weight (metric):

Net (kg):	3.6
Net Without Stand (kg):	3.1
Gross (kg):	5.0

Dimensions (imperial) (WxHxD):

Packaging (in.):	27.1 x 17.6 x 5.0
Physical (in.):	24.1 x 18.0 x 8.1
Physical Without Stand (in.):	24.1 x 14.2 x 1.6

Dimensions (metric) (WxHxD):

Packaging (mm):	688.0 x 448.0 x 128.0
Physical (mm):	613.0 x 456.0 x 205.0
Physical Without Stand (mm):	613.0 x 361.0 x 40.0

General:

Regulations: RoHS, WEEE, BSMI, RCM, VCCI, PSE

PACKAGE CONTENTS: VA2715-2K-MHD x1, HDMI Cable (v1.4; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

Warranty: Three-year limited warranty on parts, labor and backlight

UPC: 766907014662

Accessories:

CB-00008948, CB-00009950, CB-00010555, CB-00010684, LCD-DMA-002, LCD-WMK-001