

Key **Features**

- Ergonomic flexibility with quickrelease stand
- vDisplay Manager productivity software for maximized multitasking
- Dual front facing speakers for clear audio
- HDMI, DisplayPort, VGA, and USB3.2 ports for extended connectivity
- 3-side narrow bezel for uninterrupted viewing



Product **Description**

The ViewSonic VG2240 is a 22" Full HD ergonomic business monitor designed to increase productivity and efficiency within the home and office workspace. Providing the full spectrum of ergonomic flexibility, the VG2240 can tilt, swivel, pivot, and height adjustment to adapt to any setup or workflow, while the built-in vDisplay Manager productivity software delivers efficient multi-tasking ability and streamlined display control. Dual front-facing speakers ensure a perfect audio-visual experience to provide teams with quality remote communication and collaboration. The beautifully designed display includes a 3-sided narrow bezel for uninterrupted viewing in multi-monitor display setups as well HDMI. DisplayPort, VGA, and USB3.2 connectivity. Complete with an easy-to-install quick release stand that reduces setup time to only a few minutes, the VG2240 offers a high-performance, purpose-built display solution designed for workspace productivity.



Visit Us — www.viewsonic.com

| DISPLAY | | OPERATING CONDITIONS | |
|------------------------------|---|--------------------------------------|--|
| Display Size (in.): | 22 | Temperature: | 32°F to 104°F (0°C to 40°C) |
| Viewable Area (in.): | 21.5 | Humidity (non-condensing): | 20% to 90% |
| Panel Type: | VA Technology | WALL MOUNT | |
| Resolution: | 1920 x 1080 | VESA Compatible: | 100 x 100 mm |
| Resolution Type: | FHD (Full HD) | INPUT SIGNAL | |
| Static Contrast Ratio: | 3,000:1 (typ) | Frequency Horizontal: | 24 ~ 82KHz |
| Dynamic Contrast Ratio: | 80M:1 | Frequency Vertical: | 50 ~ 75Hz |
| Light Source: | LED | VIDEO INPUT | TMD0_UDML(4.4) B0LE |
| Brightness: | 250 cd/m² (typ) | Digital Sync: | TMDS - HDMI (v1.4), PCI-E - DisplayPort (v1.2) |
| Colors: | 16.7M | Analog Sync: | Separate/Composite/SOG - RGB |
| Color Space Support: | 8 bit true | | Analog |
| Aspect Ratio: | 16:9 | ERGONOMICS | 130 |
| Response Time (Typical GTG): | 5ms | Height Adjust (mm): | |
| Response Time (GTG w/OD): | 5ms | Swivel: | 120° |
| Viewing Angles: | 178º horizontal, 178º vertical | Tilt (Forward/Back): | -5° / 40° |
| Backlight Life (Hours): | 30000 Hrs (Min) | Pivot (Right/Left): | 90° / 90° |
| Curvature: | Flat | WEIGHT (IMPERIAL) Net (lbs): | 11.5 |
| Refresh Rate (Hz): | 60 | Net (los). Net Without Stand (lbs): | 6.2 |
| Blue Light Filter: | Yes | . , | |
| Flicker-Free: | Yes | Gross (lbs): WEIGHT (METRIC) | 16.8 |
| Color Gamut: | NTSC: 72% size (Typ) | Net (kg): | 5.2 |
| Pixel Size: | sRGB: 103% size (Typ) 0.249 mm (H) x 0.241 mm (V) | Net Without Stand (kg): | 2.8 |
| Surface Treatment: | Anti-Glare, Hard Coating (3H) | Gross (kg): | 7.6 |
| COMPATIBILITY | Anti-Glare, Hard Coating (SH) | DIMENSIONS (IMPERIAL) (W | |
| PC Resolution (max): | 1920x1080 | Packaging (in.): | 21.9 x 14.9 x 8.3 |
| Mac® Resolution (max): | 1920×1080 | Physical (in.): | 19.7 x 15.23~19.56 x 8.1 |
| | Windows 10/11 certified; macOS | Physical Without Stand (in.): | 19.7 x 11.6 x 2 |
| PC Operating System: | tested | DIMENSIONS (METRIC) (WX | |
| Mac® Resolution (min): | 1920x1080 | Packaging (mm): | 556 x 379 x 210 |
| CONNECTOR | | Physical (mm): | 501 x 386.85~496.96 x 206 |
| VGA: | 1 | Physical Without Stand (mm): | 501 x 294 x 51 |
| USB 3.2 Type A Down Stream: | 4 | GENERAL | |
| USB 3.2 Type B Up Stream: | 1 | | cTUVus, FCC-B, ICES003, Energy |
| 3.5mm Audio In: | 1 | Regulations: | Star, EPEAT, CEC, NOM, Mexico Energy, CB, RoHS, REACH, WEEE |
| 3.5mm Audio Out: | 1 | | VG2240 x1, 3-pin Plug (IEC C13 / |
| HDMI 1.4: | 1 | PACKAGE CONTENTS: | CEE22) x1, HDMI Cable (v1.4; Male- Male) x1, USB A/B Cable (v3.2; |
| DisplayPort: | 1 | | Male-Male) x1, Audio Cable (Male- Male) x1, Quick Start Guide x1 |
| Power in: | 3-pin Socket (IEC C14 / CEE22) | 2 1 (2) | Please dispose of in accordance with |
| AUDIO | | Recycle/Disposal: | local, state or federal laws. |
| Internal Speakers: | 2Watts x2 | Warranty: | *Warranty offered may differ from market to market |
| POWER | | Power Management: | Energy Star standards, EPEAT |
| Eco Mode (Conserve): | 12.35W | 1 ower management. | Energy oral standards, El E/M |
| Eco Mode (optimized): | 14.43W | | |
| Consumption (typical): | 17.18W | | |
| Consumption (max): | 18.89W | | |
| Voltage: | AC 100-240V | | |
| Stand-by: | 0.5W | | |
| Power Supply: | Internal Power Supply | | |
| ADDITIONAL HARDWARE | | | |
| Kensington Lock Slot: | 1 | | |
| Cable Organization: | Yes | | |
| CONTROLS | | | |
| Physical Controls: | Key 1 (eye), Key 2, Key 3, Key 4, Key 5, Key 6 (power) | | |
| On Screen Display: | Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu | | |

 $\label{thm:convergence} \mbox{Copyright $@$ ViewSonic Corporation 2000-2022. All rights reserved.}$