

# ViewSonic® LCD DISPLAY

## XG341C-2K

### Key Features

- AMD FreeSync™ Premium Pro for smooth and ultra-low-latency playback
- Mini-LED w/1152 zone display and full-array local dimming for peak visual performance
- VESA DisplayHDR 1400 for mind-blowing colors and contrasts
- Refresh rate overclockable to 200Hz for hyper-responsive visuals
- HDMI 2.1 Connection for console gaming compatibility



### Product Description

Experience a new level of visual performance and upgrade your gameplay on the XG341C-2K, featuring Mini LED technology that redefines expectations. Curved 34-inch UWQHD monitor delivers a highly immersive gaming experience teleporting you straight into the middle of the action. Engineered with quantum dot technology, the resolution renders every detail with incredible brightness on VESA certified DisplayHDR™ 1400 panel. Rapid 200Hz (OC) refresh rate guarantees ultrasMOOTH gameplay, and a blazing fast 1ms (MPRT) response time to reduce in-game ghosting. Geared with AMD FreeSync™ Premium Pro technology, you'll handle even the most intense action scenes.

Visit Us [www.viewsonic.com](http://www.viewsonic.com)

**DISPLAY**

|                         |  |
|-------------------------|--|
| Display Size (in.):     | 34   |
| Viewable Area (in.):    | 34   |
| Panel Type:             | VA Technology  |
| Resolution:             | 3440 x 1440  |
| Resolution Type:        | UWQHD (UltraWide QHD)  |
| Static Contrast Ratio:  | 3,000:1 (typ)  |
| Dynamic Contrast Ratio: | 120M:1   |
| Light Source:           | mini LED   |
| Brightness:             | 720; 1400 (w/ HDR+local dimming Peak (Min))  |
| Colors:                 | 16.7M  |
| Color Space Support:    | 8 bit true   |
| Aspect Ratio:           | 21:9   |
| Response Time (MPRT):   | 1ms  |
| Viewing Angles:         | 178° horizontal, 178° vertical   |
| Backlight Life (Hours): | 30000 Hrs (Min)  |
| Curvature:              | 1500R  |
| Refresh Rate (Hz):      | 200  |
| Adaptive Sync:          | FreeSync Premium Pro   |
| Blue Light Filter:      | Yes  |
| Flicker-Free:           | Yes  |
| Color Gamut:            | DCI-P3: 97% coverage (Typ)<br>NTSC: 99% size (Typ)<br>sRGB: 140% size / 99% coverage (Typ) |
| Pixel Size:             | 0.232 mm (H) x 0.232 mm (V)  |
| Surface Treatment:      | Anti-Glare, Hard Coating (3H)  |

**COMPATIBILITY**

|                        |                                       |
|------------------------|---------------------------------------|
| PC Resolution (max):   | 3440x1440                             |
| Mac® Resolution (max): | 3440x1440                             |
| PC Operating System:   | Windows 10/11 certified; macOS tested |
| Mac® Resolution (min): | 3440x1440                             |

**CONNECTOR**

|  |                                |
|--|--------------------------------|
| USB 3.2 Type A Down Stream:                      | 3                              |
| USB 3.2 Type B Up Stream:                        | 1                              |
| USB 3.2 Type C Up Stream; DisplayPort Alt mode : | 1                              |
| 3.5mm Audio Out:                                 | 1                              |
| HDMI 2.1:  | 2                              |
| DisplayPort:                                     | 1                              |
| Power in:  | 3-pin Socket (IEC C14 / CEE22) |

**AUDIO**

|                    |           |
|--------------------|-----------|
| Internal Speakers: | 5Watts x2 |
|--------------------|-----------|

**POWER**

|                        |                       |
|------------------------|-----------------------|
| Eco Mode (Conserve):   | 45W                   |
| Eco Mode (optimized):  | 53W                   |
| Consumption (typical): | 57W                   |
| Consumption (max):     | 60W                   |
| Voltage:               | AC 100-240V           |
| Stand-by:              | 0.5W                  |
| Power Supply:          | Internal Power Supply |

**ADDITIONAL HARDWARE**

|                       |     |
|-----------------------|-----|
| Kensington Lock Slot: | 1   |
| Cable Organization:   | Yes |

**CONTROLS**

|                    |   |
|--------------------|---|
| Physical Controls: | Up, Right, Down, Left, Power  |
| On Screen Display: | Game Modes, Display, Input Select, ViewMode, Audio Adjust, Setup Menu |

**OPERATING CONDITIONS**

|                            |                             |
|----------------------------|-----------------------------|
| Temperature:               | 32°F to 104°F (0°C to 40°C) |
| Humidity (non-condensing): | 20% to 90%                  |

**WALL MOUNT**

|                  |              |
|------------------|--------------|
| VESA Compatible: | 100 x 100 mm |
|------------------|--------------|

**INPUT SIGNAL**

|                       |             |
|-----------------------|-------------|
| Frequency Horizontal: | 30 ~ 320KHz |
| Frequency Vertical:   | 48 ~ 200Hz  |

**VIDEO INPUT**

|               |   |
|---------------|---|
| Digital Sync: | TMDS - HDMI (v2.1), PCI-E - DisplayPort (v1.4), Micro-Packet - Type C |
|---------------|---|

**ERGONOMICS**

|                      |           |
|----------------------|-----------|
| Height Adjust (mm):  | 120       |
| Swivel:              | 50°       |
| Tilt (Forward/Back): | -5° / 23° |

**WEIGHT (IMPERIAL)**

|                          |      |
|--------------------------|------|
| Net (lbs):               | 25   |
| Net Without Stand (lbs): | 18.7 |
| Gross (lbs):             | 40.3 |

**WEIGHT (METRIC)**

|                         |      |
|-------------------------|------|
| Net (kg):               | 11.4 |
| Net Without Stand (kg): | 8.5  |
| Gross (kg):             | 18.3 |

**DIMENSIONS (IMPERIAL) (WXHXD)**

|                               |                           |
|-------------------------------|---------------------------|
| Packaging (in.):              | 37.9 x 20.4 x 13.8        |
| Physical (in.):               | 31.8 x 18.94~23.67 x 15.1 |
| Physical Without Stand (in.): | 31.8 x 14.3 x 5.2         |

**DIMENSIONS (METRIC) (WXHXD)**

|                              |                           |
|------------------------------|---------------------------|
| Packaging (mm):              | 963 x 518 x 351           |
| Physical (mm):               | 807 x 481.11~601.11 x 384 |
| Physical Without Stand (mm): | 807 x 363 x 132           |

**GENERAL**

|              |  |
|--------------|--|
| Regulations: | cTUVus, FCC-B, ICES003, CEC, MX-CoC, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, UKCA, CCC, China RoHS, China Energy Label |
|--------------|--|

|                   |  |
|-------------------|--|
| PACKAGE CONTENTS: | XG341C-2K x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v2.1; Male-Male) x1, DisplayPort Cable (v1.4; Male-Male) x1, USB Type-C Gen2 Cable (Male-Male) x1, USB A/B Cable (v3.2; Male-Male) x1, Quick Start Guide x1 |
|-------------------|--|

|                   |  |
|-------------------|--|
| Recycle/Disposal: | Please dispose of in accordance with local, state or federal laws. |
|-------------------|--|

|           |  |
|-----------|--|
| Warranty: | *Warranty offered may differ from market to market |
|-----------|--|