



205 Westwood Ave, Long Branch, NJ 07740 Phone: 866-94 BOARDS (26273) / (732)-222-1511 Fax: (732)-222-7088 | E-mail: sales@touchboards.com



MULTIMEDIA PROJECTORS

D910HD

The 1080p Cross-Over projector for SOHO

1080p transitions from the home to the office with the Vivitek D910HD, which delivers 3000 ANSI Lumens of brightness and a 6000:1 contrast ratio. The Vivitek D910HD displays impressive color reproduction and amazing performance with the assistance of DLP® and BrilliantColor™ technologies. A stylish projector with a built-in speaker and an assortment of connectivity options, the D910HD is the ultimate match for today's high-definition presentations.

Features

- 3000 ANSI Lumens of brightness with a 6000:1 contrast ratio
- DLP® and BrilliantColor™ technologies from Texas Instruments
- Connectivity options include: HDMI, DisplayPort, VGAin (2x), VGA-Out, composite video, component video, Svideo
- Network-ready for integration and system administration via RJ45
- Direct 3D over HDMI
- Top-loading, sliding cover for quick and easy lamp replacement
- Keypad lock prevents accidental system adjustments











Brightness 3000 ANSI Lumens Native Resolution 1080p (1920 x 1080) Max. Resolution WUXGA (1920 x 1200) @60Hz Contrast Ratio 6000:1 Lamp Life and Type 3,500/5,000 Hours (Normal/Eco Mode), 240W/190W Display Type Single 0.65" DLP® Technology by Texas Instruments Throw Ratio 1.58 to 1.92:1 (Distance/Width) Image Size (Diagonal) 23.5" to 300" Projection Distance 1.0 to 10.0 m Projection Lens F=2.51~2.77, f = 23.5~28.2mm Zoom Ratio 1.2x Aspect Ratio 16:9 Native, 4:3, 16:10 Compatible Offset (full image height) 115% Keystone Correction ±40° Vertical Speaker 10 Watt Remote Control Fully Featured IR Remote with Laser Pointer Projection Method Table Top or Ceiling Mount (Front or Rear) Video Compatibility SDTV(480), 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, KI, L) I/O Connection Ports VGA-In (2x), HDMI v.1.4, DisplayPort, S-Video, Composite, Audio-In (RCA), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RI-45, 12V-Trigger, RS-232, Mini-USB (service) Security Kensington® Lock Port, Security Bar Weight 3.15kg Dimensions (W x D x H) 285 x 261 x 122 mm Noise Level 35dB/32dB (Normal/Eco Mode) Power Supply: AC 100-240V, 50/60Hz Consumption: 290W/240W (Normal./Eco Mode) <0.5W (Standby Mode) Warranty 3 Years, 1 Year (or 1,000h) on the Lamp Education Warranty 5-Year (warranty, 3-Year (or 2,000 hours) AC Power Cord, VGA Cable, Carrying Case, Remote Control, Batteries for Remote, Lens Cap, User's Manual (CD), Warranty Card Optional Accessories Replacement Lamp, Remote, Carrying Case		
Native Resolution 1080p (1920 x 1080) Max. Resolution WUXGA (1920 x 1200) @60Hz Contrast Ratio 6000:1 Lamp Life and Type 3,500/5,000 Hours (Normal/Eco Mode), 240W/190W Display Type Single 0.65" DLP® Technology by Texas Instruments Throw Ratio 1.58 to 1.92:1 (Distance/Width) Image Size (Diagonal) 23.5" to 300" Projection Distance 1.0 to 10.0 m Projection Lens F=2.51~2.77, f = 23.5~28.2mm Zoom Ratio 1.2x Aspect Ratio 16:9 Native, 4:3, 16:10 Compatible Offset (full image height) 115% Keystone Correction 440° Vertical Speaker 10 Watt Remote Control Fully Featured IR Remote with Laser Pointer Projection Method Table Top or Ceiling Mount (Front or Rear) Video Compatibility SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L) I/O Connection Ports VGA-In (2x), HDMI v.1.4, DisplayPort, S-Video, Composite, Audio-In (RCA), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RJ-45, 12V-Trigger, RS-232, Mini-USB (service) Security Kensington® Lock Port, Security Bar Weight 3.15kg Dimensions (W x D x H) 285 x 261 x 122 mm Noise Level Supply: AC 100-240V, 50/60Hz Consumption: 290W/240W (Normal./Eco Mode) <0.5W (Standby Mode) Warranty 3 Years, 1 Year (or 1,000h) on the Lamp Education Warranty 5-Year Warranty, 3-Year (or 2,000 hours) Standard Accessories Replacement Lamp, Remote, Carrying Case, Remote Control, Batteries for Remote, Lens Cap, User's Manual (CD), Warranty Card	Specifications	
Max. Resolution WUKGA (1920 x 1200) @60Hz Contrast Ratio 6000:1 Lamp Life and Type 3,500/5,000 Hours (Normal/Eco Mode), 240W/190W Display Type Single 0.65" DLP® Technology by Texas Instruments Throw Ratio 1.58 to 1.92:1 (Distance/Width) Image Size (Diagonal) 23.5" to 300" Projection Distance 1.0 to 10.0 m Projection Lens F=2.51~2.77, f = 23.5~28.2mm Zoom Ratio 1.2x Aspect Ratio 16:9 Native, 4:3, 16:10 Compatible Offset (full image height) 115% Keystone Correction ±40° Vertical Speaker 10 Watt Remote Control Fully Featured IR Remote with Laser Pointer Projection Method Table Top or Ceiling Mount (Front or Rear) Video Compatibility SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L) I/O Connection Ports VGA-In (2x), HDMI v.1.4, DisplayPort, S-Video, Composite, Audio-In (RCA), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), R1-45, 12V-Trigger, RS-232, Mini-USB (service) Security Kensington® Lock Port, Security Bar Weight 3.15 Kg Dimensions (W x D x H) 285 x 261 x 122 mm Noise Level Sd58/32dB (Normal/Eco Mode) Power Supply: AC 100-240V, 50/60Hz Consumption: 290W/240W (Normal./Eco Mode) <0.5W (Standby Mode) Warranty 3 Years, 1 Year (or 1,000h) on the Lamp Education Warranty 5-Year Warranty, 3-Year (or 2,000 hours) Standard Accessories Replacement Lamp, Remote, Carrying Case, Remote Control, Batteries for Remote, Lens Cap, User's Manual (CD), Warranty Card	Brightness	3000 ANSI Lumens
Contrast Ratio 6000:1 Lamp Life and Type 3,500/5,000 Hours (Normal/Eco Mode), 240W/190W Display Type Single 0.65" DLP® Technology by Texas Instruments Throw Ratio 1.58 to 1.92:1 (Distance/Width) Image Size (Diagonal) 23.5" to 300" Projection Distance 1.0 to 10.0 m Projection Lens F=2.51~2.77, f = 23.5~28.2mm Zoom Ratio 1.2x Aspect Ratio 16:9 Native, 4:3, 16:10 Compatible Offset (full image height) 115% Keystone Correction ±40° Vertical Speaker 10 Watt Remote Control Fully Featured IR Remote with Laser Pointer Projection Method Table Top or Ceiling Mount (Front or Rear) Video Compatibility SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L) I/O Connection Ports VGA-In (2x), HDMI v.1.4, DisplayPort, S-Video, Composite, Audio-In (RCA), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RJ-45, 12V-Trigger, RS-232, Mini-USB (service) Security Kensington® Lock Port, Security Bar Weight 3.15Kg Dimensions (W x D x H) 285 x 261 x 122 mm Noise Level 35dB/32dB (Normal/Eco Mode) Power Supply: AC 100-240V, 50/60Hz Consumption: 290W/240W (Normal./Eco Mode) <0.5W (Standby Mode) Warranty 3 Years, 1 Year (or 1,000h) on the Lamp Education Warranty 5-Year Warranty, 3-Year (or 2,000 hours) Standard Accessories Replacement Lamp, Remote, Carrying Case, Remote Control, Batteries for Remote, Lens Cap, User's Manual (CD), Warranty Card	Native Resolution	1080p (1920 x 1080)
Lamp Life and Type 3,500/5,000 Hours (Normal/Eco Mode), 240W/190W Display Type Single 0.65" DLP® Technology by Texas Instruments 1.58 to 1.92:1 (Distance/Width) Image Size (Diagonal) Projection Distance 1.0 to 10.0 m Projection Lens F=2.51~2.77, f = 23.5~28.2mm Zoom Ratio 1.2x Aspect Ratio 16:9 Native, 4:3, 16:10 Compatible Offset (full image height) Keystone Correction \$40\text{0}\text{Vertical}\$ Speaker 10 Watt Remote Control Projection Method Table Top or Ceiling Mount (Front or Rear) Video Compatibility \$15V(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L) I/O Connection Ports VGA-In (2x), HDMI v.1.4, DisplayPort, S-Video, Composite, Audio-In (RCA), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RJ-45, 12V-Trigger, RS-232, Mini-USB (service) Security Weight 3.15Kg Dimensions (W x D x H) Noise Level Power Supply: AC 100-240V, 50/60Hz Consumption: 290W/240W (Normal./Eco Mode) <0.5W (Standby Mode) Warranty Education Warranty \$40 Power Cord, VGA Cable, Carrying Case, Remote Control, Batteries for Remote, Lens Cap, User's Manual (CD), Warranty Card Optional Accessories Replacement Lamp, Remote, Carrying Case	Max. Resolution	WUXGA (1920 x 1200) @60Hz
Display Type Single 0.65" DLP® Technology by Texas Instruments Throw Ratio 1.58 to 1.92:1 (Distance/Width) Projection Distance 1.0 to 10.0 m Projection Lens F=2.51~2.77, f = 23.5~28.2mm Zoom Ratio 1.2x Aspect Ratio 16:9 Native, 4:3, 16:10 Compatible Offset (full image height) Keystone Correction Speaker 10 Watt Remote Control Projection Method Table Top or Ceiling Mount (Front or Rear) Video Compatibility SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L) VGA-In (2x), HDMI v.1.4, DisplayPort, S-Video, Composite, Audio-In (RCA), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RJ-45, 12V-Trigger, RS-232, Mini-USB (service) Security Kensington® Lock Port, Security Bar Weight 3.15Kg Dimensions (W x D x H) Noise Level Power Supply: AC 100-240V, 50/60Hz Consumption: 290W/240W (Normal./Eco Mode) <0.5W (Standby Mode) Warranty Education Warranty 5-Year Warranty, 3-Year (or 2,000 hours) Standard Accessories Replacement Lamp, Remote, Carrying Case	Contrast Ratio	6000:1
Throw Ratio 1.58 to 1.92:1 (Distance/Width) Image Size (Diagonal) 23.5" to 300" Projection Distance 1.0 to 10.0 m Projection Lens F=2.51~2.77, f = 23.5~28.2mm Zoom Ratio 1.2x Aspect Ratio 16:9 Native, 4:3, 16:10 Compatible Offset (full image height) 115% Keystone Correction \$\frac{\pmathcal{4}0^{\text{\text{9}}}\text{ Vertical}}{\text{3}}\$ Speaker 10 Watt Remote Control Projection Method Table Top or Ceiling Mount (Front or Rear) Video Compatibility \$\text{SDTV}(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L) I/O Connection Ports VGA-In (2x), HDMI v.1.4, DisplayPort, S-Video, Composite, Audio-In (RCA), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RJ-45, 12V-Trigger, RS-232, Mini-USB (service) Security Kensington® Lock Port, Security Bar Weight 3.15Kg Dimensions (W x D x H) Noise Level Power \$\text{35dB/32dB (Normal/Eco Mode)}{\text{35dB/32dB} \text{ Normal/Eco Mode}}{\text{35dB/32dB} \text{ Normal/Eco Mode}} < 0.5W (Standby Mode) Warranty \$\text{3} \text{ year (or 1,000h) on the Lamp} \text{ 5-Year Warranty, 3-Year (or 2,000 hours)}}{\text{35tandard Accessories}}{\text{40}} Replacement Lamp, Remote, Carrying Case, Remote Control, Batteries for Remote, Lens Cap, User's Manual (CD), Warranty Card Optional Accessories	Lamp Life and Type	3,500/5,000 Hours (Normal/Eco Mode), 240W/190W
Image Size (Diagonal) 23.5" to 300"	Display Type	Single 0.65" DLP® Technology by Texas Instruments
Projection Distance Projection Lens F=2.51~2.77, f = 23.5~28.2mm Zoom Ratio 1.2x Aspect Ratio 16:9 Native, 4:3, 16:10 Compatible Offset (full image height) 115% Keystone Correction \$\frac{\pmathbb{4}}{240}\text{ Vertical}\$ Speaker 10 Watt Remote Control Projection Method Table Top or Ceiling Mount (Front or Rear) Video Compatibility SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L) I/O Connection Ports VGA-In (2x), HDMI v.1.4, DisplayPort, S-Video, Composite, Audio-In (RCA), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RJ-45, 12V-Trigger, RS-232, Mini-USB (service) Security Kensington* Lock Port, Security Bar Weight 3.15Kg Dimensions (W x D x H) Noise Level Supply: AC 100-240V, 50/60Hz Consumption: 290W/240W (Normal./Eco Mode) <0.5W (Standby Mode) Warranty Standard Accessories AC Power Cord, VGA Cable, Carrying Case, Remote Control, Batteries for Remote, Lens Cap, User's Manual (CD), Warranty Card Optional Accessories Replacement Lamp, Remote, Carrying Case	Throw Ratio	1.58 to 1.92:1 (Distance/Width)
Projection Lens F=2.51~2.77, f = 23.5~28.2mm Zoom Ratio 1.2x Aspect Ratio 16:9 Native, 4:3, 16:10 Compatible Offset (full image height) Level 115% Keystone Correction \$40° Vertical Speaker 10 Watt Remote Control Fully Featured IR Remote with Laser Pointer Projection Method Table Top or Ceiling Mount (Front or Rear) Video Compatibility SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L) I/O Connection Ports VGA-In (2x), HDMI v.1.4, DisplayPort, S-Video, Composite, Audio-In (RCA), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RJ-45, 12V-Trigger, RS-232, Mini-USB (service) Security Kensington® Lock Port, Security Bar Weight 3.15Kg Dimensions (W x D x H) Noise Level 35dB/32dB (Normal/Eco Mode) Power Supply: AC 100-240V, 50/60Hz Consumption: 290W/240W (Normal./Eco Mode) <0.5W (Standby Mode) Warranty 3 Years, 1 Year (or 1,000h) on the Lamp Education Warranty 5-Year Warranty, 3-Year (or 2,000 hours) Standard Accessories Replacement Lamp, Remote, Carrying Case, Remote Control, Batteries for Remote, Lens Cap, User's Manual (CD), Warranty Card Optional Accessories	Image Size (Diagonal)	23.5" to 300"
Zoom Ratio1.2xAspect Ratio16:9 Native, 4:3, 16:10 CompatibleOffset (full image height)115%Keystone Correction±40° VerticalSpeaker10 WattRemote ControlFully Featured IR Remote with Laser PointerProjection MethodTable Top or Ceiling Mount (Front or Rear)Video CompatibilitySDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)I/O Connection PortsVGA-In (2x), HDMI v.1.4, DisplayPort, S-Video, Composite, Audio-In (RCA), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RJ-45, 12V-Trigger, RS-232, Mini-USB (service)SecurityKensington® Lock Port, Security BarWeight3.15KgDimensions (W x D x H)285 x 261 x 122 mmNoise Level35dB/32dB (Normal/Eco Mode)PowerSupply: AC 100-240V, 50/60Hz Consumption: 290W/240W (Normal./Eco Mode) <0.5W (Standby Mode)	Projection Distance	1.0 to 10.0 m
Aspect Ratio 16:9 Native, 4:3, 16:10 Compatible Offset (full image height) 115% Keystone Correction \$40\text{ Vertical}\$ Speaker 10 Watt Remote Control Projection Method Table Top or Ceiling Mount (Front or Rear) Video Compatibility \$50 V(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L) I/O Connection Ports VGA-In (2x), HDMI v.1.4, DisplayPort, S-Video, Composite, Audio-In (RCA), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RJ-45, 12V-Trigger, RS-232, Mini-USB (service) Security Kensington® Lock Port, Security Bar Weight 3.15Kg Dimensions (W x D x H) Noise Level 35dB/32dB (Normal/Eco Mode) Power Supply: AC 100-240V, 50/60Hz Consumption: 290W/240W (Normal./Eco Mode) <0.5W (Standby Mode) Warranty 3 Years, 1 Year (or 1,000h) on the Lamp 5-Year Warranty, 3-Year (or 2,000 hours) Standard Accessories AC Power Cord, VGA Cable, Carrying Case, Remote Control, Batteries for Remote, Lens Cap, User's Manual (CD), Warranty Card Optional Accessories Replacement Lamp, Remote, Carrying Case	Projection Lens	F=2.51~2.77, f = 23.5~28.2mm
Offset (full image height) Keystone Correction \$peaker	Zoom Ratio	1.2x
Keystone Correction±40° VerticalSpeaker10 WattRemote ControlFully Featured IR Remote with Laser PointerProjection MethodTable Top or Ceiling Mount (Front or Rear)Video CompatibilitySDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)I/O Connection PortsVGA-In (2x), HDMI v.1.4, DisplayPort, S-Video, Composite, Audio-In (RCA), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RJ-45, 12V-Trigger, RS-232, Mini-USB (service)SecurityKensington® Lock Port, Security BarWeight3.15KgDimensions (W x D x H)285 x 261 x 122 mmNoise Level35dB/32dB (Normal/Eco Mode)PowerSupply: AC 100-240V, 50/60Hz Consumption: 290W/240W (Normal./Eco Mode) <0.5W (Standby Mode)	Aspect Ratio	16:9 Native, 4:3, 16:10 Compatible
Speaker Remote Control Fully Featured IR Remote with Laser Pointer Projection Method Table Top or Ceiling Mount (Front or Rear) Video Compatibility SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L) I/O Connection Ports VGA-In (2x), HDMI v.1.4, DisplayPort, S-Video, Composite, Audio-In (RCA), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RI-45, 12V-Trigger, RS-232, Mini-USB (service) Security Kensington® Lock Port, Security Bar 3.15Kg Dimensions (W x D x H) Noise Level Power Supply: AC 100-240V, 50/60Hz Consumption: 290W/240W (Normal./Eco Mode) <0.5W (Standby Mode) Warranty Education Warranty S-Year (or 1,000h) on the Lamp Education Warranty S-Year Warranty, 3-Year (or 2,000 hours) Standard Accessories Replacement Lamp, Remote, Carrying Case	Offset (full image height)	115%
Remote Control Fully Featured IR Remote with Laser Pointer Projection Method Table Top or Ceilling Mount (Front or Rear) SDTV (480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L) I/O Connection Ports VGA-In (2x), HDMI v.1.4, DisplayPort, S-Video, Composite, Audio-In (RCA), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RJ-45, 12V-Trigger, RS-232, Mini-USB (service) Security Kensington® Lock Port, Security Bar Weight 3.15Kg Dimensions (W x D x H) Noise Level Power Supply: AC 100-240V, 50/60Hz Consumption: 290W/240W (Normal./Eco Mode) <0.5W (Standby Mode) Warranty Education Warranty S Years, 1 Year (or 1,000h) on the Lamp Education Warranty S-Year Warranty, 3-Year (or 2,000 hours) Standard Accessories AC Power Cord, VGA Cable, Carrying Case, Remote Control, Batteries for Remote, Lens Cap, User's Manual (CD), Warranty Card Optional Accessories Replacement Lamp, Remote, Carrying Case	Keystone Correction	±40º Vertical
Projection Method Table Top or Ceiling Mount (Front or Rear) SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L) I/O Connection Ports VGA-In (2x), HDMI v.1.4, DisplayPort, S-Video, Composite, Audio-In (RCA), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RJ-45, 12V-Trigger, RS-232, Mini-USB (service) Security Kensington® Lock Port, Security Bar Weight 3.15Kg Dimensions (W x D x H) Noise Level 35dB/32dB (Normal/Eco Mode) Power Supply: AC 100-240V, 50/60Hz Consumption: 290W/240W (Normal./Eco Mode) <0.5W (Standby Mode) Warranty Education Warranty Standard Accessories AC Power Cord, VGA Cable, Carrying Case, Remote Control, Batteries for Remote, Lens Cap, User's Manual (CD), Warranty Card Optional Accessories Replacement Lamp, Remote, Carrying Case	Speaker	10 Watt
Video Compatibility SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L) I/O Connection Ports VGA-In (2x), HDMI v.1.4, DisplayPort, S-Video, Composite, Audio-In (RCA), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RJ-45, 12V-Trigger, RS-232, Mini-USB (service) Security Kensington® Lock Port, Security Bar Weight 3.15Kg Dimensions (W x D x H) Noise Level 35dB/32dB (Normal/Eco Mode) Power Supply: AC 100-240V, 50/60Hz Consumption: 290W/240W (Normal./Eco Mode) <0.5W (Standby Mode) Warranty Education Warranty 3 Years, 1 Year (or 1,000h) on the Lamp 5-Year Warranty, 3-Year (or 2,000 hours) AC Power Cord, VGA Cable, Carrying Case, Remote Control, Batteries for Remote, Lens Cap, User's Manual (CD), Warranty Card Optional Accessories Replacement Lamp, Remote, Carrying Case	Remote Control	Fully Featured IR Remote with Laser Pointer
NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L) I/O Connection Ports VGA-In (2x), HDMI v.1.4, DisplayPort, S-Video, Composite, Audio-In (RCA), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RJ-45, 12V-Trigger, RS-232, Mini-USB (service) Security Kensington® Lock Port, Security Bar Weight 3.15Kg Dimensions (W x D x H) Noise Level 35dB/32dB (Normal/Eco Mode) Power Supply: AC 100-240V, 50/60Hz Consumption: 290W/240W (Normal./Eco Mode) <0.5W (Standby Mode) Warranty 5-Year Warranty, 3-Year (or 2,000 hours) Standard Accessories AC Power Cord, VGA Cable, Carrying Case, Remote Control, Batteries for Remote, Lens Cap, User's Manual (CD), Warranty Card Optional Accessories Replacement Lamp, Remote, Carrying Case	Projection Method	Table Top or Ceiling Mount (Front or Rear)
Audio-In (RCA), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RJ-45, 12V-Trigger, RS-232, Mini-USB (service) Security Kensington® Lock Port, Security Bar 3.15Kg Dimensions (W x D x H) 285 x 261 x 122 mm Noise Level 35dB/32dB (Normal/Eco Mode) Power Supply: AC 100-240V, 50/60Hz Consumption: 290W/240W (Normal./Eco Mode) <0.5W (Standby Mode) Warranty 3 Years, 1 Year (or 1,000h) on the Lamp Education Warranty 5-Year Warranty, 3-Year (or 2,000 hours) Standard Accessories AC Power Cord, VGA Cable, Carrying Case, Remote Control, Batteries for Remote, Lens Cap, User's Manual (CD), Warranty Card Optional Accessories Replacement Lamp, Remote, Carrying Case	Video Compatibility	NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM
Weight 3.15kg Dimensions (W x D x H) 285 x 261 x 122 mm Noise Level 35dB/32dB (Normal/Eco Mode) Power Supply: AC 100-240V, 50/60Hz Consumption: 290W/240W (Normal./Eco Mode) <0.5W (Standby Mode) Warranty 3 Years, 1 Year (or 1,000h) on the Lamp Education Warranty 5-Year Warranty, 3-Year (or 2,000 hours) Standard Accessories AC Power Cord, VGA Cable, Carrying Case, Remote Control, Batteries for Remote, Lens Cap, User's Manual (CD), Warranty Card Optional Accessories Replacement Lamp, Remote, Carrying Case	I/O Connection Ports	Audio-In (RCA), Audio-In (Mini-Jack), VGA-Out, Audio-Out
Dimensions (W x D x H) 285 x 261 x 122 mm 35dB/32dB (Normal/Eco Mode) Power Supply: AC 100-240V, 50/60Hz Consumption: 290W/240W (Normal./Eco Mode) <0.5W (Standby Mode) Warranty 3 Years, 1 Year (or 1,000h) on the Lamp Education Warranty 5-Year Warranty, 3-Year (or 2,000 hours) Standard Accessories AC Power Cord, VGA Cable, Carrying Case, Remote Control, Batteries for Remote, Lens Cap, User's Manual (CD), Warranty Card Optional Accessories Replacement Lamp, Remote, Carrying Case	Security	Kensington® Lock Port, Security Bar
Noise Level Supply: AC 100-240V, 50/60Hz Consumption: 290W/240W (Normal./Eco Mode) <0.5W (Standby Mode) Warranty Education Warranty Standard Accessories AC Power Cord, VGA Cable, Carrying Case, Remote Control, Batteries for Remote, Lens Cap, User's Manual (CD), Warranty Card Optional Accessories Replacement Lamp, Remote, Carrying Case	Weight	3.15Kg
Power Supply: AC 100-240V, 50/60Hz Consumption: 290W/240W (Normal./Eco Mode) <0.5W (Standby Mode) Warranty Education Warranty S-Year (or 1,000h) on the Lamp 5-Year Warranty, 3-Year (or 2,000 hours) AC Power Cord, VGA Cable, Carrying Case, Remote Control, Batteries for Remote, Lens Cap, User's Manual (CD), Warranty Card Optional Accessories Replacement Lamp, Remote, Carrying Case	Dimensions (W x D x H)	285 x 261 x 122 mm
Consumption: 290W/240W (Normal./Eco Mode) <0.5W (Standby Mode) Warranty 3 Years, 1 Year (or 1,000h) on the Lamp Education Warranty 5-Year Warranty, 3-Year (or 2,000 hours) Standard Accessories AC Power Cord, VGA Cable, Carrying Case, Remote Control, Batteries for Remote, Lens Cap, User's Manual (CD), Warranty Card Optional Accessories Replacement Lamp, Remote, Carrying Case	Noise Level	35dB/32dB (Normal/Eco Mode)
Education Warranty 5-Year Warranty, 3-Year (or 2,000 hours) AC Power Cord, VGA Cable, Carrying Case, Remote Control, Batteries for Remote, Lens Cap, User's Manual (CD), Warranty Card Optional Accessories Replacement Lamp, Remote, Carrying Case	Power	Consumption: 290W/240W (Normal./Eco Mode) <0.5W
Standard Accessories AC Power Cord, VGA Cable, Carrying Case, Remote Control, Batteries for Remote, Lens Cap, User's Manual (CD), Warranty Card Optional Accessories Replacement Lamp, Remote, Carrying Case	Warranty	3 Years, 1 Year (or 1,000h) on the Lamp
Batteries for Remote, Lens Cap, User's Manual (CD), Warranty Card Optional Accessories Replacement Lamp, Remote, Carrying Case	Education Warranty	5-Year Warranty, 3-Year (or 2,000 hours)
	Standard Accessories	Batteries for Remote, Lens Cap, User's Manual (CD),
LIDC	Optional Accessories	Replacement Lamp, Remote, Carrying Case
010	UPC	