



POCKET PROJECTOR

Qumi Q5

Bright and Lightweight, HD, and Wireless Capability

The Qumi Q5, the next generation of Vivitek's series of HD LED pocket projectors, has a brightness level up to 500 lumens and weighs only 1.1 pounds. The Qumi Q5 features a DLP® Pico chipset and BrilliantColor™ technologies from Texas Instruments and wireless capability. The Qumi's sleek design and connectivity options allows it to be used with a variety of other portable devices, including, but not limited to smart phones, laptops, netbooks and tablets, digital and video cameras. Versatile and portable, the Vivitek Qumi Q5 is perfect for sharing digital content at work and play.

Features

- Native WXGA native resolution, HD 720p compatible resolution
- Up to 500 lumens of brightness and 10,000:1 contrast
- Estimated 30,000 hours of operation
- 4GB built-in memory and USB port for memory expansion to display content without a PC
- 3D-Ready via DLP Link
- Connectivity options include: HDMI, Universal I/O for VGA, AV mini-jack, mini-jack audio-out
- Only 1.1 pounds and available in blue, red, yellow, black or white finish















Specifications	
Brightness	Up to 500 Lumens
Native Resolution	WXGA (1280 x 800)
Max. Resolution	UXGA (1600 x 1200)
Contrast Ratio	10,000:1 (Full On/Full Off)
Light Source Life and Type	≈30,000 Hours, LED
Display Type	HD Pico DLP Technology by Texas Instruments
Throw Ratio (±3%)	1.55:1 (Distance/Width)
Image Size (Diagonal)	30" to 90" (0.8 to 2.3 m)
Projection Distance	3.3' to 9.9' (1.0 to 3.0 m)
Zoom Ratio	Fixed Lens, Manual Focus
Aspect Ratio	16:10 Native, 4:3 & 16:9 Compatible
Offset	102.5%
Keystone Correction	± 40° Vertical
Color Spectrum	1.07 Billion
Horizontal Scan Rate	15, 30 to 90 KHz
Vertical Scan Rate	43 to 85 Hz
Speaker	2W Mono
Projection Method	Table Top, Tripod (¼ - 20) or Ceiling (Front or Rear)
Uniformity	85%
File Compatibility	Office Viewer (Doc, XLS, PPT, PDF, TXT)
	Video (MPEG-4, H.264, Divx™, WMV)
	Image (JPEG, PNG, BMP, GIF) Audio (MP3, WAV)
Computer Compatibility	UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized;
Computer computationty	VESA Standards; PC and Macintosh Compatible
Video Compatibility	SDTV (480i), EDTV (480p), HDTV (720p, 1080i/p),
	NTSC/NTSC 4.43, PAL B/G/H/I/M/N 60, SECAM
I/O Connection Ports	HDMI, Universal I/O (24-Pin Connector for
	VGA/Component Input), AV Mini-Jack, Mini-Jack Audio- Out, USB (Type A)
Weight	17.3 oz (1.1 lbs)
Dimensions (W x H x D)	6.3" x 1.3" x 4.0" (162 x 32 x 102 mm)
Noise Level	28dB/32dB (Standard / Boost Mode)
Power	Supply: AC 100-240V, 50/60Hz
	Consumption: 65W (Boost Mode), <0.5W (Standby)
Operating Temperature	41 to 104°F (5 to 40°C)
Warranty	2-Year Limited Parts and Labor
Standard Accessories	Power Adapter, Universal I/O to VGA Cable, HDMI Cable,
	3.5mm AV-in Cable, Carrying Pouch, Remote Control,
	User Manual (CD) Quick Start Guide, Warranty Card
Optional Accessories	Battery Dock, Wi-Fi USB Dongle
UPC	8 14964 33659 0 (White/Q5-WH),
	8 14964 33661 3(Black/Q5-BK), 8 14964 33663 7 (Red/Q5-RD),
	8 14964 33665 1 (Blue/Q5-BL),
	8 14964 33667 5(Yellow/Q5-YW)