

ULTRA SHORT-THROW
Interactive 3D PROJECTOR

DW771USTi

High brightness WXGA UST projector with finger and pen touch IWB advantage, 4K compatible

Features

- DLP® and BrilliantColor™ technologies by Texas Instruments for sharp and detailed image quality
- 3,500 lumens of brightness with a 5,000:1 contrast ratio
- Native WXGA (1280 x800) resolution display up to UHD
- 4K incoming signal compatible
- 10-point finger touch and pen enabled IWB functionality (Required DT02 Kit)*
- Ultra short-throw to limit shadows and light glare
- Energy efficient lamps that last up to 12,000 hours (Dynamic Eco mode)
- 3D-ready via DLP® Link™, and Blu-Ray 3D functionality
- Full Connectivity options include: Two (2) HDMI 2.0, VGA and Composite video
- VGA-Out for display on secondary monitor
- Total 20W (10W x2) audio power with audio-in and audio-out ports for external device connection
- RJ45/RS-232 for integration and system administration
- Network ready and Crestron® RoomView™ approved for network monitoring and management
- Sealed optical engine to minimize the impact of dust
- Top-loading, cover for quick and easy lamp replacement



Specifications			
Display Type	Single Chip 0.65" DLP Technology by TI		
Brightness	3,500 ANSI Lumens		
Native Resolution	WXGA (1280 x 800)		
Contrast Ratio	5,000:1		
Light Source Life/Type	5,000/10,000/12,000 Hours (Normal/Eco. Mode/Dynamic Eco. Mode), 240W/170W		
Throw Ratio	0.35:1		
Image Size (Diagonal)	80" - 100"		
Projection Distance	605mm -755mm		
Projection Lens	Manual Focus		
Zoom Ratio	Fixed		
Aspect Ratio	16:10 Native		
Offset	120%±1.7%		
Keystone Correction	Vertical ±40° (±40 Step)		
Horizontal Frequency	15, 31 - 91.4kHz		
Vertical Scan Rate	24 - 30Hz, 47 - 120Hz		
Interactive Functionality	Yes (via Camera) (Finger Touch* and Pen Based Control) (*Requires DT02 Kit)		
3D Functionality	Yes (Supports DLP Link, Blu-Ray 3D)		
Audio Speakers	10W (x2)		
Projection Method	Table Top or Ceiling Mount (Front or Rear)		
Uniformity	85%		
Computer Compatibility	VGA, SVGA, XGA, SXGA, SXGA+, WXGA, UXGA@60Hz, Mac		
Video Compatibility	UHD / HDTV (720p, 1080i, 1080p) / EDTV (480p, 576p) / SDTV (480i, 576i) / NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L)		
I/O Connection Ports	HDMI 2.0 (x2)	VGA-Out	
	VGA-In	RJ-45	
	Composite Video	RS-232	
	Audio-In	RCA (L/R)	USB mini-B (Interactive)
		Mini-Jack	USB A (Power) 5V/1.5A
	Audio-Out (Mini-Jack)	USB B (Service Only)	
Security	Kensington® Lock Port, Security Bar		
Weight	11lbs (5.0 kg)		
Dimensions (W x H x D) (Not including height of mirror)	11.3" x 4.9" x 14.7" (287.7 x 126.6 x 374.5 mm)		
Noise Level	34dB/29dB (Normal / Eco. Mode)		
Power	Supply: AC 100-240V, 50/60Hz Consumption: 250W (Eco Mode), 290W (Normal Mode), <0.5W (Standby Mode)		
Operating Temperature	41 to 104°F (5 to 40°C)		
Warranty	5-Year Limited Parts/Labor, 1-Year on Lamp		
Standard Accessories	AC Power Cord, VGA Cable, Interactive Pen (x2), Remote Control, Batteries for Remote, User Manual (CD), Warranty Card, Wall Mount (%WM-3)		
Optional Accessories	Spare Lamp P/N (N/A) Remote Control P/N (N/A)		
UPC	813097024275		

