



Maintenance-Free Laser Projector

FEATURES

- Ultra short throw lens to make 150 inch big screen at only 40cm away
- 4,000 ANSI lumens of brightness, WXGA resolution and 12,000:1 contrast ratio for clear, crisp and bright projection
- Maintenance-free laser light source for up to 20,000 hours operation
- 10W speaker and multiple audio ports for external sound device
- Image adjustment with 4 corner correction
- Network ready for integration and system administration via RJ45



Ultra Short Throw with up to 150 inch screen size

The DW763Z-UST is designed for large screen displays at museum, in education or showroom applications where installation space is a constraint. Features a WXGA (1280 x 800), an amazing 4,000 ANSI Lumens and 12,000:1 contrast ratio for a clear and bright projection. In addition to this, the device is maintenance free, thanks to their lamp less laser light source design, which delivers up to 20,000 hours of operational time.



DW763Z-UST SPECIFICATIONS

Image	Display Type	Single chip DLP® Technology by Texas Instruments
	Brightness	4000 ANSI Lumens
	Native Resolution	WXGA (1280 x 800)
	Max. Supported Resolution	WUXGA (1920 x 1200) @60Hz
	Native Aspect Ratio	16:10
	Contrast Ratio	12,000:1
	Keystone Correction	Vertical: +/- 30°; Horizontal: +/- 30°
Optical	Throw Ratio	0.24:1
	Zoom Ratio	Fixed 1x
	Image Size (Diagonal)	80" - 150"
	Projection Distance	4 - 41 cm (from the screen to the projector)
	Offset (Based on Full Image Height)	115% from the lens center; 122% from the bottom of the projector
Features	Features	3D Ready(DLP link, PC+Video), Direct 3D (HDMI 1.4a), 3D Mandatory Formats supported (top/bottom, right/left, frame sequential), Keypad lock
Compatibility	Video	SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L)
Connectivity	I/O Connection Ports	VGA-In (15pin D-Sub), HDMI (x2), S-Video, Composite Video, Audio-In (RCA) , Audio-In (Mini-Jack), VGA-Out (15pin D-Sub), Audio-Out (Mini-Jack), RJ45, RS-232, USB A (Power Only), USB miniB (Service)
General	Dimensions (W x D x H)	509 x 390 x 145 mm
	Weight	10.5 kg
	Power	Supply: AC 100-240V, 50/60Hz Consumption: 315W (Eco. Mode), 380W (Normal Mode), <0.5W (Standby)
	Lamp Life and Type	Lamp free design. Laser light source last up to 20,000 hours
	Speakers	10W
	Noise Level	31dB / 28dB (Normal / Eco. Mode)
	Standard Accessories	VGA Cable, User Manual (CD), Quick Start Guide, Warranty Card (by region), Remote Controller (with battery), AC Power Cord
	Optional Accessories	Optional Wall Mount (LT30B-G), Remote Control P/N (tbc)
	Warranty	Ultra Short Throw Laser Phosphor Warranty: 3-Year warranty on projector/ 3-year or 10. 000h on the Laser Phosphor illumination source. (Whichever comes first)
	UPC Code	813097022592