



Large Venue Projector

Vivitek DX4630Z

High performance WUXGA laser projector with sealed optical engine, MHL compatibility and a full suite of displays ports



Features

- Advanced laser phosphor light engine for superior brightness and color uniformity
- Lampless design delivers up to 20,000 hours of operational time
- Up to 5,000 ANSI lumens with a 20,000:1 contrast ratio
- Native XGA resolution with a maximum WUXGA resolution
- Manual zoom and focus for easy adjustment and positioning flexibility
- Horizontal and vertical lens shift for greater installation convenience and flexibility
- Distorted and trapezoid image issues are easily corrected with keystone, and 4-corner adjustment
- MHL device compatibility for streaming of video and audio content from a compatible mobile device
- Full suite of display connectivity inputs and outputs 10W of total stereo audio power (5W x 2) with multiple audio-in and audio-out ports
- 3D sync port for compatibility with IR (infrared) 3D passive synchronization protocol
- 360° operation and projection design for set up in all angles
- Portrait mode projection allows the projector to be easily setup and installed in a 90° installation
- Airtight sealed engine and filter-less design for improved performance against fighting dust and fibers
- Choose from 8 pre-set display modes to get the most suitable display image
- Network ready for integration and system administration via RJ45
- Crestron® RoomView™ integration for network monitoring and management
- Anti-theft security features include: Kensington® security slot, and security bar

**PRELIMINARY SPECIFICATION FOR REFERENCE ONLY.
SUBJECT TO CHANGE WITHOUT PRIOR NOTICE. EXPECTED
Q2/2017 PRODUCT LAUNCH.**

Specifications

Display Type	Single Chip 0.55" DLP Technology by TI
Brightness	5,000 ANSI Lumens
Native Resolution	XGA (1024 x 768)
Maximum Resolution	WUXGA (1920x1200)@60Hz
Contrast Ratio	20,000:1
Laser Life/Type	20,000 + hours (Laser Phosphor Light Engine)
Throw Ratio	1.51 - 2.5:1
Image Size (Diagonal)	50" - 208"
Projection Distance	1.5m - 5m (4.9ft - 16.4ft)
Projection Lens	F#2.45 - 3.13, f=17.23 - 27.9mm
Zoom Ratio	1.65x
Aspect Ratio	4:3
Offset	142%/121%
Keystone Correction	Vertical ±25° - ±30°, Horizontal ±30°
Horizontal Frequency	15, 31 - 91.4kHz
Vertical Frequency	24 - 30Hz, 47 - 120Hz
3D Compatibility	TBD
Speaker	5W (x2)
Lens Shift Range	Vertical: TBD
	Horizontal: TBD
Computer Compatibility	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, WUXGA@60Hz, Mac
Video Compatibility	SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L)
I/O Connection Ports	HDMI v1.4b (x2), MHL/HDMI 1.4b, Composite Video, VGA-In, Audio-In RCA (L/R), Audio-In (Mini-Jack), MIC-In (3.5mm), VGA-Out, Audio-Out RCA (L/R), 3D Sync-Out, USB Type A Power (5V/1.5A), RJ45, RS232, USB (Service)
Projection Method	Table Top, Ceiling Mount (Front or Rear)
Security Solutions	Kensington® Security Slot, Security Bar, Keypad Lock
Dimensions (WxDxH)	350 x 450 x 151mm (13.8" x 17.7" x 5.9")
Weight	10.7kg (23.6lbs)
Available Colors	White (DX4530Z-WH), Black (DX4530Z-BK)
Noise Level	TBDdB/TBDdB (Normal/Eco. Mode)
Power Supply	AC 100-240V, 50/60Hz
Power Consumption	430W (Normal Mode), 350W (Eco. Mode), <0.5W (Standby Mode), <2W (LAN Standby Mode)
Standard Accessories	AC Power Cord, VGA Cable, Remote Control, Documentation Kit
Optional Accessories	N/A

©2017 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.



Photos

