



The Ultimate Short-Throw Solutions

High performance and HDMI Full 3D capability, the DX881ST 3D digital projector offers outstanding digital image, versatility and value. With HDTV compatibility, rapid start-up and shutdown, the DX881ST offers ease-of-use operation. The Vivitek DX881ST digital projectors also feature multiple connectivity options, DLP® and BrilliantColor™ technologies, and long-life lamp promoting environment friendly operation.

Features

- Native XGA resolution and displays up to WUXGA
- 3300 lumens of brightness with a 6000:1 contrast
- 3D-Ready via DLP® Link™, Full 3D From Blu-Ray or broadcasted via cable or satellite
- High-efficiency lamps that last up to 5000 hours (in standard mode)
- VGA-out for display on a secondary monitor
- Keypad lock prevents accidental system adjustments
- Enhanced color and display adjustments
- Top-loading, sliding cover for quick and easy lamp replacement
- RJ45/RS-232c for integration and system administration
- 12V trigger for simple screen/projector automation

Specifications	
Brightness	3300 Lumens
Native Resolution	XGA (1024 x 768)
Max. Resolution	WUXGA (1920 x 1200)
Contrast Ratio	6000:1 (Full On/Off)
Lamp Life and Type	3500/5000 Hours (Normal/Eco Mode), 240W
Lamp Part #	5811119560-SVV
Display Type	Single 0.55" DLP® Technology by Texas Instruments
Throw Ratio (±3%)	0.626 (Distance/Width)
Image Size (Diagonal)	37.3" - 373" (0.9 - 9.5 m)
Projection Distance	1.56' to 15.57' (0.475 to 4.745m)
Projection Lens	F2.8 , f=7.26mm @ 77 inch
Zoom Ratio	Fixed Lens, Manual Focus
Aspect Ratio	4:3 Native, 16:9 Compatible
Offset	116.2%
Keystone Correction	±40° Vertical
Color Spectrum	1.07 Million
Horizontal Scan Rate	15, 31 to 91.4KHz
Vertical Scan Rate	24 ~ 30Hz, 47 ~ 120Hz
Speaker	10 Watt Mono
Remote Control	Full Featured IR Remote w/ Laser Pointer
Projection Method	Table Top or Ceiling Mount (Front or Rear)
Uniformity	85%
Computer Compatibility	WUXGA, UXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized; VESA Standards; PC and Macintosh Compatible
Video Compatibility	SDTV (480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)
Full 3D Video Compatibility	720p 50/60 Frame Packing, 1080i 50/60 Side-by-Side, 1080p24 Frame Packing
I/O Connection Ports	HDMI v1.4, VGA-In (X2), S- Video, Composite Video, VGA-Out, Audio-In (Mini-Jack) x3, Audio-Out (Mini-Jack), Microphone-In (Mini-Jack), RJ45, RS-232c, 12V Trigger, USB Type A (Power only), Mini USB (Service)
Security	Kensington® Lock Port
Weight	N/A
Dimensions (W x H x D)	12.56" x 8.11" x 3.94" (319 x 206 x 100 mm)
Noise Level	32dB/36dB (Eco/Normal Mode)
Power	Supply: AC 100-240V, 50/60Hz Consumption: 330W (Normal Mode), 280W (Eco Mode), <0.5W (Standby Mode)
Operating Temperature	41 to 104°F (5 to 40°C)
Warranty	5-Year Limited Parts/Labor, 1year Lamp
Standard Accessories	AC Power Cord, VGA Cable, Remote Control, Batteries for Remote, Carrying Case, User's Manual (CD), Lens Cap, Warranty Card
UPC	814964 339836



205 Westwood Ave, Long Branch, NJ 07740
 Phone: 866-94 BOARDS (26273) / (732)-222-1511
 Fax: (732)-222-7088 | E-mail: sales@touchboards.com