

NovoTouch EK863i

True 86" 4K interactive display with wireless collaboration and touch interaction for the classroom



Features

- 86" display with ultraHD 4K (3,840 x 2,160) resolution for outstanding details and stunning visuals
- Backlit D-LED (ADS panel) technology for brighter pictures, flawless colors, richer textures, and extra wide viewing angles (178°/178°)
- Preconfigured with NovoConnect wireless presentation and collaborative system for cable-free and hassle-free presenting in the classroom
- Connect up to 64 users simultaneously, and allow 4 people to present on one display to facilitate large group work
- High contrast ratio and fast response time deliverables crisp, readable content
- Interactive functionality with up to a 20-point finger touch capabilities (10-point writing, 20-point touch) for on-screen annotation, drawing and common gesture controls
- Simple wireless display and true fast collaboration solution thanks to 802.11n/ac dual-band 2.4/5GHz support
- Remote manager with IT management software with automatic discovery and configuration
- Full suite of connectivity ports including HDMI-In VGA-In, Audio-In/Out, LAN, RS232 and USB.
- Front bezel USB ports for quick connection to USB memory drives and data
- 4mm thick toughened glass for added protection against scratches or screen damage
- Powerful front-facing stereo audio speakers with up to 32W of total power (16Wx2) and multiple audio-in/out ports

Display	Type/Technology		Backlit D-LED (ADS Panel)
	Panel Size		86"
	Brightness		350cd/m2
	Contrast Ratio		1,200:1
	Native Resolution		4K Ultra-HD (3840 x 2160)
	Viewing Angle (H/V)		178°/178°
	Aspect Ratio		16:9
	Response Time (MS)		8ms
	Refresh Rate (Hz)		60Hz
	Estimated Life Time (Typ)		30,000 hours
	Display Color (Bit)		1.07 billion (10-bit)
	Installation Orientation		Landscape
	Daily Operation (Hours/Days)		16/7
Interactivity	Technology		Infrared Touch
	Touch Points	Writing	10 Point (Standard)
		Touch	20 Point (Standard)
	Accuracy	Finger	±1.5mm (Over 90% area)
		Passive Pen	±1.5mm (Over 90% area)
	Response Time		<10ms
	Touch Resolution		32,768 x 32,768
	Surface Protection		4mm Thick Toughened Glass (Level 7H on Mohs Scale of Mineral Hardness)
Touch Tools		Finger, Stylus, Glove, Opaque Objects	
Operating System	System Version		Android™ v8.0
	CPU		Multi-Core High-Performance ARM® CPU
	GPU		4* Mali™ G51
	RAM		3GB DDR3
	Internal Storage		16GB (eMMC Flash) (About 9GB User Availability)
Connectivity	Input	Display	HDMI v2.0 (x3) (HDCP v2.2 Compliant), VGA-In (x1)
		Audio	Audio-In (3.5mm) (x1)
	Output	Display	HDMI-Out v2.0 (x1) (HDCP v2.2 Compliant)
		Audio	Audio-Out (3.5mm) (x1), SPDIF-Out (x1)
	Internet		LAN (RJ45) (x1)
	Control		RS232-In (x1)
	Wireless	Wifi (USB Module)	IEEE 802.11 a/b/g/n/ac (2.4GHz/5GHz)
		I/R Receiver	Front (x1) (±25° Angle, >8m Distance)
	USB	Front	USB 2.0 (x2)
		Side	USB3.0 (x3), USB Type B (x2)(For Touch Port)
		Bottom	USB 2.0 (x1)
Expansion	Android Module (Option)		Slot 1: 120pin NovoConnect OPS (Option)
	Window Module (Option)		Slot 2: Standard Intel 80pin OPS (Option)
Audio	Speakers		16W (x2) (Stereo)
Power	Power Supply (Internal)		AC 100 - 240V, 50/60Hz (4.0A)
	Consumption		450W
	Standby Mode		<0.5W (Standby)
Physical Characteristics	Dimension (L x H x D)		1,957.4 x 1,160.1 x 91.4mm (77.1" x 45.7" x 3.6")
	Weight		70.8kg (156.1lbs)
	VESA Mounting (FPMPMI)		4 - M8 x 25mm, 800 x 600mm (31.5" x 23.6")
	Color		Grey
Accessories	Standard	AC Power Cord, VGA Cable, HDMI Cable, USB Cable, Audio Cable, Stylus (x2), Remote Control (W/Batteries), Wall Mount Kit, Wifi USB Module, Documentation Kit	
UPC	813097025050		

©2020 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.