

WR3ME MULTI-CHANNEL, HOT AIR, DESOLDERING, SOLDERING REWORK SYSTEM: **WR3000SA**



WR3ME + WP80 + DXV80 + HAP200 + Tool stands + Tips included

PRODUCT DETAILS

Order number:	WR3000SA
Station power:	WR3ME 400W
Soldering power:	WP80 80W
Desoldering power:	DXV80 80W
Hot air power:	HAP200 200W
Total tool power:	360W

Weller includes tips + PC connectivity and data logging software + 360 watts total tool power

400 watts of power over three independently controlled channels

Application flexibility with up to 20 controllable tool options

Up to 200 watts of hot air power for efficient lead-free rework

Less than 5 seconds hot air time to temperature performance

Continuous productivity with no end of cycle hot air cool down time

Unmatched tool air flow volume of 1-15 L/Min

Up to 120 watts of desoldering power for demanding ground plane and multi-layer boards (optional)

Up to 200 watts of soldering power for unmatched application versatility (optional)

Connectivity to low voltage pre-heating plates and soldering baths

System operational right out of the box with all critical components and tips supplied

Sustainability of new tool developments with field accessible firmware update port

Included PC software enables PC connectivity and data logging capabilities

No system cooling requirements ensures lowest operational costs

Large, intuitive LCD display shows critical functions for all 3 channels

Temperature stability of $\pm 2^{\circ}\text{C}$ / $\pm 4^{\circ}\text{F}$ for superior reliability

Rotary vane vacuum pump for long life and quiet operation

Meets or exceeds mil-std and J-std 001E industry spec

ESD safe