

# WXA2N

2-Channel Power Unit, 200 W (255 W)  
Product no.: WXA2N



## Benefits

- › Digital 2 channel control unit 120V, 200 W (255 W) - base unit only
- › Temperature: 200 - 999° F / 50 - 550° C
- › Compressed air supply required: 87 PSI / 6 Bar (Max.)
- › Compatibility with all WX series tools
- › When using the WXHAP200 hot air pencil, only the WXMP-MS or WXMP series tools can be used simultaneously
- › Acts as a benchtop controller for the WHP1000 / WHP3000 hot plates
- › Acts as a benchtop controller for the Zero Smog 4V / 6V Filtration units
- › Air Flow rate: 0 - 20 l/min
- › Compressed air supply required: 400 - 600 kPa (58-87 psi); oil-free, dry compressed air
- › ESD safe

For this purpose, we recommend:



Solder fume extractors



Soldering irons



Cleaning



Pre-heating plates



Technical Data

Dimensions L x W x H (mm)	174 x 154 x 135
Dimensions L x W x H (inches)	6,69 x 5,95 x 5,12
Weight (approx.) in kg	4.0
Voltage	120 V
Power	200 W (255 W)
Channels	2
Temperature range (depends on tool) °C	50 - 550
Temperature range (depends on tool) °F	150 - 999
Temperature accuracy °C	±9
Temperature accuracy °F	±17
Temperature stability °C	±2
Temperature stability °F	±4
Equipotential bonding socket	Via 3, 5 mm pawl socket on back of device.
Display	255 x 128 dots / Hintergrundbeleuchtung
Air consumption l/min	20
Operating pressure in bar/psi	4,00 - 6,00 / 58 - 87
Capacity l/min	20
Vacuum	-0,6 bar

Owning the bench



PROFESSIONAL



FILTRATION



EREM



XCELITE