WXMP MS Set

Product no.: T0052923499



- For standard and micro applications. Component size M to L
 - > Extremely short heat-up time: 5 sec.
 - > According to Military Standard
 - > Triple awarded active Soldering tips
 - > Tip can be exchanged quick and easy
 - > Excellent heat transfer
 - > Excellent reaction time
 - RT solder tips can be changed quickly and easily

Weller®

Technical DataActive Tip heating element technologyonPower Response heating element technologySilver Line heating element technologyVoltage12 VPower40 W (55 W with RT 11MS)Tip rangeRTM MS	
Active Tip heating element technologyonPower Response heating element technologySilver Line heating element technologyVoltage12 VPower40 W (55 W with RT 11MS)	
technologyPower Response heating element technologySilver Line heating element technologyVoltageVoltagePower40 W (55 W with RT 11MS)	
element technology Silver Line heating element technology Voltage Voltage 12 V Power 40 W (55 W with RT 11MS)	
technology 12 V Voltage 12 V Power 40 W (55 W with RT 11MS)	
Power 40 W (55 W with RT 11MS)	
Tip range RTM MS	
Supply unitWX 1, WX 2, WXA 2, WXD 2, WXR 3	
WX-compatible on	
Temperature range °C100 - 450	
Temperature range °F200 - 850	
Heating time 5	
Safety rest WSR 200 (T0051517499N)	
Safety rest (optional)	
Barrel	
Integrated direct extraction	