



EAN:	4013288014405	Size:	25x7x7 mm
Part number:	05056662001	Weight:	4 g
Article number:	853/1 TZ ACR PH	Country of origin:	CZ
		Customs tariff number:	82079030

- For Phillips screws
- ACR (anti cam-out feature) to prevent any slipping out of the screw head
- Torsion zone for absorption of peak loads
- Enhanced service life of the bits
- Tough for hard materials
- 1/4" hexagon drive (Wera connecting series 1)

High quality bits with Torsion zone: where kinetic energy is diverted from peak loads. This greatly extends the product service life. Come with rough ribs (anti cam-out feature, ACR). Tough viscous, for universal use; 1/4" hexagon, suitable for holders as per DIN ISO 1173-D 6.3.

Web link

https://products.wera.de/en/bits_holders_adaptors_and_sets_the_range_of_bits_bits_for_phillips_screws_853_1_tz_acr_ph.html

Wera - 853/1 TZ ACR PH
05056662001 - 4013288014405

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

Bits for Phillips Screws

ACR®-Bits



ACR® stands for "anti-cam-out ribs". ACR® bits have ribs at the drive tip that protect against slipping out of the screw head. It is recommended that ACR® bits are matched with ribbed ACR® screws for maximum effect. ACR® is a registered trademark of Phillips Screw Company.

TZ-Bits





TZ-Bits are tough bits with a torsion zone. Torsion bits absorb the damaging peak torque loads in the torsion zone. This prevents premature wear and enhances the service life of the bits.

Tough-absorbing bits



Tough-absorbing Wera bits (Z) prevent any premature breakage of the drive tip.

Further versions in this product family:

		 mm	 inch
05056660001	PH 1	25	1"
05056662001	PH 2	25	1"
05056664001	PH 3	25	1"

Web link

https://products.wera.de/en/bits_holders_adaptors_and_sets_the_range_of_bits_bits_for_phillips_screws_853_1_tz_acr_ph.html

Wera - 853/1 TZ ACR PH
05056662001 - 4013288014405

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de