CASIO CASIO LAMP FREE PROJECTORS

Low Total Cost of Ownership
Eco Friendly
Lamp Change "Down Time" Eliminated
Extended Operating Life



PRO LINE XJ-H2650

3500 LUMENS • WXGA (1280 X 800) • 1.2X ZOOM • USB • WLAN

The Casio Pro series projectors with 3500 lumen brightness provides the brightness and performance needed for the largest rooms.

WHITEBOARD READY

Casio Pro series projectors are interactive whiteboard ready, using an optional Interactive Pen with any white surface, whether whiteboard, screen



or wall. Use the Interactive Pen as a PC mouse to scroll and click through software applications or as a pen to draw, write and annotate images. You can touch the screen as you would with a marker or use it from a distance, even with screens so large that you can't reach the entire surface. Choose a Pro series projector to minimize shadows, whether it is wall or ceiling mounted or on an AV cart. No special software needed. No calibration required.

IP NETWORK DIGITAL SIGNAGE CONNECTIVITY

Tie Casio Pro series models into your IP network for (remote control and maintenance. These projectors each include a standard RJ-4511 Ethernet connection and related firmware.

3-D READY

3D is not just for scientists or movie fans. It can provide

dramatic impact for business presentations– and research has shown that it can help students better engage with their lessons and it can lead to better academic performance. All Casio Pro models include 3D capability. Optional 2D-3D software can help you convert standard presentations to 3D. (3D glasses and software required and sold separately.)

MOBISHOW[®] (Smartphone compatible) Leave your laptop home and make your presentation from your mobile device. Casio Pro models will project from iPhone[®],



Android[®], iPad[®], iPod[®] and Microsoft Windows[®] Mobile, via a WiFi 802.11b/g/n connection. Software is required and included with select Casio USB models. Device application is also required and available by free download with select Casio USB models.

AUTOMATIC BRIGHTNESS ADJUSTMENT

Power saving automatic use of ECO mode and proper brightness for reduced eye fatigue.



© 2011 CASIO AMERICA, INC. All rights reserved. Casio is a registered trademark of Casio Computer Co., Ltd. in the United States and/or other countries. Specifications subject to change without notice. DLP logo is a registered trademark of Texas Instruments Incorporated. Crestron Logo is a registered trademark of Crestron Electronics, Inc. MobiShow is a registered trademark of Awind Inc.







SPECIFICATIONS XJ-H2650



	3500 lumens
Telephoto Mode	1400 : 1
	1.2X Manual
	Manual Focus
	100%
	Casio Laser & LED Hybrid
	Up to 20,000 Hours (Warranty 3 years or 6,000 Hrs)
	30 ~ 300-inch diagonal
60-inch screen	6.9 ~ 8.2 ft
100-inch screen	11.5 ~ 13.8 ft
Minimum	3.3 ft
	1.62 ~ 1.95:1
r tojection katio	DLP [®]
D. L. T.	
Color Reproduction	0.7-inch DLP Chip
	1280 x 800
	16:10
	Full Color (16.77 Million Colors)
	Vertical +30° (Auto) Vertical + or - 30° (Manual)
Including Projections	15.75 x 12.72 x 4.17 Inches
	15.75 x 12.72 x 3.78 Inches
Excluding Projections	
	15.6 lbs
	AC100~240V, 50/60Hz
Operating	Operating power: 350W (with Eco Mode "Eco 1" selected),
Standby	430W (with Eco Mode Off "Bright" selected)
	0.4 w (LAN OFF), 4.8 w (LAN ON)
	Yes
- ·	Yes
Fower On Fassword	
	Mount optional and available separately from 3rd party vendors
	M4 Qty. 4 (Optional and sold separately)
	China
Operating Temperature	41~95°F
Operating Humidity	20~80% (non condensation)
	Yes (For Operation 3,300~6,600 ft)
High Altitude Mode	16.5 ft Maximum
	3 years Parts and Labor Plus 3 Years or 6,000 hours
	light source, see Warranty Statement included with
	product for complete details
	Wireless remote control, 6' RGB cable, 6' AV cable, 6' AC Power Cord,
	Manual on CD-ROM and booklet, Wireless LAN Adapter (YW-3)
Windows [®] Compatible Only	Windows [®] Only—Wireless Connection 3/EZ-Converter
windows compatible only	
	FA/ArcSoft Media Converter 3 For CASIO Projector
	(ONLY USB MODEL)
	Active Shutter 3D Glasses (YA-G30)/ 2D-3D Conversion
	Software (YA-D30)/Interactive (IWB) Pen (YA-P10)
	Software (YA-D30)/Interactive (IWB) Pen (YA-P10)
	Software (YA-D30)/Interactive (IWB) Pen (YA-P10)
	mini D-Sub 15 pin x 2 Also use as YCbCr/YPbPr input—
	mini D-Sub 15 pin x 2 Also use as YCbCr/YPbPr input—
	mini D-Sub 15 pin x 2 Also use as YCbCr/YPbPr input— commercially available adapter required
	mini D-Sub 15 pin x 2 Also use as YCbCr/YPbPr input— commercially available adapter required WXGA (1280 x 800) 1,024,000 pixels
	mini D-Sub 15 pin x 2 Also use as YCbCr/YPbPr input— commercially available adapter required WXGA (1280 x 800) 1,024,000 pixels HDMI Type A x 1 (Locking Type)
	mini D-Sub 15 pin x 2 Also use as YCbCr/YPbPr input— commercially available adapter required WXGA (1280 x 800) 1,024,000 pixels HDMI Type A x 1 (Locking Type) Mini D sub 15 pin x 1
Input	mini D-Sub 15 pin x 2 Also use as YCbCr/YPbPr input— commercially available adapter required WXGA (1280 x 800) 1,024,000 pixels HDMI Type A x 1 (Locking Type) Mini D sub 15 pin x 1 RCA (R/L) x1, Stereo mini x 2
Input Output	mini D-Sub 15 pin x 2 Also use as YCbCr/YPbPr input— commercially available adapter required WXGA (1280 x 800) 1,024,000 pixels HDMI Type A x 1 (Locking Type) Mini D sub 15 pin x 1
•	mini D-Sub 15 pin x 2 Also use as YCbCr/YPbPr input— commercially available adapter required WXGA (1280 x 800) 1,024,000 pixels HDMI Type A x 1 (Locking Type) Mini D sub 15 pin x 1 RCA (R/L) x1, Stereo mini x 2
Output Speaker	mini D-Sub 15 pin x 2 Also use as YCbCr/YPbPr input— commercially available adapter required WXGA (1280 x 800) 1,024,000 pixels HDMI Type A x 1 (Locking Type) Mini D sub 15 pin x 1 RCA (R/L) x1, Stereo mini x 2 Stereo Mini x 1
Output Speaker Video Systems	mini D-Sub 15 pin x 2 Also use as YCbCr/YPbPr input— commercially available adapter required WXGA (1280 x 800) 1,024,000 pixels HDMI Type A x 1 (Locking Type) Mini D sub 15 pin x 1 RCA (R/L) x1, Stereo mini x 2 Stereo Mini x 1 10W Monaural Speaker NTSC/ PAL/ PAL-N/ PAL-M/ PAL60/ SECAM
Output Speaker	mini D-Sub 15 pin x 2 Also use as YCbCr/YPbPr input— commercially available adapter required WXGA (1280 x 800) 1,024,000 pixels HDMI Type A x 1 (Locking Type) Mini D sub 15 pin x 1 RCA (R/L) x1, Stereo mini x 2 Stereo Mini x 1 10W Monaural Speaker NTSC/ PAL/ PAL-N/ PAL-M/ PAL60/ SECAM 480i/480P/576i/576P/720p/1080i/1080p
Output Speaker Video Systems	mini D-Sub 15 pin x 2 Also use as YCbCr/YPbPr input— commercially available adapter required WXGA (1280 x 800) 1,024,000 pixels HDMI Type A x 1 (Locking Type) Mini D sub 15 pin x 1 RCA (R/L) x1, Stereo mini x 2 Stereo Mini x 1 10W Monaural Speaker NTSC/ PAL/ PAL-N/ PAL-M/ PAL60/ SECAM 480i/480P/576i/576P/720p/1080i/1080p Composite Video (RCA) x 1, S-Video x 1
Output Speaker Video Systems	mini D-Sub 15 pin x 2 Also use as YCbCr/YPbPr input— commercially available adapter required WXGA (1280 x 800) 1,024,000 pixels HDMI Type A x 1 (Locking Type) Mini D sub 15 pin x 1 RCA (R/L) x1, Stereo mini x 2 Stereo Mini x 1 10W Monaural Speaker NTSC/ PAL/ PAL-N/ PAL-M/ PAL60/ SECAM 480i/480P/576i/576P/720p/1080i/1080p Composite Video (RCA) x 1, S-Video x 1 RS-232C (Mini D sub 9 pin) x 1
Output Speaker Video Systems	mini D-Sub 15 pin x 2 Also use as YCbCr/YPbPr input— commercially available adapter required WXGA (1280 x 800) 1,024,000 pixels HDMI Type A x 1 (Locking Type) Mini D sub 15 pin x 1 RCA (R/L) x1, Stereo mini x 2 Stereo Mini x 1 10W Monaural Speaker NTSC/ PAL/ PAL-N/ PAL-M/ PAL60/ SECAM 480i/480P/576i/576P/720p/1080i/1080p Composite Video (RCA) x 1, S-Video x 1 RS-232C (Mini D sub 9 pin) x 1 Type A (USB 2.0) x 1, Type B x 1
Output Speaker Video Systems DTV/HDTV	mini D-Sub 15 pin x 2 Also use as YCbCr/YPbPr input— commercially available adapter required WXGA (1280 x 800) 1,024,000 pixels HDMI Type A x 1 (Locking Type) Mini D sub 15 pin x 1 RCA (R/L) x1, Stereo mini x 2 Stereo Mini x 1 10W Monaural Speaker NTSC/ PAL/ PAL-N/ PAL-M/ PAL60/ SECAM 480i/480P/576i/576P/720p/1080i/1080p Composite Video (RCA) x 1, S-Video x 1 RS-232C (Mini D sub 9 pin) x 1 Type A (USB 2.0) x 1, Type B x 1 RJ-45 x 1
Output Speaker Video Systems	mini D-Sub 15 pin x 2 Also use as YCbCr/YPbPr input— commercially available adapter required WXGA (1280 x 800) 1,024,000 pixels HDMI Type A x 1 (Locking Type) Mini D sub 15 pin x 1 RCA (R/L) x1, Stereo mini x 2 Stereo Mini x 1 10W Monaural Speaker NTSC/ PAL/ PAL-N/ PAL-M/ PAL60/ SECAM 480i/480P/576i/576P/720p/1080i/1080p Composite Video (RCA) x 1, S-Video x 1 RS-232C (Mini D sub 9 pin) x 1 Type A (USB 2.0) x 1, Type B x 1
Output Speaker Video Systems DTV/HDTV	mini D-Sub 15 pin x 2 Also use as YCbCr/YPbPr input— commercially available adapter required WXGA (1280 x 800) 1,024,000 pixels HDMI Type A x 1 (Locking Type) Mini D sub 15 pin x 1 RCA (R/L) x1, Stereo mini x 2 Stereo Mini x 1 10W Monaural Speaker NTSC/ PAL/ PAL-N/ PAL-M/ PAL60/ SECAM 480i/480P/576i/576P/720p/1080i/1080p Composite Video (RCA) x 1, S-Video x 1 RS-232C (Mini D sub 9 pin) x 1 Type A (USB 2.0) x 1, Type B x 1 RJ-45 x 1
Output Speaker Video Systems DTV/HDTV	mini D-Sub 15 pin x 2 Also use as YCbCr/YPbPr input— commercially available adapter required WXGA (1280 x 800) 1,024,000 pixels HDMI Type A x 1 (Locking Type) Mini D sub 15 pin x 1 RCA (R/L) x1, Stereo mini x 2 Stereo Mini x 1 10W Monaural Speaker NTSC/ PAL/ PAL-N/ PAL-M/ PAL60/ SECAM 480i/480P/576i/576P/720p/1080i/1080p Composite Video (RCA) x 1, S-Video x 1 RS-232C (Mini D sub 9 pin) x 1 Type A (USB 2.0) x 1, Type B x 1 RJ-45 x 1 USB memory (commercially available) (Not Included) CASIO's Digital Camera/Graphing calculator/Electronic
Output Speaker Video Systems DTV/HDTV	mini D-Sub 15 pin x 2 Also use as YCbCr/YPbPr input— commercially available adapter required WXGA (1280 x 800) 1,024,000 pixels HDMI Type A x 1 (Locking Type) Mini D sub 15 pin x 1 RCA (R/L) x1, Stereo mini x 2 Stereo Mini x 1 10W Monaural Speaker NTSC/ PAL/ PAL-N/ PAL-M/ PAL60/ SECAM 480i/480P/576i/576P/720p/1080i/1080p Composite Video (RCA) x 1, S-Video x 1 RS-232C (Mini D sub 9 pin) x 1 Type A (USB 2.0) x 1, Type B x 1 RJ-45 x 1 USB memory (commercially available) (Not Included)
	60-inch screen 100-inch screen Minimum Projection Ratio Device Type Native Resolution Native Aspect Ratio Including Projections Excluding Projections Operating Standby Kensington Compatible Power On Password