

# CASIO LAMP FREE PROJECTORS

Low Total Cost of Ownership
Eco Friendly
Lamp Change "Down Time" Eliminated
Extended Operating Life



## **SHORT THROW | XJ-ST155**

3000 LUMENS • XGA (1024 X 768) • USB • WLAN

The Casio Short Throw series projectors projects bright crisp images at close range with a full assortment of connectivity and features. 2.64 ft for 60 inch screen (0.68 Throw Ratio).

#### WHITEBOARD READY

Casio Short Throw series projectors are interactive whiteboard ready, using an optional Interactive Pen with any white surface, whether



whiteboard, screen or wall. Use the Interactive Pen as a PC mouse to scroll and click through software applications or as a pen to draw, write and annotate images. You can touch the screen as you would with a marker or use it from a distance, even with screens so large that you can't reach the entire surface. Choose a Casio Short Throw projector to minimize shadows, whether it is wall or ceiling mounted or on an AV cart. No special software needed. No calibration required.

#### IP NETWORK DIGITAL SIGNAGE CONNECTIVITY

Tie Casio Short Throw series models into your IP network for digital signage and other video server applications. These projectors each include a standard RJ-45 Ethernet connection and related firmware.

#### 3-D READY

3D is not just for scientists or movie fans. It can provide dramatic impact for business presentations— and research has shown that it can help students better engage with their lessons and it can lead to better academic performance. All Casio Short Throw models include 3D capability. Optional 2D-3D software can help you convert standard presentations to 3D. (3D glasses and software required and sold separately.)



Leave your laptop home and make your presentation from your mobile device. Casio Short Throw models will project from



iPhone®, Android®, iPad®, iPod® and Microsoft Windows® Mobile, via a WiFi 802.11b/g/n connection. Software is required and included with select Casio USB models. Device application is also required and available by free download with select Casio USB models.

#### **AUTOMATIC BRIGHTNESS ADJUSTMENT**

Power saving automatic use of ECO mode and proper brightness for reduced eye fatigue.









### SPECIFICATIONS XJ-ST155

**Brightness** Contrast Ratio 1800:1 Telephoto Mode Zoom Fixed Focus Manual Focus Lens Offset 109%

**Light Source** Casio Laser & LED Hybrid

**Estimated Operating Life** Up to 20,000 Hours (Warranty 3 years or 6,000 Hrs)

45 ~ 142-inch diagonal **Projection Screen Size** 2.64 ft **Projection Range** 60-inch screen

100-inch screen 4.62 ft

> Minimum 2 ft (45" Diagonal)

**Projection Ratio** 0.68:1 DLP®

Device Type 0.7-inch DLP Chip 1024 X 768 Native Resolution

Native Aspect Ratio

Color Reproduction Full Color (16.77 million colors)

**Keystone Correction** Vertical +30° (Auto) Vertical + or - 30° (Manual) Dimension

**Including Projections** 16.5 x 12.72 x 4.17 Inches **Excluding Projections** 16.5 x 12.72 x 3.78 Inches

Weight

**Power Source** AC100-240V, 50/60Hz

0.4 w (LAN OFF), 4.8w (LAN ON) Standby Kensington Compatible

Power On Password

Ceiling Mount Mount optional and available separately from 3rd party vendors **Mounting Screw Size** 

and Quantity M4 Qty. 4 (Optional and sold separately)

China

OTHER INFORMATION

Manufactured in

Security Compatibility

Projection System

**Operating Temperature** 41~95°F Usage Environment

> **Operating Humidity** 20~80% (non condensation) Yes (for operation 3,300~6,600 ft) High Altitude Mode

Remote Control Range 16.5 ft Maximum

Limited Warranty 3 years Parts and Labor plus 3 years or 6,000 hours

light source, See Warranty Statement included with

product for complete details

Wireless remote control, 6' RGB Cable, 6' AV Cable, 6' AC Power Cord, Included Accessories Manual on CD-ROM & booklet, Wireless LAN Adapter (YW-3)

Windows® Compatible only Windows® Only—Wireless Connection 3/EZ-Converter

FA/ArcSoft Media Converter 3 For CASIO Projector **Optional Accessories** Active Shutter 3D Glasses (YA-G30)/ 2D-3D Conversion

Software (YA-D30)/Interactive (IWB) Pen (YA-P10)

I/O CONNECTIVITY

Included Software

RGB/Component Video Input mini D-Sub 15 pin x 2 Also use as YCbCr/YPbPr input—

commercially available adapter required

Native Resolution (1024 x 768) 786,432 pixels Digital Input HDMI Type A x 1 (Locking Type) **RGB Output** Mini D sub 15 Pin x 1

Audio Input RCA (R/L) x1, Stereo mini x 2

Output Stereo Mini X 1 Speaker 10W Monaural Speaker

Video Signal Compatability Video Systems NTSC/ PAL/ PAL-N/ PAL-M/ PAL60/ SECAM

> DTV/HDTV 480i/480P/576i/576P/720P/1080i/1080p Composite Video (RCA) x 1, S-Video x 1

Video Input **Control Terminal** RS-232C (Mini D sub 9 pin) x 1 USB Type A (USB 2.0) X 1, Type B x 1

**Network Terminal** 

Connectable Equipment USB memory (commercially available) (Not included)

CASIO's Digital Camera/Graphing calculator/Electronic

dictionary (Not Included)

Wireless Capability Wireless LAN Adapter (YW-3) Is Included With USB Models

(802.11 b/g/n)







