

Technical Specifications

XMP-7500

Supported Video Formats	H.265/HEVC up to 4K (3840 x 2160) H.264/AVC up to 1080p (1920 x 1080) MPEG-4 up to 1080p (1920 x 1080) MPEG-2 up to 1080p (1920 x 1080) MPEG-1 up to 1080p (1920 x 1080) VC-1 up to 1080p (1920 x 1080)
Supported Image Formats	JPEG up to 1920 x 1080 PNG up to 1920 x 1080
Supported Audio Formats	MP3 up to 320 Kbps
Supported Open Standards	HTML5, JavaScript, and CSS W3C SMIL for cross-platform management W3C Widgets for HTML delivery Android 7.1 API
HTML5 Support	Widgets for calendar, clock, news, and web page integration HTML5 technologies including CSS and Javascript

Search ...

Advanced Signage Features	Remote commissioning AlwaysOn, AppLockto prevent unauthorized access StrongCache for continued playback even when network is not available
Connectivity	Gigabit Ethernet Wireless: 802.11 b/g/n (2.4 GHz) HDMI 2.0 (3840 x 2160 @ 60fps) Micro USB for ADB USB 2.0 x 2 3.5 mm analog stereo audio out S/PDIF out Optional 3G / 4G mobile module via USB
Local Storage	16 GB eMMC built-in Micro SD card slot (card replaces internal storage)
Expansion Options	Memory expandable to 16 GB / 32 GB with Micro SD / SDHC card
Accessories	HDMI cable External 2 dB wireless antenna Velcro Power / Micro SD card bracket
Power	Input: 100 - 240 V, 50 - 60 Hz, 0.5 A Max. Output: 12 V, 1.5 A UL/CB/PSE certified power supplies Interchangeable connector system includes US plugs (optional for EU, UK, and AUS plugs)
Environmental Tolerance	Operating temperature: -20 to 50 °C Humidity: 10 to 85 % @ 45 °C non-condensing



Search ...