Tooling

60 Ton, Latch Head, Remote Powered Single Acting Light Weight Hydraulic Tool

Y60LW Tool:

- Remote power operated
- Used with BURNDY L, wide L style dies, and HPS/Fargo-equivalent
- Base stand and metal carry case (for head only) included
- Side lift handle

For Use On:

Copper 300 - 2000 kcmil Str. Code Cable

Terminals: YA, YA-2N, YA-4N, YA-L, YA-2LN, YA-LB

Splices: YS, YST, YS-L, YS-T, YSP-T

Aluminum 250 - 2000 kcmil Str. Code Cable

Terminals: YA-A Splices: YS-A, YS-AT

Transmission & Distribution Connectors:

Tension Sleeves:

Copper: 1/0 str. - 1000 kcmil Aluminum: 1/0 str. - 2300 kcmil ACSR: 1/0 str. - 2156 (84/19 str.) kcmil

Aerial:

Copper: 4/0 str. - 2500 kcmil Aluminum: 3/0 str. - 2500 kcmil

Types: YTS, YTN, YNS, YNA, YNT, YNTA, YNU, YDS,

YDN, YCS, YCA, YCU



Wide L-dies (sold separately) can be used to save time and labor! Indicator marks on die set for ease of aligning connector properly. L725W shown.



Models:

Y60LW Standard Remote Latch Head tool

Specifications:

Output Force: 60 Tons **Tool Weight:** 43.0 lbs

12.93" x 8.06" x 8.06" Size: Die Style: L (standard or wide style);

HPS/Fargo-equivalent 60 ton dies

Operating Pressure: 10,000 PSI

Warranty: 5 year limited warranty

Accessories:

Y60LWSTAND: Metal stand for Y60LW (included with tool) Y60LWCASE: Steel carry case for Y60LW head (included

with tool)

See Gas or Electric Pumps and Hydraulic Hoses: Pump Accessories for other necessary equipment.





