

Ultra Low Freezers

ULF Series

Temperature range -40°C to -85°C / -40°F to -121°F
-40°C to -80°C / -40°F to -112°F

Style

Chest
(Horizontal)

Upright
(Vertical)

Undercounter

1 ULF SERIES CHEST AND UPRIGHT ULTRA LOW FREEZERS

■ Features

- Digital temperature control with dual display and adjustable temperature range. Scan button for setting temperature and tamper proof lockout
- Quick pull-down to operating temperature with efficient and reliable cascade refrigeration. Two large hermetic compressors ensure rapid pull-down of product load. Because of the unique design of the freezers, the pressure in the refrigeration system is held very low, eliminating excessive heat build up. This low pressure allows the freezer to operate efficiently, extending compressor life.
- Compressor life is extended by an energy-saving low stage which operates only on demand.
- Compressors are protected with a constant flow of refrigerant
- Heat is efficiently and effectively dissipated by an air-cooled condenser with two heavy-duty fans. Condenser requires no liquid coolant
- Freezer has automatic timer system that restarts unit in case of power failure
- Frost and ice build-up along the gasket is minimized by a heater harness located beneath the channel
- CFC-Free R-508B and R-404A refrigerants

■ Primary Uses

- Clinics
- Research
- Small laboratories
- Hospital rooms
- Medical clinics

■ Common Specifications

Temperature control system	Digital control displays set point and chamber temperature
Digital alarm system with relay	Battery operated alarm system will emit an audible and visual signal when there is a mechanical or electrical failure. Alarm has over and under temperature setting, alarm silencing switch, and battery test switch. Also provided is a relay for remote alarm hook-up.
Refrigeration system	Cascade type - Two hermetic compressors. CFC & HCFC free refrigerants
Construction	Chamber is 14-ga. zinc coated galvanized steel. Exterior is 16-ga. steel. Powder coated cool gray finish.
Electrical requirements	115V, 60 Hz, 1 phase 208V, 60 Hz, 1 phase 230V, 60 Hz, 1 phase 220V, 50 Hz, 1 phase 220V, 60 Hz, 1 phase
Optional accessories	Chart recorder, CO ² and LN ² back-up system, Racks, Cold safety gloves

■ Unique Specifications for CHEST TYPE (HORIZONTAL) Ultra Low Freezers - Top Opening

Model	Capacity		Rack Capacity	Temp. Range	Internal Dimension		External Dimension	
	Liters	Cu. ft.			Inch	Centimeter	Inch	Centimeter
ULF001C	56	2	6	-40°C to -85°C / -40°F to -121°F	17" x 14" x 14"	43 x 35 x 35	25.25" x 25.75" x 40"	64 x 65 x 101
ULF101C	83	3	8	-40°C to -85°C / -40°F to -121°F	24" x 12" x 18"	60 x 30 x 45	34.5" x 25.25" x 48"	87 x 64 x 121
ULF201C	142	5	15	-40°C to -85°C / -40°F to -121°F	30" x 18" x 16"	76 x 45 x 40	40.5" x 31" x 47"	102 x 81 x 119
ULF301C	255	9	16	-40°C to -85°C / -40°F to -121°F	46" x 16" x 20"	116 x 40 x 50	57.5" x 29" x 46.5"	146 x 73 x 116
ULF401C	340	12	27	-40°C to -85°C / -40°F to -121°F	55" x 19" x 20"	139 x 48 x 50	65.5" x 32" x 47.5"	166 x 81 x 120
ULF501C	400	14	30	-40°C to -85°C / -40°F to -121°F	62" x 20" x 20"	157 x 50 x 50	72.5" x 33" x 47.5"	184 x 83 x 120
ULF601C	480	17	36	-40°C to -85°C / -40°F to -121°F	69" x 20" x 21"	175 x 50 x 53	81.25" x 33.5" x 48.5"	206 x 85 x 123
ULF701C	594	21	36	-40°C to -80°C / -40°F to -112°F	81" x 21.5" x 21"	205 x 54 x 53	91" x 36" x 49"	231 x 91 x 124
ULF801C	626	22	36	-40°C to -85°C / -40°F to -121°F	67" x 19" x 30"	170 x 48 x 76	98" x 36" x 43.5"	248 x 91 x 110
ULF901C	766	27	48	-40°C to -80°C / -40°F to -112°F	67" x 23" x 31.25"	170 x 57 x 79	98" x 36" x 43.5"	248 x 91 x 110

CHEST TYPE (HORIZONTAL) Ultra Low Freezers - Top Opening



56L
ULF001C



83L
ULF101C



142L
ULF201C



340L
ULF401C



480L
ULF601C



766L
ULF901C

■ Unique Specifications for **UPRIGHT TYPE (VERTICAL) Ultra Low Freezers**

Model	Capacity		Rack Capacity	Shelving	Temp. Range	Internal Dimension		External Dimension	
	Liters	Cu. ft.				Inch	Centimeter	Inch	Centimeter
ULF401U	370	13	15	4 adjustable (5 compartments)	-40°C to -85°C / -40°F to -121°F	20" x 22" x 51.25	50 x 55 x 130	35" x 34.5" x 79.5"	88 x 87 x 201
ULF501U	505	18	20	4 adjustable (5 compartments)	-40°C to -85°C / -40°F to -121°F	23" x 26" x 51.25"	58 x 66 x 130	40" x 36" x 79.5"	101 x 91 x 201
ULF601U	626	22	25	4 adjustable (5 compartments)	-40°C to -85°C / -40°F to -121°F	28.5" x 26" x 51.25"	72 x 66 x 130	43" x 37" x 79.5"	109 x 93 x 201
ULF701U	710	25	30	4 adjustable (5 compartments)	-40°C to -85°C / -40°F to -121°F	34" x 25" x 51.25"	86 x 63 x 130	50" x 37" x 79.5"	127 x 93 x 201
ULF801U	792	28	30	4 adjustable (5 compartments)	-40°C to -80°C / -40°F to -112°F	38" x 25" x 51.25"	96 x 63 x 130	54" x 37" x 79.5"	137 x 93 x 201
ULF901U	877	31	35	4 fixed (5 compartments)	-40°C to -80°C / -40°F to -112°F	42" x 25" x 51.25"	106 x 63 x 130	60.5" x 37" x 79.5"	153 x 93 x 201



370L
ULF401U



505L
ULF501U



710L
ULF701U



877L
ULF901U

2 ULF SERIES UNDERCOUNTER MINI-CHEST ULTRA LOW FREEZERS

Common Specifications

Temperature range	-40°C to -85°C / -76°F to -121°F
Temperature control system	Digital data logging. Battery back-up, Hi/Low alarm.
Clearance	4" on sides and back.
Alarm system	Battery operated alarm system will emit an audible and visual signal when there is a mechanical or electrical failure. A relay for a remote alarm hook-up is also provided
Doors	Single solid, locking
Legs	Four, leveling
Evaporator	Cold wall
Defrost	Manual
Insulation	Polyurethane CFC Free.
Electrical requirements	115V, 60 Hz, 1 phase
Supply plug	NEMA 5-15P ETL listed

Unique Specifications for UNDERCOUNTER Ultra Low Freezers

Model	Capacity		Internal Dimension		External Dimension	
	Liters	Cu. ft.	Inch	Centimeter	Inch	Centimeter
ULF001UN	7	.25	5.75" x 5.5" x 12"	15 x 14 x 31	15.75" x 25" x 26.25"	40 x 60 x 66
ULF101UN	54	2	14" x 18" x 12.5"	35 x 45 x 31	23" x 27" x 32"	58 x 68 x 81
ULF201UN	94	3	14" x 19.25" x 20.75"	36 x 49 x 53	37.5" x 28.5" x 32"	95.25 x 72 x 81



7L
ULF001UN



54L
ULF101UN



94L
ULF201UN