

COMPACT STERILIZER

SK200C/210C/300C/310C

NEW

Space-saving, affordable, compact sterilizer,
ideal for research facilities

Features

Easy to use

- Space-saving size - 24 / 30 Liter
- Mobile on wheels
- Powerful 1500W pipe heater
- Easy to read 4 digit LED display
- Three Way Drain Valve eliminates air at the bottom of chamber during operation, and drains waste water after operation
- Programmable sterilizing and temperature functions
- Timer Setting Range 0 to 999 min.

Increased Safety Features

- Water level detection sensor with alarm
- Overheat Protection Sensor
- Lid closure sensor (Inter lock)
- Pressure lamp and Inter Lock sensor lamp
- New improved silicone lid gasket and easy to replace



SK300C

Specifications

Model	SK200C	SK210C	SK300C	SK310C
Temp. range for sterilization	50~126°C			
Maximum operational pressure	0.142MPa (at 126°C)			
Pipe heater	115V, 1500W	220V, 1500W	115V, 1500W	220V, 1500W
Temp. setting/display method	Digital setting / 4 digit LED display			
Temp. controller	PID controlled by microprocessor			
Internal dimensions of chamber (mm)	Dia280 x H360		Dia280 x H440	
External dimensions (mm)	W353 x Dia386 x H737		W353 x Dia386 x H827	
Internal capacity	24L		30L	
Power source 50/60Hz	AC 115V, 15A	AC 220V, 9A	AC 115V, 15A	AC 220V, 9A
Weight	~26.5kg		~31.5kg	