

# Laboratory Refrigerators

## SLR Series

Temperature range 2°C~8°C / 36°F~46°F

Door type Glass Door Solid Door

### SLR SERIES LABORATORY REFRIGERATORS with GLASS DOOR

#### Common Specifications

Temperature range	2°C to 8°C / 36°F to 46°F
Temperature control system	Digital display with Hi/Low alarm, Alarm relay dry contacts, Min/Max memory, Power failure relay, Battery back up
Access port	1/2" Diameter
Interior and exterior finish	White coated steel
Interior lighting	LED light
Insulation	Polyurethane foam
Refrigerant	R290 CFC free
Air circulation	Forced air
Defrost	Cycle, Automatic
Compressor	1/5 hp (SLR1301DG, SLR1301DGSL) 2 x 1/3 hp (SLR2001TG)
Voltage	115V, 60 Hz, 1 phase
Running amps / breaker	5A / 15A (SLR301SG) 6A / 15A (SLR701SG to SLR1301DGSL) 12A / 15A (SLR2001TG)
Supply plug	5-15P NEMA UL listed
Optional accessories	Extra shelf, Leg seismic restraints, wall seismic restraints

#### Unique Specifications

Model	Capacity		Door	Shelves	Internal Dimension		External Dimension		Weight	Casters
	Liters	Cu. ft.			Inch	Centimeter	Inch	Centimeter		
SLR301SG	340	12	Single glass, locking	4 adjustable	18.9" x 19.69" x 45.28"	48 x 50 x 115	23.62" x 25.27" x 71.75"	60 x 64 x 182	165	4 locking
SLR701SG	708	25	Single glass, locking	4 adjustable	23.62" x 26.18" x 59.84"	60 x 66 x 152	28.35" x 31.5" x 79.25"	72 x 80 x 201	253	4 locking
SLR801SG	850	30	Single glass, locking	4 adjustable	27.50" x 30.80" x 61.84"	70 x 78 x 157	33.85" x 37.80" x 81.12"	86 x 96 x 206	420	4 locking
SLR1301DG	1387	49	Two hinged glass, locking	8 adjustable	51.97" x 26.18" x 59.84"	132 x 66 x 152	56.69" x 31.5" x 79.25"	144 x 80 x 201	450	6 locking
SLR1301DGSL	1387	49	Two sliding glass	8 adjustable	51.97" x 26.18" x 59.84"	132 x 66 x 152	56.69" x 31.5" x 79.25"	144 x 80 x 201	450	6 locking
SLR2001TG	2039	72	Three hinged glass, locking	12 adjustable	80.31" x 26.18" x 59.84"	204 x 66 x 152	85.04" x 33.46" x 79.25"	216 x 85 x 201	700	12 adjustable



340L  
SLR301SG



850L  
SLR801SG



1387L  
SLR1301DGSL



2039L  
SLR2001TG

## SLR SERIES LABORATORY REFRIGERATORS with SOLID DOOR

### Common Specifications

Temperature range	2°C to 8°C / 36°F to 46°F
Temperature control system	Digital display with Hi/Low alarm, Alarm relay dry contacts, Min/Max memory, Power failure relay, Battery back up
Access port	1/2" Diameter
Interior and exterior finish	White coated steel
Interior lighting	LED light
Insulation	Polyurethane foam
Refrigerant	R290 CFC free
Air circulation	Forced air
Defrost	Cycle, Automatic
Compressor	1/5 hp (SLR1301DS)
Voltage	115V, 60 Hz, 1 phase
Running amps / breaker	6A / 15A
Supply plug	5-15P NEMA UL listed
Optional accessories	Extra shelf, Leg seismic restraints, wall seismic restraints

### Unique Specifications

Model	Capacity		Door	Shelves	Internal Dimension		External Dimension		Weight	Casters
	Liters	Cu. ft.			Inch	Centimeter	Inch	Centimeter		
<b>SLR701SS</b>	708	25	Single solid, locking	4 adjustable	23.62" x 26.18" x 59.84"	60 x 66 x 152	28.35" x 31.5" x 79.25"	72 x 80 x 201	275	4 locking
<b>SLR801SS</b>	850	30	Single solid, locking	4 adjustable	27.50" x 30.80" x 61.84"	70 x 78 x 157	33.85" x 37.80" x 81.12"	86 x 96 x 206	420	4 locking
<b>SLR1301DS</b>	1387	49	Two hinged solid, locking	8 adjustable	51.97" x 26.18" x 59.84"	132 x 66 x 152	56.69" x 31.5" x 79.25"	144 x 80 x 201	450	6 locking



**708L**  
SLR701SS



**850L**  
SLR801SS



**1387L**  
SLR1301DS