

STERILIZER OVERVIEW

STEAM Sterilization
 DRY Sterilization

Benchtop



SK

Internal Capacity: 18L

- Low cost, space saving
- Programmable
- Easy to read 4 digit LED display

Compact



SK

24, 30L

Standard **without dryer**



SN

Internal Capacity: 32, 47L

- Ergonomically designed easy top loading
- Programmable / preset-programs for commonly used sample types
- Cooling fan to shorten cool down time

Large capacity **without dryer**



SQ

Internal Capacity: 50, 80L



SQL

Internal Capacity: 85, 110L

- Ergonomically designed easy top loading
- Programmable / preset-programs for commonly used sample types
- Cooling fan to shorten cool down time

Standard **with dryer**



SM

Internal Capacity: 20, 32, 47L

- Programmable
- Pre-installed drying cycle
- Quick drying capability making samples ready to use right after sterilization

Large capacity **with dryer**



SM

Internal Capacity: 50, 80L

- Programmable with 7" interactive touch screen
- Fully automatic sterilization and drying
- 11L heat resistant stainless steel bottle

Standard dry sterilization



SI

Internal Capacity: 77, 159L

- Dry heat sterilization through natural convection
- Programmable: 6 patterns, 30 steps
- Temp. rising time to 260°C: ~70min.

Large capacity dry sterilization



SK

Internal Capacity: 99, 162, 300L

- Dry heat sterilization through natural or forced convection
- Programmable: 99 patterns, 99 steps
- Temp. rising time to 260°C: ~60min.