

Undercounter and Countertop Refrigerators

UCR Series

Temperature range 2°C to 8°C / 36°F to 46°F

Door type Solid Door Glass Door

Internal capacity 70L 2.5 cu.ft. 113L 4 cu.ft.

Specifications

Specifications

Model	UCR001	UCR001G	UCR101	UCR101G
Capacity	70L / 2.5 cu.ft.	70L / 2.5 cu.ft.	113L / 4 cu.ft.	113L / 4 cu.ft.
Door	Single solid, locking	Single glass, locking	Single solid, locking	Single glass, locking
Temperature range	2°C to 8°C / 36°F to 46°F			
Temperature control	Digital display with hi/low alarm, Alarm relay dry contacts			
Access port	1/2"			
Shelves	2 full	2 full	2 adjustable, 1 full, 1 half	2 full, 1 half
Insulation	Polyurethane foam			
Refrigerant	R600			
Compressor	-	-	1/3 hp	
Air circulation	Forced air			
Defrost	Cycle, Automatic			
Exterior construction	Painted white			
Internal dimensions (WxDxH)	17" x 15" x 17" 43 x 38 x 43 cm		20" x 15.25" x 22.75" 51 x 38 x 57 cm	20" x 17.75" x 24.5" 51 x 45 x 62 cm
External dimensions (WxDxH)	20" x 21.5" x 25" 50 x 54 x 63 cm		23.75" x 21.5" x 32" 60 x 64 x 84 cm	
Weight	110 lbs.		150 lbs.	
Voltage	115V, 60 Hz, 1/10 HP			
Running amps / breaker	1.2A / 15A			
Supply plug	5-15P NEMA			
Optional accessory	Chart recorder			



70L
UCR001

113L
UCR101



70L
UCR001G

113L
UCR101G