






OVEN OVERVIEW

	Series	Model No.	Operating Temperature Range	Internal Capacity (L)	Program	Characteristics
Natural Convection	DX	302C/312C	RT+5~300°C	28	--	- Economical - High temperature - Do not use fans. Heat rises by natural air convection for a slower heat flow 
		402C/412C		74	--	
		602C/612C	RT+5~280°C	153	--	
	DVS	403C/413C	RT+10~260°C	99	Yes	
		603C/613C		162	Yes	
	DR	201	300~700°C	13.75	Yes	
	DG	400C/410C	RT+5~70°C	92	--	
		440C/450C		92	--	
		800C/810C		445	--	
		840C/850C*		445	--	
Forced Convection	DKL	301C/311C	RT+10~260°C	27	--	- High level of air circulation, accuracy and uniformity - Use fan motors for vertical air circulation providing a more uniform heat flow - Built-in exhaust port - Calibration offset function 
		401C/411C		90	--	
		601C/611C		150	--	
	DKN	303	RT+10~260°C	27	Yes	
		400/410	RT+10~270°C	90	Yes	
		600/610		150	Yes	
		810		300	Yes	
	DKV	910	RT+10~220°C	545	Yes	
		401/411	RT+20~210°C	90	Yes	
		601/611		150	Yes	
	DNE	811	RT+15~210°C	300	Yes	
		911		540	Yes	
	DNF	301	RT+15~260°C (Wind velocity: 1~10)	27	Yes	
		401/411		90	Yes	
		601/611		150	Yes	
		811		300	Yes	
		911		540	Yes	
Fine	DF	412	RT+15~260°C	91	Yes	- Rapid & high volume of airflow - Use forced convection for a horizontal air flow as opposed to vertical - Very high uniformity, accuracy and performance - Quick exhaust and cooling 
		612		216	Yes	
		832	RT+15~200°C	512	Yes	
		1032		1000	Yes	
	DH	412	RT+15~360°C	91	Yes	
		612		216	Yes	
		650Z	RT+10~500°C	216	Yes	
		832	RT+15~300°C	512	Yes	
		1032		1000	Yes	
Vacuum	ADP	200C/210C	40~240°C	10	Yes	- Handle sensitive samples at lower temperature - Heat is evenly distributed from arrangement of the heaters against outer chamber walls - Reduced oxidation 
		300C/310C		27	Yes	
	SDP	300/310	RT+10~220°C	47.2	Yes	
		400/410		127.4	Yes	
		610	RT+15~220°C	264	Yes	
	DP	43C	40~200°C	91	Yes	
		63C		216	Yes	
		83C		512	Yes	
		104C		1000	Yes	

OVEN OVERVIEW

	Series	Model No.	Operating Temperature Range								Internal Capacity (L)	Program	Characteristics	
			0	100	200	300	400	500	600	700				
Inert	DN	411IE	RT+15~360°C									95	Yes	- Creates non-oxidative environment - Controllable nitrogen flow 
		611IE										223	Yes	
Clean	DE	411	RT+30~260°C									91	Yes	- Class 100 - Adopts anti-fouling casters preventing wheel contamination during transportation - Improved optional accessories and more customization options 
		611	RT+30~260°C									216	Yes	
	DT	411	RT+30~360°C									91	Yes	
		611	RT+30~360°C									216	Yes	
	DES	830	RT+30~260°C									327	Yes	- Class 100 - Stable cleanliness through forced circulation with rear exhaust 
	DTS	830	RT+30~360°C									327	Yes	