

# Laboratory Freezers

## SLF Series

Temperature range -18°C to -25°C / 0°F to -13°F

Door type Solid Door

### SLF SERIES LABORATORY FREEZERS with SOLID DOOR

#### Common Specifications

Temperature range	-18°C to -25°C / 0°F to -13°F
Temperature control system	Digital display with Hi/Low alarm, Alarm relay dry contacts, Min/Max memory, Power failure relay, Battery back up
Access port	1/2" Diameter
Interior and exterior finish	White coated steel
Interior lighting	LED light
Insulation	Polyurethane foam
Refrigerant	R290 CFC free
Air circulation	Forced air
Evaporator	Adjustable
Defrost	Automatic
Compressor	1 hp (SLF1301DS)
Voltage	115V, 60 Hz, 1 phase
Running amps / breaker	10.3A / 15A
Supply plug	5-15P NEMA UL listed (SLF701SS) 5-20P NEMA UL listed (SLF1301DS)
Optional accessories	Extra shelf, Leg seismic restraints, wall seismic restraints

#### Unique Specifications

Model	Capacity		Door	Shelves	Internal Dimension		External Dimension		Weight	Casters
	Liters	Cu. ft.			Inch	Centimeter	Inch	Centimeter		
<b>SLF701SS</b>	708	25	Single solid, locking	3 adjustable	23.62" x 26.18" x 59.84"	60 x 66 x 152	28.35" x 31.5" x 79.25"	72 x 80 x 201	255	4 locking
<b>SLF1301DS</b>	1387	49	Two solid, locking	6 adjustable	51.97" x 26.18" x 59.84"	132 x 66 x 152	56.69" x 31.5" x 79.25"	144 x 80 x 201	450	6 locking



**708L**  
SLF701SS



**1387L**  
SLF1301DS