

Laboratory Freezers

SLF Series

Temperature range -18°C to -25°C / 0°F to -13°F

Door type Solid Door

SLF SERIES LABORATORY FREEZERS with SOLID DOOR

Common Specifications

Temperature range	-18°C to -25°C / 0°F to -13°F
Temperature control system	Digital display with Hi/Low alarm, Alarm relay dry contacts, Min/Max memory, Power failure relay, Battery back up
Access port	1/2" Diameter
Interior and exterior finish	White coated steel
Interior lighting	LED light
Insulation	Polyurethane foam
Refrigerant	R290 CFC free
Air circulation	Forced air
Evaporator	Adjustable
Defrost	Automatic
Compressor	1 hp (SLF1301DS)
Voltage	115V, 60 Hz, 1 phase
Running amps / breaker	10.3A / 15A
Supply plug	5-15P NEMA UL listed (SLF701SS) 5-20P NEMA UL listed (SLF1301DS)
Optional accessories	Extra shelf, Leg seismic restraints, wall seismic restraints

Unique Specifications

Model	Capacity		Door	Shelves	Internal Dimension		External Dimension		Weight	Casters
	Liters	Cu. ft.			Inch	Centimeter	Inch	Centimeter		
SLF701SS	708	25	Single solid, locking	3 adjustable	23.62" x 26.18" x 59.84"	60 x 66 x 152	28.35" x 31.5" x 79.25"	72 x 80 x 201	255	4 locking
SLF1301DS	1387	49	Two solid, locking	6 adjustable	51.97" x 26.18" x 59.84"	132 x 66 x 152	56.69" x 31.5" x 79.25"	144 x 80 x 201	450	6 locking



708L
SLF701SS



1387L
SLF1301DS