SPECIFICATIONS

Image Intensifier Tube	Gen 2+ or Gen 3
Magnification	1x
Lens System	27 mm, F/1.3
FOV	40°
Focus Range	0.25 m to Infinity
Diopter Adjustment	-6 to +2 diopters
Interpupillary Distance	56 to 72 mm
Eye Relief	25 mm
LED Indicators (in the FOV)	- Low Battery - IR On - Excessive Light Conditions
Manual Gain Control	Yes
Bright Light Cut-Off	Yes
Automatic Shut-Off System	Yes
Infrared Illuminator	Yes; Two power levels
Battery Type	One CR123A (3V) or AA (1.5 V)
Battery Life (Operating)	Up to 20 hours at 20°C (up to 80 hrs with optional battery pack)
Operating Temperature Range	-40°C to +50°C (-40°F to +122°F)
Storage Temperature Range	-50°C to +70°C (-58°F to +158°F)
Weight	645 g (1.42 lb)
Overall Dimensions	115 × 118 × 74 mm (4.5 × 4.6 × 2.9 in)
Package Includes	Night Vision Goggles, NVG Interface Shoe, Bayonet/Horn Interface Shoe, Demist Shield (2), Sacrificial Window (2), Soft Carrying Case, Lens Cloth, Battery Adapter, User Manual

Specifications are subject to change without notice. Images are for illustration purposes only.

OPTIONAL EQUIPMENT

AGM G50 Afocal Magnifier Lens Kit, 3X (2 lenses and adapter) (P/N 6102AFK1)

AGM Goggle Kit W G50 (P/N 6104GK51)

AGM Helmet Mount G50MP for MICH and PASGT Helmets ($\ensuremath{\mathsf{P/N}}$ 6103HM51)

AGM Helmet Mount G50S for Shroud (P/N 6103HS51)

NVG Interface Shoe with Connector (P/N 6108ISC1)

Mini-Rail Interface Shoe (P/N 6506MRN1)

Battery Locking Plate Adapter (P/N 6108BLP1)

AGM Battery Pack (P/N 6108BPA1)

AGM External Battery Pack Kit G50 (P/N 6108EBP1)

Sioux850-W Kit (includes Sioux850 Long-Range Infrared Illuminator, Mount, Adapter, Rechargeable Battery and Charger) (P/N 501SIOUW850IR1)

Hard Case (P/N 6610HCS1)





MAIN OFFICE | 173 West Main Street | PO Box 962 | Springerville, AZ 85938, USA Tel. +1.928.333.4300 | info@agmglobalvision.com | www.agmglobalvision.com

EUROPEAN OFFICE | Andrey Lyapchev #7 | Sofia, P.C. 1756 | Bulgaria Tel. +35.988.412.5573 | info@agmglobalvision.eu | www.agmglobalvision.eu

www.agmglobalvision.com