

ViewSonic® EPOSTER EP4220

Key Features

- Features



Product Description

Free-standing dynamic advertising is easy with ViewSonic's EP4220—an ultra-slim 42" Full HD digital ePoster LED display. Retail and information messaging is easily broadcast via the display's internal media player, or by connecting your own media to the industry-standard HDMI or VGA input connections. ViewSonic's ePoster display can also be connected to a corporate network by adding a network capable media player. Security is achieved through the locking back cover. Compatible ViewSonic media players are available in both X86 and RISC (Linux) configurations. This display is ideal in highvisibility locations such as retail settings, hotel lobbies, banks and universities.

Visit Us - www.viewsonic.com

DISPLAY

Panel Size:	42"
Type/Tech:	TFT LCD Module with LED Backlight
Display Area (mm):	930.24(H) x 523.26(V)
Aspect Ratio:	9:16
Native Resolution:	1080x1920
Colors:	16.7M
Brightness:	350 nits (typ.)
Contrast Ratio:	3000:1 Typ.
Response Time:	6.5ms
Viewing Angles:	H = 178, V = 178 typ.
Backlight Life:	30,000 Hours Typ.
Surface Treatment:	AG coating (3H)
Orientation:	Portrait

TOUCH**STORAGE****INPUT**

HDMI:	x1
RGB / VGA:	x1
Audio:	x1 PC audio(3.5 mm)
RS232:	x1
SD/SDHC:	SD/CF x1, (for expand storage)

OUTPUT**LAN****USB**

Type A:	x1
---------	----

SPEAKERS

2.5W x 2

COMPATIBILITY

RGB PC/HDMI PC:	Refer to timing table
HDMI:	480i, 480p, 720p, 1080i, 1080p

CONTROLS

Physical- Top OSD:	PICTURE: Picture Mode, Color Temperature, Aspect Ratio, Noise Reduction, Screen AUDIO: Sound Mode, Balance, Auto Volume, Surround Sound, EQ TIME: Clock, On/Off Time, Time Volume, Display Mode, Display Mirror, User Reset, Software Version, Software Update (USB) OPTION: OSD Language, Subtitle Color, Subtitle BG Color, Subtitle Speed, Play Mode, Photo Time, Picture Slide Show, USB Copy Mode
--------------------	---

Multimedia:	JPG, MPEG 1/2/3, H.264, Xvid 1.00-AVI, MP4, WMA, MP3, M4A (AA CC)
-------------	---

BUNDLE SOFTWARE**POWER**

Voltage:	100-240VAC +/- 10% 50/60Hz Wide Range
Consumption:	180W (max.) < 0.5 W ("Off")

ERGONOMICS**OPERATING CONDITIONS**

Temperature (° C):	0°C to 45°C
Humidity:	10% ~ 85% non-condensing

DIMENSIONS**(W X H X D)**

Physical (inch / mm):	27.0 x 72.2 x 17.7 / 685 x 1835 x 450
Packaging (inch / mm):	32.3 x 76.7 x 21.3 / 820 x 1950 x 540

WEIGHT

Net (lb / kg):	125 / 57
Gross (lb / kg):	147 / 67

REGULATIONS

FCC

PACKAGE CONTENTS

1. EP4220 ePoster 2. power cable 3. VGA cable 4. remote control with batteries 5. Quick Start Guide 6. ViewSonic Wizard CD (with User Guide) *Actual content may differ from market to market
--