## 8122WI LCD Projector



Accessories		
Supplied Accessories	Remote control, AAA batteries x 4, power cord (4.5m) x 1, computer cable, cable cover, adapter cover, USB cable, interactive pen x 2, pen tips x 4, AA batteries x 2, PIN code sticker	
Optional Accessories	Finger touch unit (FT-01B), interactive pen (I-PEN4), wireless adapter (USBWL5G), wall mount (HAS-WM05), table stand kit (TT-03), Apple TV bracket (HAS-RB01)	
Replacement Parts		
Lamp	456-8109W	
Remote Control	HL03033	
Filter	UX37191	

## **Projection Throw Chart (In inches)**

Screen Size 16:1	0 Throw D	Throw Distance	
Diagonal	Distance from edge of projector to screen	Distance from mirror cover to screen	
60	5.0	16.1	
70	7.8	18.9	
80	10.5	21.6	
90	13.3	24.4	
100	16.1	27.1	

Throw Ratio: (distance: width) 0.2:1 from edge of projector 0.3:1 from mirror cover



- Comes bundled with Dukane interactive projectors
- World-class integrated software
- Collaborate, integrate, annotate





## **DUKANE CORP**

Audio Visual Products 2900 Dukane Drive, St. Charles, Illinois 60174 Toll-free: 888-245-1966 • Fax: 630-584-5156

E-mail: avsales@dukane.com www.dukane.com/av

Specifications				
	Projection Technology	3LCD, 3 chip technology		
Display	Resolution	WXGA 1280 x 800		
	White Light Output	3,700 ANSI lumens		
	Color Light Output	3,700 ANSI lumens		
	Colors	16.7 million colors		
	Aspect Ratio	Native 16:10, 4:3, 16:9, 14:9 and zoom compatible		
	Contrast Ratio	20,000 : 1 (using active IRIS)		
	Throw Ratio (distance : width)	0.2 : 1 from edge of projector to screen 0.3 : 1 from mirror cover to screen		
	Focus Distance	16" - 27" from mirror cover to screen		
	Display Size	60" - 100"		
Lens & Operation	Lens	f = 4.21 mm, digital zoom x 1.35, powered focus		
	Lamp Wattage	250W		
	Expected Lamp Life*	Approximately 4,000 hours (standard mode) 6,000 hours (Eco-2 mode)		
	Expected Filter Life**	Approximately 4,000 hours		
	Speaker Output	16W x 1		
	Keystone	H and V: +/- 5°		
. <u>Ş</u>	Computer	VGA, SVGA, WXGA, WXGA+, SXGA, SXGA+, UXGA (compressed), MAC 16"		
	H-Sync	15 kHz - 106 kHz		
Compatibility	V-Sync	50 Hz - 120 Hz		
pat	Composite Video	NTSC, NTSC4.43, PAL, PAL-M, -N, SECAM		
E o	Component Video	480i, 480p, 576i, 576p, 1080i, 1080p		
ŏ	HDMI	480i, 480p, 576i, 576p, 1080i, 1080p, computer signal TMDS clock 27 MHz - 150 MHz		
	MHL In	HDMI connector x 1 (HDCP compliant) shared with HDMI 1 input		
	Digital Input	HDMI x 2 (HDCP compliant) (1 shared with MHL)		
	HDMI In	HDMI Connector x 2 (HDCP compliant)		
	Computer Input 1	15-pin mini D-sub x 1 (shared with analog component video input)		
	Computer Input 2	15-pin mini D-sub x 1 (shared with component video input and monitor out)		
	Computer Monitor Output	15-pin mini D-sub x 1 (shared with computer in 2)		
2	Video Input	DCA ingles 1		
Connectors	Composite Video Component Video	RCA jack x 1  15-pin D-sub x 2 (shared with computer in 1/2)		
Jue	Audio Input			
- ဝိ	Audio Output	3.5 mm stereo mini jack x 1, RCA jack (L/R) x 1 3.5 mm stereo mini jack x 1		
	Network LAN Wired	RJ-45 port (10 base-T / 100 base-TX)		
	Network LAN Wireless	USB-A, IEEE802.11 b/g/n - optional wireless adapter required		
	USB	Type A x 2 (PC-less presentation, wireless adapter) Type B x 1 (USB display or mouse control)		
	Microphone In	3.5 mm mini jack x 1		
	Control Terminals	9-pin D-sub x 1 (RS-232 control)		
	Power Supply	AC100-120V / AC220-240V, 50/60Hz		
≥	Power Consumption	380W/360W		
Ratings & Warranty	Operating Temperature	32°F - 104°F (0°C - 40°C)		
	Dimensions (W x D x H)	14.8" x 14.2" x 5.4" (excluding protruding parts) Shipping 22.2" x 18.9" x 9.6"		
	Weight	Approximately 10.1 lbs. / Shipping 19.0 lbs.		
	Approvals	UL 60950-1 / cUL, FCC part 15 subpart B Class B		
	Warranty	Five (5) year limited warranty plus Dukane's 1 year Peace of Mind Loaner Program		
	UPC	605194006779		

Actual lamp life will vary by individual lamp based on environmental conditions, selected operating mode, user settings and usage. Hours of average lamp life specified are not guaranteed and do not constitute part of the product or lamp warranty. Lamp brightness decreases over time.

Actual filter life will vary by individual filter based on environmental conditions, selected operating mode, user settings and usage. Hours of average filter life specified are not guaranteed and do not constitute part of the product warranty.







