

Accessories

Supplied Accessories	Remote control, AA batteries x 2, power cord (4.5m) x 1, computer cable, cable cover, adapter cover, PIN code sticker
Optional Accessories	Wireless adapter (USBWL11N), Table Stand kit (TT-03), Apple TV bracket (HAS-RB01)
Replacement Parts	
Lamp	456-8109W
Remote Control	HL03033
Filter	UX37191

Projection Throw Chart (In inches)

Screen Size 16:10		
Diagonal	Distance from edge of projector to screen	Distance from mirror cover to screen
60	5.0	16.1
70	7.8	18.9
80	10.5	21.6
90	13.3	24.4
100	16.1	27.1

Throw Ratio: (distance : width)
0.2 : 1 from edge of projector
0.3 : 1 from mirror cover



HI0577-02/18
All specifications subject to change without notice.
3LCD and the 3LCD logo are registered trademarks of the Seiko Epson Corporation.
©2018 Dukane America, Ltd. All Rights Reserved.

DUKANE CORP.

Audio Visual Products
2900 Dukane Drive, St. Charles, Illinois 60174
Toll-free: 888-245-1966 • Fax: 630-584-5156
E-mail: avsales@dukane.com
www.dukaneav.com

Specifications

Display	Projection Technology	3LCD, 3 chip technology
	Resolution	WXGA 1280 x 800
	White Light Output	3,700 ANSI lumens
	Color Light Output	3,700 ANSI lumens
	Colors	16.7 million colors
	Aspect Ratio	Native 16:10, 4:3, 16:9, 14:9 and zoom compatible
	Contrast Ratio	20,000 : 1 (using active IRIS)
Lens & Operation	Throw Ratio (distance : width)	0.2 : 1 from edge of projector to screen 0.3 : 1 from mirror cover to screen
	Focus Distance	16" - 27" from mirror cover to screen
	Display Size	60" - 100"
	Lens	f = 4.21 mm, digital zoom x 1.35, powered focus
	Lamp Wattage	250W
Compatibility	Expected Lamp Life*	Approximately 4,000 hours (standard mode) 6,000 hours (Eco-2 mode)
	Expected Filter Life**	Approximately 4,000 hours
	Speaker Output	16W x 1
Connectors	Keystone	H and V: +/- 5°
	Computer	VGA, SVGA, WXGA, WXGA+, SXGA, SXGA+, UXGA (compressed), MAC 16"
	H-Sync	15 kHz - 106 kHz
	V-Sync	50 Hz - 120 Hz
	Composite Video	NTSC, NTSC4.43, PAL, PAL-M, -N, SECAM
	Component Video	480i, 480p, 576i, 720p, 1080i, 1080p
	HDMI	480i, 480p, 576i, 720p, 1080i, 1080p, computer signal TMDS clock 27 MHz - 150 MHz
	Digital Input	HDMI x 2 (HDCP compliant)
	HDMI IN	HDMI Connector x 2 (HDCP compliant)
	Computer Input 1	15-pin mini D-sub x 1 (shared with analog component video input)
Ratings & Warranty	Computer Input 2	15-pin mini D-sub x 1 (shared with component video input and monitor out)
	Computer Monitor Output	15-pin mini D-sub x 1 (shared with computer in 2)
	Video Input	
	Composite Video	RCA jack x 1
	Component Video	15-pin mini D-sub x 2 (shared with computer in 1/2)
	Audio Input	3.5 mm stereo mini jack x 1, RCA jack (L/R) x 1,
	Audio Output	3.5 mm stereo mini jack x 1
	Network LAN Wired	RJ-45 port (10 base-T / 100 base-TX)
	Network LAN Wireless	USB-A, IEEE802.11 a/b/g/n/ac - optional wireless adapter required
	USB	Type A x 2 (PC-less presentation or wireless network) Type B x 1 (Remote control mouse or PC screen display)
Microphone In	3.5mm mini jack x 1	
Control Terminals	9-pin D-sub x 1 (RS-232 control)	
Power Supply	AC100-120V / AC220-240V, 50/60Hz	
Power Consumption	360W/350W	
Operating Temperature	32°F - 104°F (0°C - 40°C)	
Dimensions (W x D x H)	14.8" x 14.2" x 5.4" (excluding protruding parts) Shipping 22.0" x 19.0" x 8.0"	
Weight	Approximately 9.7 lbs / Shipping 16.0 lbs.	
Approvals	UL 60950-1 / cUL, FCC part 15 subpart B Class B	
Warranty	Five (5) year limited warranty plus Dukane's 1 year Peace of Mind Loaner Program. 5 years or 10,000 hours light source.	
UPC	605194006984	

* Actual lamp life will vary by individual lamp based on environmental conditions, selected operating mode, user settings and usage. Hours of average lamp life specified are not guaranteed and do not constitute part of the product or lamp warranty. Lamp brightness decreases over time.

** Actual filter life will vary by individual filter based on environmental conditions, selected operating mode, user settings and usage. Hours of average filter life specified are not guaranteed and do not constitute part of the product warranty.

