

DW

Series

Intelligent-Weigh™ Washdown Checkweighing Scale



- Ultra-Fast Checkweigher
- Rechargeable Battery
- HI-LO-GO
- Washdown
- lb, g, kg, lb:oz



Weighing Technology

A Higher Level of Precision . . . A Higher Level of Performance

Made in Democratic Taiwan



Weighing Technology

A Higher Level of Precision . . . A Higher Level of Performance

DW

Series

Model	DW-6000E1	DW-15KE	DW-30KE
Capacity	6000 g / 12 lb	15 kg / 33 lb	30 kg / 66 lb
Readability	1 g 0.002 lb 0.05 oz	0.005 kg 0.01 lb 0.2 oz	0.01 kg 0.02 lb 0.5 oz
Divisions	6,000	3,000	
Weighing Units / Functions	g / lb:oz / lb Decimal / checkweighing	kg / lb:oz / lb Decimal / checkweighing	
Stabilization Time (seconds)	< 1		
Tare Range	To capacity by subtraction		
Power Source	Built-in rechargeable battery or external power adapter (included)		
Construction	Stainless steel pan and water resistant ABS housing		
Display	0.75 inch / 19 mm wide viewing angle LED		
Pan Size (W x D)	9.84 x 8.46 inches / 250 x 215 mm		
Overall Dimensions (W x D x H)	10.62 x 10.9 x 5.7 inches / 270 x 278 x 145 mm		
Operating Environment	32 °F to 104 °F / 0 °C to 40 °C non condensing R.H. ≤ 95%		
Net Weight	8.5 lb / 3.7 kg		
Shipping Weight	11 lb / 5 kg		
IP Ratings / Approvals	IP 66		

Features	Benefits
HI-LO-GO indicators with configurable buzzer output	Ideal for portion control or checkweighing
Washdown design to IP 66	Can be used in wet conditions
Heavy duty construction	Will withstand harsh industrial operation
Fast reaction time	Allows fast throughput
Sealed electronics	Improved water and dust resistance
Moisture detection desiccant inside	Alerts to moisture inside scale
Low profile, compact size	Uses less counter space
Low battery indicator / charge status indicator	Alerts you to charge the battery, saving downtime
Adjustable feet and spirit level	Scale remains level for accurate results on uneven surfaces – anti slip
LED Display	Can be read even in poor lighting conditions
Easy calibration function	Ensures accuracy
Reads in grams, pounds, and pounds:ounces	Flexibility in operation
Zero tracking	Ensures that you always start weighing at zero
Automatic power save / standby indicator	Conserves battery power
Built-in rechargeable battery or external power adapter	Portability – battery lasts minimum of 150 hours
In-use cover	Keeps scale clear of contamination