CERTIFICATION



©II 2G Ex ia op is IIC T4 Gb

FEATURES & FUNCTIONS

- High accuracy
- Handy size
- Digital display also for over-head measurement
- Types of measurement revolution, speed
- Measurement range 3 ... 99.999 rpm

STANDARD DELIVERY

- A2109/LSR
- Batteries
- Adaption wheel
- Carrying case
- Calibration statement
- Instruction manual

Laser-Tachometer A2109/LSR FOR ZONE 1

CONTACTLESS AND PRECISE

The A2109/LSR is ideal for fast laser-accurate measurement of the revolution of a shaft (either with or without contact) and speed (utilising the special adapter) in Zone 1. The simple 3 push-button operation and the large clearly-readable display with over-head facility enables a wide, flexible field of application. This light-weight device provides an easy one handed operation and facilitates the carrying-out of measurement, after which it can be stowed away in the tool box or jacket pocket. For boiler mixers, the rotor speed can be read from the drive shaft at a safe distance and documented. Motor revolutions can be acquired contactlessly in the immediate vicinity without having to open or remove safety fittings such as covers or protective grills. The duration of pulses or the intervals between them can be simply, easily and accurately ascertained. Data can be simply acquired within Ex-protected areas without having to switch machines off because laser-accurate measurements can be made at a safe


distance through protective devices thus complying with safety regulations. The transport speed of conveyor belts can be exactly measured using the add-on adapter and thus directly recorded in the documentation.

OPERATION AND DISPLAY

- ON button Auto-Off after 1 min.
- HOLD function for 1 min. after releasing button
- Programming function using 3 buttons
- Statistic functions (min./max./average)
- 5 digit
- Large display
- LOW-batt. display
- Pulse recognition
- Function mode



FLEXIBLE MEASUREMENT IN ZONE 1



ACCESSORIES

ARTICLE NO.	PRODUCT DESCRIPTION	
A0003007 😉	Accessory reflective tape scotchlite 3290 white 5x (2.5 x 15) cm	
A0003008	UKAS Calibration – 8 calibration points: rpm 6, 60, 600, 3000, 6000, 15000, 30000, 60000	
A0003009	WKS Calibration	



EMEA

Germany (Headquarters) 1

ecom instruments GmbH Industriestraße 2 97959 Assamstadt Phone +49 62 94 42 24-0 Fax +49 62 94 42 24-100 sales@ecom-ex.com

Benelux ²

ecom instruments BV
Watertoren 45c
3247 CL Dirksland, Netherlands
Phone +31 1 87 60 59 16
Fax +31 1 87 60 33 47
info.nl@ecom-ex.com
²also responsible for Belgium and
Luxemburg

France ³

ecom Nied sarl

4 Rue Ettore Bugatti
67201 Eckbolsheim
Phone +33 3 88 76 46 84
Fax +33 3 88 76 02 85
info.fr@ecom-ex.com

3 also responsible for Algeria, Egypt, Morocco, Libya and Tunisia

Italv

Via Gandhi, 15 Galleria 20017 Rho (MI) Phone +39 02 93 90 92 16 Fax +39 02 93 90 62 97 info.it@ecom-ex.com

ecom instruments srl

Switzerland

ecom instruments GmbH Merkurstraße 2 6210 Sursee Phone +41 4 19 21 60 00 Fax +41 4 19 22 00 08 info.ch@ecom-ex.com

United Kingdom

ecom instruments ltd A310, The Wilton Centre, Redcar, TS10 4RF United Kingdom Phone +44 1642 46 54 00 Fax +44 1642 46 54 02 info.uk@ecom-ex.com

Nordics

ecom instruments GmbH Postbox 304 2970 Hørsholm Denmark Phone +45 28 252 575 info.nordics@ecom-ex.com

Middle East

ecom instruments fze P.O. Box 8918 Saif-Zone, Sharjah, UAE Phone +971 6 5 57 34 30 Fax +971 6 5 57 34 31 info.uae@ecom-ex.com

Americas

USA

ecom instruments Inc. 1779 Westborough Drive, Suite 102 Katy, Texas 77449 Phone +1 281 496 59 30 Fax +1 281 496 23 21 sales.us@ecom-ex.com

Asia

South East Asia

ecom instruments (SEA) Pte Ltd.
12 Arumugam Road
#05-11 Lion Building B
Singapore 409958
Phone +65 61 00 33 29
Fax +65 63 99 33 29
info.sq@ecom-ex.com

