

Magnet-Ex12

CERTIFICATION



Ⓔ II 2 G Ex ia IIC T4



Class I, Division 1, Groups A,B,C,D T6
Class I, Zone 0, AEx ia IIC T6

STANDARD DELIVERY

- Magnet-Ex 12
- Batteries
- Instruction manual
- Ex-Certificate
- EU Declaration of conformity

FEATURES & FUNCTIONS

- Highly sensitive probe point
- No contact with test object required
- Resistant to dirt
- Optical indication
- Built-in test magnet for testing Magnet-Ex 12 and for battery check

Magnet Probe **Magnet-Ex12** FOR ZONE 1

DETECTING MAGNETIC FIELDS

Magnet-Ex 12 is a pencil sized magnet probe, designed to detect magnetic fields in hazardous areas. Within seconds it is possible to detect whether or not a solenoid valve is electrically activated.

Connection to electronic circuitry or opening of terminal boxes is rendered unnecessary.

The highly sensitive probe point of the Magnet-Ex 12 only needs to be brought near the coil of a solenoid valve, if a magnetic field is detected, the test tip illuminates red. In the same manner tests can be carried out on flowmeters or any other equipment that is working magnetically, even when located in hazardous areas.

The Magnet-Ex 12 comes with an integral test magnet that is securely fitted in such a way that it cannot be easily lost. Using this magnet, tests can be carried out to establish the working state of both unit and batteries.

After any check the Magnet-Ex 12 will automatically switch off if it is no longer being used. This ensures a long battery life.

The clip attached to the instrument's side secures it from accidental loss and allows the maintenance engineer to easily carry it at all times.

HIGHLY SENSITIVE TIP FOR TESTING



TECHNICAL DATA	
Ambient temperature	-20 °C ... +50 °C
Storage temperature	-40 °C ... +60 °C
Magnetic field types	alternating, direct and permanent fields
Detection	no contact with test object required
Indication	optical, built-in LED
Power supply	2 x LR03 (AAA) according to IEC, type approved
Casing material	metal (plastic probe point)
Dimensions	150 x 18 mm (L x Ø)
Weight	approx. 60 g (batteries included)
IP protection class	IP 54

EMEA

Germany (Headquarters) ¹

ecom instruments GmbH
Industriestraße 2
97959 Assamstadt
Phone +49 62 94 42 24-0
Fax +49 62 94 42 24-100
sales@ecom-ex.com

¹ also responsible for Austria

Benelux ²

ecom instruments BV
Watertoren 45c
3247 CL Dirksland, Netherlands
Phone +31 1 87 60 59 16
Fax +31 1 87 60 33 47
info.nl@ecom-ex.com

² also responsible for Belgium and
Luxemburg

France ³

ecom Nied sarl
4 Rue Ettore Bugatti
67201 Eckbolsheim
Phone +33 3 88 76 46 84
Fax +33 3 88 76 02 85
info.fr@ecom-ex.com

³ also responsible for Algeria, Egypt, Mo-
rocco, Libya and Tunisia

Italy

ecom instruments srl
Via Gandhi, 15 Galleria
20017 Rho (MI)
Phone +39 02 93 90 92 16
Fax +39 02 93 90 62 97
info.it@ecom-ex.com

Switzerland

ecom instruments GmbH
Merkurstraße 2
6210 Sursee
Phone +41 4 19 21 60 00
Fax +41 4 19 22 00 08
info.ch@ecom-ex.com

United Kingdom

ecom instruments ltd
A310, The Wilton Centre,
Redcar, TS10 4RF
United Kingdom
Phone +44 1642 46 54 00
Fax +44 1642 46 54 02
info.uk@ecom-ex.com

Nordics

ecom instruments GmbH
Postbox 304
2970 Hørsholm
Denmark
Phone +45 28 252 575
info.nordics@ecom-ex.com

Middle East

ecom instruments fze
P.O. Box 8918
Saif-Zone, Sharjah, UAE
Phone +971 6 5 57 34 30
Fax +971 6 5 57 34 31
info.uae@ecom-ex.com

Americas

USA

ecom instruments Inc.
1779 Westborough Drive, Suite 102
Katy, Texas 77449
Phone +1 281 496 59 30
Fax +1 281 496 23 21
sales.us@ecom-ex.com

Asia

South East Asia

ecom instruments (SEA) Pte Ltd.
12 Arumugam Road
#05-11 Lion Building B
Singapore 409958
Phone +65 61 00 33 29
Fax +65 63 99 33 29
info.sg@ecom-ex.com

