

Vertical Markets



K-12



Higher-Ed



Corporation

Product Specifications

Sensor	1/3" 13MP CMOS	Image Rotation	0° / 180° / Flip / Mirror
Total Pixels	3840 x 2160	Video / Audio Recording	Ladibug™ Software
Output Resolution	4K(2160p), 1600x1200, 1080p,720p, XGA, 960x540, 640x480, 640x360	Freeze	Yes
Frame Rate	30fps for 2160p 60fps for 1080p / 720p	Pan	Yes
Sensor Zoom	2x for 1080p (1920x1080) 3x for 720p (1280x720) 3x for XGA (1024x768)	Mask / Spotlight	Ladibug™ Software
Mechanical Zoom	7x	USB Image Transmission	USB 3.0
Close-up	2.4" (60 mm)	Image Capture	Single or Continuous Capturing (via Software)
Shooting Area Max.	16.8" x 12.6" (428 mm x 321 mm)	Driver	UVC / UAC
Lamp	LED Lamp	Free Lumens™ Software	Support Windows 10, 8, 7, Mac OS X, Chrome OS
Arm	Joint-free Gooseneck	Anti-Theft	Kensington Anti-Theft Lock Device
Power	USB Bus Power	VESA Mount	Yes, 75 mm x 75 mm
Output	USB 3.0 (Compatible with USB2.0)	Included Accessories	USB 3.0 Cable
Control	USB	Sharpness	MTF 1000 Line
Built-in Microphone	Yes	Power Consumption	2.25W (Maximum)
Auto Tune	Yes, One Button for Optimization Image	Weight	2.65 lbs (1.2 kg)
Focus Mode	Auto / Manual	Dimensions: (LxWxH)	Folded : 9.3" x 4.2" x 11" (236 x 106 x 280 mm) Open : 13.8" x 4.2" x 15" (350 x 106 x 380 mm)

Compatible Software

zoom



Cisco
webex

Microsoft Teams

BlueJeans
by Verizon

GoToMeeting by LogMeIn

Jitsi Meet

Google Meet

Vidyo®

User Interface



Kensington
Lock Slot

USB 3.0

Lumens®

Lumens Integration, Inc.
4116 Clipper Court
Fremont, CA, 94538
Phone: +1-866-600-0988
Fax: +1-510-252-1389

Lumens Europe
De Nayerstraat 17 9470
Denderleeuw Belgium
Phone : +32-473-58-38-95
Fax : +32-2-452-76-00



www.MyLumens.com