

# Specifications

INTERFACE	
<b>Output</b>	1 HDMI 1.4
<b>Control</b>	1 IR Extender (3.5mm) 1 RS-232 (3-pin Terminal Block) 8 Trigger (10-pin Terminal Block) 1 USB 2.0 (Type-A) 2 Ethernet (RJ-45)
<b>Reserved Port</b>	1 RS-232 (5-pin Terminal Block)
VIDEO	
<b>Output Signal Type</b>	HDMI 1.4 1080p60
AUDIO	
<b>HDMI</b>	LPCM (8 Channels) / Bitstream / HD Bitstream
POWER	
<b>Power Supply</b>	5V/2.6A DC (Locking) PoE (802.3af)
<b>Power Consumption</b>	2.99W
ENVIRONMENTAL	
<b>Operating Temperature</b>	0°C ~ 40°C
<b>Operating Humidity</b>	20~80%, non-condensing
<b>Storage Temperature</b>	-40°C ~ 60°C
<b>Storage Humidity</b>	90%, non-condensing
ENCLOSURE	
<b>Housing</b>	Metal
<b>Weight</b>	0.55lbs (0.25kg)
<b>Dimensions (W×H×D)</b>	Case Only: 9.11" x 0.98" x 4.25" (231.5mm x 25mm x 108mm) All Inclusive: 9.11" x 0.98" x 4.61" (231.5mm x 25mm x 117mm)



Lumens Integration, Inc.  
4116 Clipper Court  
Fremont, CA, 94538  
Phone : +1-866-600-0988  
Fax : +1-510-252-1389

Lumens Europe  
De Nayerstraat 17 9470  
Denderleeuw Belgium  
Phone : +32-473-58-38-95  
Fax : +32-2-452-76-00



[www.MyLumens.com](http://www.MyLumens.com)