

## m70L-D - 70" High Performance LCD Monitor



The Planar m70L-D is a commercial-grade 70" LCD display featuring full high definition for signage applications. The m70L-D combines a customer-centric suite of features and high 24x7 reliability into a display solution that is ideal for mission critical installations. Additional features of the Planar m70L-D include ambient light control, industrial metal bezel for durability, DVI and VGA inputs, and RS-232 control. The Planar m70L-D offers portrait and landscape orientation flexibility as well as high brightness up to 600 nits.

### Specifications

<b>Model (Family)</b>	m70L-V (M-Series)
<b>Display Resolution</b>	1920 x 1080p
<b>Aspect Ratio</b>	16:9
<b>Display Technology</b>	Commercial-grade Direct-view LCD
<b>Screen Size</b>	Diagonal: 70" (177.8 cm); W x H: 61" x 34.3" (155 cm x 87.2 cm)
<b>Cabinet Dimensions (W x H x D)</b>	65.5" x 38.8" x 5.8" (166.4 cm x 98.4 cm x 14.8 cm)
<b>Screen Brightness (typical)</b>	600 cd/m <sup>2</sup>
<b>Response Time</b>	8 ms
<b>Contrast Ratio</b>	1500:1
<b>Full viewing angle</b>	178°
<b>Colors</b>	16.7 million
<b>Color Gamut</b>	72% NTSC, 100% EBU
<b>Backlight</b>	CCFL
<b>Backlight life (1/2 brightness)</b>	50,000 hours

<b>Line Voltage</b>	100-120/200-240VAC 50/60Hz (auto switching)
<b>Power Consumption</b>	~720 watts
<b>Operating Environments</b>	Temperature: 0-35° C (32-86° F) Humidity: 20-80% RH non-condensing
<b>Safety regulations</b>	Complies with EN60950, FCC Class A, CE, EN55022 (CISPR22)
<b>Data Inputs</b>	VGA (640x480) to full HD (1080p); DSUB15-pin connector; DVI-D (with loop through)
<b>Video Inputs (optional)</b>	Composite video (NTSC, PAL, SECAM) RCAx1; Component video (NTSC, PAL, VGA-1080p) RCAx3; S-Video (NTSC, PAL) Mini DIN 4-pin connector; SDI (NTSC, PAL, 720, 1080i) BNCx1 (with loop through)
<b>Video Inputs</b>	Composite video (NTSC, PAL, SECAM) RCAx1; Component video (NTSC, PAL, VGA-1080p) RCAx3; S-Video (NTSC, PAL) Mini DIN 4-pin connector; SDI (NTSC, PAL, 720, 1080i) BNCx1 (with loop through)
<b>Frame Lock</b>	50-65Hz
<b>Display Control</b>	RS-232 (with loop out) and IR remote
<b>Optional Accessories</b>	VESA wall mount adapters, table stand
<b>Big Picture</b>	Integrated
<b>Wallnet</b>	Supported
<b>Mullion Width (edge to active area)</b>	49.25 mm horizontal, 50 mm vertical
<b>Mounting Pattern</b>	VESA MIS-F, 600/600
<b>Power Management</b>	DPMS (standby, suspend)