

MODEL		CB651Q	CB751Q	CB861Q
LCD MODULE	Panel Technology		IPS	
	Viewable Image Size	65"	75"	86"
	Native Resolution		3840 x 2160	
	Brightness (Typical)		350 cd/m <sup>2</sup>	
	Contrast Ratio (Typical)	1200:1	1100:1	1200:1
	Viewing Angle		178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR>10	
	Aspect Ratio		16:9	
	Displayable Colors		Over 1.07 Billion	
	Orientation		Landscape	
	Panel Haze (%)		28	
CONNECTIVITY	Input Terminals		HDMI 2.0 x 3	
	Digital		VGA mini 15pin D-SUB, HDCP 2.2/1.4	
	Analog		Audio Mini-Jack, HDMI Audio x3	
	Audio		LAN (100Mbit), IR Remote, RS232C	
	External Control		USB 2.0 x6	
	Data		None	
	Output Terminals		Audio Mini-Jack, SPDIF (Optical)	
	Digital		LAN	
	Analog		Anti-glare protective glass, 10pt writing/ 20pt use IR touch, Windows 7/8/8.1/10, Android, Mac OS X, Ubuntu, Chrome	
	Audio			
POWER CONSUMPTION	On (Typ/Max Brightness/ Overall Max)	160W	210W	365W
	Network Standby		2W	
	Normal Standby		0.5W	
	Current Rating	4.0A@100V, 1.6A@240V	4.3A@100V, 1.8A@240V	6.2A@100V, 2.5A@240V
	Speaker Rating		Integrated 12W + 12W	
PHYSICAL SPECIFICATIONS	Bezel Width (L/R, T/B)		0.71/0.71in, 0.71, 1.77in	
	Net Dimensions (Without stand; W x H x D)	58.6 x 35.31 x 3.44in / 1488.4 x 896.9 x 87.4mm	67.3 x 40.16 x 3.42in / 1709.4 x 1020 x 86.9mm	77.05 x 45.66 x 3.42in / 1957 x 1159.8 x 86.9mm
	Net Weight (Without Stand)	86.3lb / 39.1kg	115.9lb / 52.6kg	148.4lb / 67.3kg
	VESA Hole Configuration	600x400 M8x4	800x400 M8x4	800x600 M8x4
ENVIRONMENTAL CONDITIONS	Operating Temperature		0 to 40C (32 to 104F)	
	Operating Humidity		10-90%	
	Operating Altitude		5000m(16404ft)	
LIMITED WARRANTY		3 years		
ADDITIONAL FEATURES	Mosaic Canvas whiteboard software, Mosaic Connect wireless presentation software, Ethernet Control and Communication, RS-232 Control and Communication, OPS Expansion Slot, Fixed/Variable Audio Out, Built-In Speakers, LED Backlighting		Anti-Glare protective glass w/ IR touch, touch support 10pt writing/20pt use, Built in SoC including Internet browser and Mosaic Canvas/Connect collaborative software	
SHIPS WITH	Power Cord, HDMI cable, 2 passive pens, Wireless Remote Control, AAA Batteries, Setup Manual, Wall mount		3m AC Power Cord, 1.8m HDMI cable, IR Remote Control, Batteries, 3 passive pens, Flat slim style wall mount	
OPTIONAL ACCESSORIES	OPS-AI7W-IS, OPS-AI5W-IS, OPS-AI3W-IS, OPS-APIS-PS, Motorized cart		All OPS Option Cards, NP05LM1 adds wireless Internet connectivity, SMK-6586 mobile cart with motorized height adjust	



MultiSync, NaViSet and TileMatrix are trademarks or registered trademarks of NEC Display Solutions, Ltd. in Japan, the United States and other countries. The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. DisplayPort and DisplayPort Compliance Logo are trademarks owned by the Video Electronics Standards Association in the United States and other countries. HDBaseT™ and the HDBaseT Alliance logo are trademarks of the HDBaseT Alliance. CRESTRON and CRESTRON ROOMVIEW are trademarks or registered trademarks of Crestron Electronics, Inc. AMX is a trademark or registered trademark of AMX in the United States and other countries. VESA is a trademark of a nonprofit organization, Video Electronics Standard Association.  
All other trademarks are the property of their respective owners. The images in this brochure are samples.  
All specifications are subject to change without notice.