

PS2

Series

Intelligent-Weigh™ Stainless Steel Washdown Bench Scale



- Heavy Duty All Stainless Steel Construction
- Rechargeable Battery
- Large Backlit LCD Display
- Stainless Steel Load Cell



Washdown



Weighing Technology

A Higher Level of Precision . . . A Higher Level of Performance

Made in Democratic Taiwan



Weighing Technology

A Higher Level of Precision . . . A Higher Level of Performance

PS2

Series

Model	PS2-6000	PS2-12K	PS2-30K
Capacity	6,000 g / 13.2 lb	12 kg / 26.4 lb	30 kg / 66 lb
Readability	1g / 0.002 lb / 0.05 oz	0.002 kg / 0.005 lb / 0.1 oz	0.005 kg / 0.01 lb / 0.2 oz
Divisions	6,000		
Weighing Units / Functions	g, lb, lb: oz / accumulation		
Stabilization Time	< 1.5 seconds		
Tare Range	To capacity by subtraction		
Power Source	Built-in rechargeable battery or external power adapter (included)		
Construction	Stainless steel indicator, base and load cell		
Display	1 inch / 25.4 mm wide viewing angle LCD backlit display		
Platform Size (W x D x H)	11 x 13 x 3.7 inches / 280 x 330 x 95 mm		
Dimensions (W x D x H)	11 x 13 x 17.9 inches / 280 x 330 x 455 mm		
Operating Environment	32 ° F to 104 ° F non condensing R.H. ≤ 85%		
Net Weight	14.5 lb / 6.6 kg		15.1 lb / 6.9 kg
Shipping Weight	18 lb / 8.1 kg		21 lb / 9.5 kg
NEMA / IP Rating	IP 67		

Features	Benefits
All stainless steel platform, pillar, indicator, load cell and base	Easy to clean for food processing or harsh environments / washdown resistant
Heavy duty construction	Will withstand harsh industrial operation
Sealed electronics	Improved water and dust resistance
Low profile	Easy to load and unload – platform only 3.7 inches / 95 mm high
Reads in grams, pounds and pounds:ounces	Flexibility of operation
Built-in rechargeable battery or external power adapter	Portability – battery lasts a minimum of 100 hours (without backlight)
Accumulation function	Allows you to add together consecutive weights to arrive at a total
Zero tracking	Assures that you always start weighing at zero
Automatic power save	Conserves battery power
Low battery indicator / charge status indicator	Alerts you to charge the battery, saving downtime
Easy calibration function	Ensures accuracy
Adjustable stainless steel feet with rubber inserts	Scale remains level for accurate results on uneven working surfaces – anti-slip
Wide angle LCD display with backlight	Can be seen from a wide viewing angle
Gravitational correction software	Enables you to input different G acceleration factors